

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

L'Oreal USA Products, Inc.
133 Terminal Avenue
Clark, NJ 07066

L'Oreal Canada
4895 rue Hickmore
Ville St-Laurent, H4T 1K5
Canada

Emergency Telephone Number

1-800-535-5053 US (International: 352-323-3500)
In Canada – 1-613-996-6666 (Canutec) (*666 cellular)

For further information:

1-732-499-2741

Poison Control Number: 412-390-3326

**Product Name: Kiehl's Dermatologist Solutions Powerful-Strength
Line-Reducing Concentrate**

Recommendations on use: Personal care product used on the skin for cosmetic effect.

Restrictions on use: Avoid fire, flame, heat and other sources of ignition. For external use only. Use only as directed. Liquid dispensed from the container is considered combustible until dry.

SECTION 2: HAZARDS IDENTIFICATION

Signal word: WARNING

Symbol	Classification	Hazard Statement	Prevention Statements
No Symbol	Flammable Liquids Category 4	Combustible Liquid	<ul style="list-style-type: none"> Keep away from flames and hot surfaces. No smoking. Wear nitrile or vinyl protective gloves. Eye protection appropriate for the manufacturing operation being performed should be used (goggles or face shield).

This material is considered hazardous by the US Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200)

General Precautionary Statements: Keep out of reach of children. Read label/insert before use.

Hazards Not Otherwise Classified: None.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Only hazardous constituents associated with the product are listed below

INGREDIENT:	CAS NO.	% WT
Glycerin	56-81-5	≤ 15.0%
Dodecamethylpentasiloxane	141-63-9	≤ 13.3%

SECTION 4: FIRST AID MEASURES

Response Statements:

IF IN EYES: If eye irritation occurs: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing until material is sufficiently removed from the eye. **If eye irritation persists:** Get medical advice/attention.

IF ON SKIN: If skin irritation occurs: Wash with plenty of water. **If skin irritation persists:** Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove person to fresh air and keep in a position comfortable for breathing. Call a Poison Control Center if you feel unwell.

IF SWALLOWED: Do not induce vomiting. Never give anything by mouth to an unconscious individual. Consult a physician or Poison Control Center immediately.

SYMPTOMS/EFFECTS: None expected.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS: Consult product labeling. No special advice.

SECTION 5: FIRE-FIGHTING MEASURES

Notes for Non-Emergency Personnel:

EXTINGUISHING MEDIA: In case of fire: Use carbon dioxide, dry chemical and/or foam to extinguish. Water spray may be used to soak other materials surrounding the product, to prevent the spread of the fire. Selection of a fire extinguisher should also be appropriate to address the location of the fire and equipment involved. Please review the tools available at your location to ensure proper availability of equipment.

Notes for those trained to participate in an emergency:

SPECIAL FIRE FIGHTING PROCEDURES: Treat as a combustible liquid. Follow National Fire Protection Association Guidelines or local guidelines appropriate for emergency response. Minimize all sources of static electricity.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Observe all appropriate precautions for handling combustible materials.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal degradation may produce oxides of carbon, silicone, hydrocarbons and/or derivatives.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Notes for non-emergency personnel:

Consult trained response personnel for clean-up of large spills or locations where providing preliminary control of the chemical release is hazardous. Hazardous locations include areas where ignition sources cannot be controlled. Isolate the area and deny entry to unnecessary and unprotected personnel. Sections 2, 5, 7 and 8 of this document should be consulted upon use of material, to become knowledgeable of the material's hazards and how to control risks associated with handling combustible liquids.

If the location is not hazardous and only a small amount of material is released, control the spill using absorbent pads while wearing the protective equipment as noted below. Clean the area with detergent and water. Prohibit discharge to drains, soil, surface and ground waters. Dispose in accordance with Section 13 of this document.

PERSONAL PROTECTIVE EQUIPMENT: Nitrile or vinyl gloves, safety glasses/goggles, protective clothing (e.g. apron) may be required for clean-up of large spills. Respiratory protection is typically not necessary, but may be used depending upon the size of the spill and occupational exposure limits. Respiratory protection may include the use of organic vapor cartridges. Refer to Section 8 for additional information.

Notes for those trained to participate in an emergency:

ACCIDENTAL RELEASE MEASURES: Eliminate all sources of ignition. Dike and contain the free liquid and absorb on vermiculite or spill pillows/pads. Place spent absorbents in UN specification drums for disposal. All precautions associated with controlling a combustible liquid should be employed during clean-up. Wash area completely with water. Take care to avoid contact with wet surfaces or walkways that may become slick when residue is present. Prohibit discharge to drains, soil, surface and ground waters.

Recommendations for personal protective equipment selection are noted above. Non-sparking tools should be utilized in all clean-up associated with combustible liquids. Dispose in accordance with section 13 of this document.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING:

Do not eat, drink or smoke while working with hazardous materials. Employees should be advised to wear appropriate protective equipment in the manufacturing environment. See section 8 of this document for protective equipment selection. Do not expose to heat or flame. All manufacturing should be performed indoors, in an enclosed environment free from uncontrolled ignition sources. Employees should be advised not to handle combustible products in close proximity to incompatible materials. Use only non-sparking tools. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge.

Maintain a clean work environment which includes use of properly functioning containers, proper housekeeping practices.

CONDITIONS FOR SAFE STORAGE:

Storage precautions for unpackaged product (manufacturing environment): Store in a well-ventilated place and keep cool. Keep containers closed when not in use. Minimize inventory. Use only non-sparking tools. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Appropriate fire suppression and detection equipment should be utilized. Store on spill pallets or other locations where spill containment will be easily accessible.

Storage precautions for packaged product: See consumer packaging.

Keep away from open drains and access to the environment.

Incompatible materials: Oxidizing agents. Store away from incompatible materials.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS: These criteria have been published by the referenced authority to establish exposure limits in the work environment. Employee work areas should be monitored to ensure that permissible limits are not exceeded during the work day. These references do not coincide with product use. These references are meant to be in association with the manufacturing environment.

OCCUPATIONAL EXPOSURE VALUES:

Component Name (CAS-No.)	Reference	TWA		STEL/CEILING	
		ppm	mg/m ³	ppm	mg/m ³
Glycerin (mist) 56-81-5	OSHA PEL	--	15*/5**	--	--
	ACGIH TLV	--	--	--	--
	NIOSH REL	--	--	--	--

Notes: *(OSHA) – Total Dust
**(OSHA) – Respirable Fraction

No occupational exposure values have been published for other constituents noted in Section 3.

WORK HYGIENIC PRACTICES: Ensure all work surfaces are maintained, to prevent contamination.

ENGINEERING CONTROLS: None required for product use. For handling large quantities of material, such as in the manufacturing of product, ventilation should be utilized. This ventilation should be compatible with the control of combustible materials. Exhaust ventilation should be utilized to maintain air concentrations of material below the occupational exposure guidelines noted above.

Local exhaust ventilation is not typically required for product use. For handling large quantities of material, such as in the manufacturing of product -- Local Exhaust: Explosion proof. Mechanical (general): Explosion proof.

PERSONAL PROTECTIVE EQUIPMENT: Consistent with good hygiene practices, personal protective equipment (PPE) should be used in conjunction with other control measures including engineering controls, ventilation and isolation. See also Section 5 of this document for PPE advice, in the event of an emergency.

Eye/Face Protection (Non-Emergency): None required for product use. For handling of large quantities of liquid material, safety glasses with side shields/goggles are recommended.

Skin Protection (Non-Emergency): None required for product use. For handling large quantities of material, such as in product manufacturing, nitrile or vinyl gloves should be considered for use. Tyvek clothing may also be suitable for handling large quantities of material in the manufacturing environment.

Respiratory Protection (Non-Emergency): Respiratory protection is not required for product use. For manufacturing of product, respiratory protection may be considered. Ensure that the respirator meets current local occupational health and safety standards. Organic vapor cartridges should be utilized with filtering respiratory protection.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Cream – White		
ODOR:	Not Available		
ODOR THRESHOLD:	Not Available		
pH:	Not Applicable		
MELTING/FREEZING POINT:	F: Not Available	C: Not Available	
BOILING POINT:	F: > 212	C: > 100	
FLASH POINT:	F: 194.4	C: 90.2	METHOD USED: Closed cup
EVAPORATION RATE:	Not Available (Butyl acetate = 1)		
FLAMMABILITY:	Not Applicable to Liquids		
FLAMMABLE LIMITS IN AIR:	Not Available		
VAPOR PRESSURE (mmHg):	@ 70F: Not Available	@ 21 C: Not Available	
VAPOR DENSITY (AIR = 1):	@ 70F: Not Available	@ 21 C: Not Available	
RELATIVE DENSITY (H2O = 1):	0.94 – 0.98		

SOLUBILITY IN WATER: Not Available
PARTITION COEFFICIENT: Not Available
AUTOIGNITION TEMPERATURE: Not Available
DECOMPOSITION TEMPERATURE: Not Available
VISCOSITY: Not Available

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY: Material is not considered reactive under typical handling and storage conditions.

STABILITY: Product is stable.

POSSIBILITY OF HAZARDOUS REACTIONS: None known. Hazardous polymerization is not expected to occur.

CONDITIONS TO AVOID: Heat, fire, flame and other sources of ignition.

INCOMPATIBILITY (MATERIAL TO AVOID): Oxidizers, acids, and bases.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal degradation may produce oxides of carbon, silicone, hydrocarbons, and/or derivatives.

SECTION 11: TOXICOLOGICAL INFORMATION

Where information is not listed specifically for constituents, published information was not available.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS:

SKIN CORROSION/IRRITATION: None expected.

SERIOUS EYE DAMAGE/IRRITATION: None expected

RESPIRATORY/SKIN SENSITIZATION: None expected

INGESTION: Harmful if swallowed

INHALATION: None expected

ROUTES OF EXPOSURE: Inhalation, ingestion, eyes, skin

SYMPTOMS: None expected.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known.

ACUTE TOXICOLOGY DATA FOR COMPONENTS

Material	Route	Species	Test Results
Glycerin	Oral LD50	Rat	27,200 mg/kg bw
Glycerin	Dermal LD50	Rabbit	> 18,700 mg/kg bw
Glycerin	LC ₅₀ (1h)	Rat	> 570 mg/m ³ air
Dodecamethylpentasiloxane (RA L3)	Oral LD ₅₀	Rat (OECD 423)	> 2,000 mg/kg bw
Dodecamethylpentasiloxane	Dermal LD ₅₀	Rat (OECD 402)	> 2,000 mg/kg bw
Dodecamethylpentasiloxane (RA L4)	LC ₅₀ (6 hr)	Rat (OECD 440 eq.)	> 5,000 mg/m ³ air

Note: RA L3 – Read Across Octamethyltrisiloxane
RA L4 – Read Across Decamethyltetrasiloxane

Skin Corrosion/Irritation:

Glycerin: Not Irritating (Rabbit)
Dodecamethylpentasiloxane: Not Irritating (Rabbit, OECD 404)

Serious Eye Damage/Irritation:

Glycerin: Not Irritating (Rabbit)
Dodecamethylpentasiloxane: Slightly Irritating (Rabbit, EPA OPPTS 870.2400) – RA L4

Respiratory Irritation:

No Data

Skin Sensitization:

Glycerin: Not Sensitizing (Guinea Pig)
Dodecamethylpentasiloxane: Not Sensitizing (Guinea Pig, OECD 406) – RA L3

CHRONIC HEALTH HAZARDS:

REPEAT DOSE TOXICITY:

NOAEL (Glycerin, oral): 8,000 mg/kg bw/d (2yr) (Rat)
NOAEL (Glycerin, inhalation): 167 mg/m³ air (90d) (Rat, OECD 413 eq.)
NOAEL (Dodecamethylpentasiloxane, oral): ≥1,000 mg/kg bw/d (28d) (Rat, OECD 407 eq.)

CARCINOGENICITY:

Component Name (CAS-No.)	OSHA	ACGIH	NTP	IARC
None established	--	--	--	--

MUTAGENICITY:

Glycerin: A variety of *in vitro* tests have produced negative results.
Dodecamethylpentasiloxane: A variety of *in vitro* tests have produced negative results. – RA L4

REPRODUCTIVE TOXICITY:

Glycerin: NOAEL: 2,000 mg/kg/day (Rat) – No effects on fertility
Dodecamethylpentasiloxane: NOAEC: ≥ 400 ppm (Rat, OECD 422) – No effects on reproduction – RA L4

DEVELOPMENTAL TOXICITY/TERATOGENICITY:

Glycerin: NOAEL: 1,310 mg/kg/day (Rat) – No effects on development
Dodecamethylpentasiloxane: NOAEC: ≥ 400 ppm (Rat, OECD 422) – No effects on development – RA L4

SECTION 12: ECOLOGICAL INFORMATION

Contact with the environment should be avoided. Spills and leaks should be immediately cleaned up and removed. All precautions should be taken to prevent contact with the environment. Published information regarding ingredients listed on this document area found below; where data is not listed, documentation was unavailable.

ACUTE AND PROLONGED TOXICITY TO FISH

INGREDIENT NAME	TEST	RESULT	SPECIES	EXPOSURE
Glycerin	LC ₅₀	54,000 mg/L	Oncorhynchus mykiss	96 h
Dodecamethylpentasiloxane	LC ₅₀ (OECD 203)	> 75 ng/L	Oncorhynchus mykiss	96 h

ACUTE TOXICITY TO AQUATIC INVERTEBRATES

INGREDIENT NAME	TEST	RESULT	SPECIES	EXPOSURE
Glycerin	LC ₅₀	54,000 mg/L	Oncorhynchus mykiss	96 h

TOXICITY TO AQUATIC PLANTS

INGREDIENT NAME	TEST	RESULT	SPECIES	EXPOSURE
Glycerin	EC ₃	> 10,000 mg/L	Scenedesmus quadricauda	8 d
Dodecamethylpentasiloxane RA – L4	EC ₅₀ (OECD 201)	> 2.2 µg/L	Pseudokirchneriella subcapitata	72 h

TOXICITY TO MICROORGANISMS

INGREDIENT NAME	TEST	RESULT	SPECIES	EXPOSURE
Glycerin	NOEC	> 10,000 mg/L	Pseudomonas putida	16 h
Dodecamethylpentasiloxane RA – L4	EC ₅₀ (OECD 201)	> 2.2 µg/L	Pseudokirchneriella subcapitata	72 h

PERSISTENCY AND DEGRADABILITY:

Glycerin: Readily Biodegradable – 92% (30d) – OECD 301
Dodecamethylpentasiloxane: Not Readily Biodegradable – OECD 310 – 0% (28d) – RA L3

BIOACCUMULATIVE POTENTIAL:

Glycerin: log Pow: -1.76; BCF: 3.162 – Not expected to bioaccumulate
Dodecamethylpentasiloxane: BCF: 1,240 – 1,430 (OECD 305) – Potential to bioaccumulate

SECTION 13: DISPOSAL CONSIDERATIONS

Those responsible for the performance of disposal, recycling or reclamation activities should refer to Section 8 of this document for advice on personal protective equipment and exposure controls.

WASTE DISPOSAL CONTAINERS: Appropriate US DOT containers should be utilized which may include fiberboard boxes for products and metal or plastic drums for liquids. These containers should meet the packaging specifications required for DOT compliance.

WASTE DISPOSAL METHOD: As manufactured, this product does not exhibit any RCRA characteristics of hazardous waste. Controlled incineration at a hazardous waste facility is the recommended technology for treatment and disposal. This material must not be disposed through sewage.

RCRA HAZARD CLASS: NOT APPLICABLE

Follow all local governmental requirements intended for disposal.

SECTION 14: TRANSPORT INFORMATION

North American Ground Transportation

- **IN CONSUMER PACKAGING:** Not regulated

In accordance with US Department of Transportation 49 CFR 173.150(f), products associated with this document have been determined to be *Combustible Liquids* and are therefore exempt from the US DOT Hazardous Materials Shipping Regulations.

- **OTHER THAN CONSUMER PACKAGING: *For containers >450 L (119 gallons)***
 UN ID Number: NA1993
 Proper Shipping Name: Combustible liquid, n.o.s.
 Technical Name: Polysiloxane
 Hazard Class: Not applicable
 Packing Group: III
 Label Statements: None



**Product Name: Kiehl's Dermatologist Solutions
Powerful-Strength Line-Reducing
Concentrate**

Transport Via Water

- **IN CONSUMER PACKAGING:** Not Regulated
- **OTHER THAN CONSUMER PACKAGING:** Not Regulated

Transport Via Air (Domestic/International)

- **IN CONSUMER PACKAGING:** Not Regulated
- **OTHER THAN CONSUMER PACKAGING:** Not Regulated

Please be aware of carrier transport variations before shipping hazardous materials.

SECTION 15: REGULATORY INFORMATION

National Fire Protection Association Codes: Health: 0 Fire: 2 Reactivity: 0 Other: None

Workplace Hazardous Materials Identification System: Class B, Division 3 – Combustible Material

This regulatory information represents the product, in its consumer packaging.

SECTION 16: OTHER INFORMATION

PREPARATION INFORMATION: This is the first issuance of this document.

Author: Ronald Weslosky (Corporate Regulatory Services)