

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard 2024 (29 CFR 1910.1200) and Canada Hazardous Products Act (HPA) and the
Hazardous Products Regulation (HPR), as amended

Revision date 13-Jan-2026

Revision Number 4

1. Identification

Product identifier

Product Name OPI Nail Lacquers Colors

Other means of identification

Product Code(s) 1588074

UN number or ID number UN1263

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Nail polish/lacquer

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Name Lighthouse Digital Commerce/Jade

Supplier Address

15402 N Nebraska Ave
Suite 100
Lutz
FL
33549
US

Emergency telephone number

Supplier Phone Number Phone:813-374-8906
Fax:936-582-0250

24 Hour Emergency Phone Number 800-634-0075

Emergency Telephone No information available

2. Hazard(s) identification

Classification of the substance or mixture

Flammable liquids	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Category 3 Target organ effects: Narcotic effects.	
Specific target organ toxicity (repeated exposure)	Category 2

Label elements

**Danger****Hazard statements**

Highly flammable liquid and vapor.
Causes serious eye irritation.
May cause an allergic skin reaction.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements - Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves, protective clothing, eye protection and face protection.
Wash face, hands and any exposed skin thoroughly after handling.
Contaminated work clothing should not be allowed out of the workplace.
Use only outdoors or in a well-ventilated area.
Do not breathe dust.
Ground and bond container and receiving equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Use explosion-proof electrical, ventilating and lighting equipment.
Keep cool.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.
Specific treatment (see supplemental first aid instructions on this label).

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice and attention.

Skin

IF ON SKIN: Wash with plenty of water and soap.
If skin irritation or rash occurs: Get medical advice and attention.
Take off contaminated clothing and wash it before reuse.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor if you feel unwell.

Fire

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Precautionary Statements - Storage

Store locked up.
Store in a well-ventilated place. Keep container tightly closed.

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

Hazards classified under paragraph (d)(1)(ii) of 1910.1200

No information available.

Other information

May be harmful if swallowed. May be harmful if inhaled. Causes mild skin irritation. Harmful to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Ethyl acetate	141-78-6	30	-	-
Butyl acetate	123-86-4	30	-	-
Tosylamide/formaldehyde resin	25035-71-6	8	-	-
Nitrocellulose	9004-70-0	8	-	-
Isopropyl alcohol	67-63-0	8	-	-
Acetyl tributyl citrate	77-90-7	8	-	-
Triphenyl phosphate	115-86-6	0.1	-	-
Ci 77820	7440-22-4	0.1	-	-
Ci 77266	1333-86-4	0.1	-	-
Adipic acid/neopentyl glycol/trimellitic anhydride copolymer	28407-73-0	0.1	-	-

4. First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms	Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation.
Effects of Exposure	May cause adverse reproductive effects - such as birth defect, miscarriages, or infertility. May cause damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

5. Fire-fighting measures

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous combustion products Carbon oxides.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage**Precautions for safe handling**

Advice on safe handling Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat,

hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Remove contaminated clothing and shoes.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up.

8. Exposure controls/personal protection

Control Parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Ethyl acetate 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m ³
Butyl acetate 123-86-4	TWA: 50 ppm STEL: 150 ppm	TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm 10% LEL TWA: 980 mg/m ³ TWA: 400 ppm STEL: 500 ppm STEL: 1225 mg/m ³
Triphenyl phosphate 115-86-6	TWA: 3 mg/m ³	TWA: 3 mg/m ³ (vacated) TWA: 3 mg/m ³	TWA: 3 mg/m ³ ; IDLH: 1000 mg/m ³
Ci 77820 7440-22-4	TWA: 0.1 mg/m ³ dust and fume	TWA: 0.01 mg/m ³ (vacated) TWA: 0.01 mg/m ³	TWA: 0.01 mg/m ³ ; dust TWA: 0.9 µg/m ³ ; nanoparticles <100 nm IDLH: 10 mg/m ³ dust
Ci 77266 1333-86-4	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³ ; TWA: 0.1 mg/m ³ ; Carbon black in presence of Polycyclic aromatic hydrocarbons PAH IDLH: 1750 mg/m ³

Chemical name	Alberta	British Columbia	Ontario	Quebec
Ethyl acetate	TWA: 400 ppm;	TWA: 150 ppm;	TWA: 400 ppm;	TWAEV: 400 ppm;

141-78-6	TWA: 1440 mg/m ³ ;			TWAEV: 1440 mg/m ³ ;
Butyl acetate 123-86-4	TWA: 150 ppm; TWA: 713 mg/m ³ ; STEL: 200 ppm; STEL: 950 mg/m ³ ;	TWA: 50 ppm; STEL: 150 ppm;	TWA: 50 ppm; STEL: 150 ppm;	TWAEV: 50 ppm; STEV: 150 ppm;
Isopropyl alcohol 67-63-0	TWA: 200 ppm; TWA: 492 mg/m ³ ; STEL: 400 ppm; STEL: 984 mg/m ³ ;	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;	TWAEV: 200 ppm; STEV: 400 ppm;
Triphenyl phosphate 115-86-6	TWA: 3 mg/m ³ ;	TWA: 3 mg/m ³ ;	TWA: 3 mg/m ³ ;	TWAEV: 3 mg/m ³ ;
Ci 77820 7440-22-4	TWA: 0.1 mg/m ³ ;	TWA: 0.01 mg/m ³ ; STEL: 0.03 mg/m ³ ;	TWA: 0.1 mg/m ³ ; dust and fume	TWAEV: 0.1 mg/m ³ ;
Ci 77266 1333-86-4	TWA: 3.5 mg/m ³ ;	TWA: 3 mg/m ³ ; inhalable	TWA: 3 mg/m ³ ; inhalable particulate matter	TWAEV: 3 mg/m ³ ; inhalable dust

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
Ethyl acetate	TWA: 400 ppm;	TWA: 400 ppm;	TWA: 400 ppm;	TWA: 400 ppm;
Butyl acetate	TWA: 50 ppm; STEL: 150 ppm;	TWA: 50 ppm; STEL: 150 ppm;	TWA: 50 ppm; STEL: 150 ppm;	TWA: 50 ppm; STEL: 150 ppm;
Isopropyl alcohol	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;
Triphenyl phosphate	TWA: 3 mg/m ³ ;	TWA: 3 mg/m ³ ;	TWA: 3 mg/m ³ ;	TWA: 3 mg/m ³ ;
Ci 77820	TWA: 0.1 mg/m ³ ; dust and fume	TWA: 0.1 mg/m ³ ; dust and fume	TWA: 0.1 mg/m ³ ; dust and fume	TWA: 0.1 mg/m ³ ; dust and fume
Ci 77266	TWA: 3 mg/m ³ ; inhalable particulate matter	TWA: 3 mg/m ³ ; inhalable fraction	TWA: 3 mg/m ³ ; inhalable particulate matter	TWA: 3 mg/m ³ ; inhalable particulate matter

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
Ethyl acetate	TWA: 400 ppm; STEL: 500 ppm;	TWA: 400 ppm;	TWA: 400 ppm; STEL: 500 ppm;	TWA: 400 ppm; TWA: 1400 mg/m ³ ; STEL: 400 ppm; STEL: 1400 mg/m ³ ;
Butyl acetate	TWA: 150 ppm; STEL: 200 ppm;	TWA: 50 ppm; STEL: 150 ppm;	TWA: 150 ppm; STEL: 200 ppm;	TWA: 150 ppm; TWA: 710 mg/m ³ ; STEL: 200 ppm; STEL: 950 mg/m ³ ;
Isopropyl alcohol	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;	TWA: 400 ppm; TWA: 980 mg/m ³ ; STEL: 500 ppm; STEL: 1225 mg/m ³ ; Sk
Triphenyl phosphate	TWA: 3 mg/m ³ ; STEL: 6 mg/m ³ ;	TWA: 3 mg/m ³ ;	TWA: 3 mg/m ³ ; STEL: 6 mg/m ³ ;	TWA: 3 mg/m ³ ; STEL: 6 mg/m ³ ;
Ci 77820	TWA: 0.1 mg/m ³ ; STEL: 0.3 mg/m ³ ;	TWA: 0.1 mg/m ³ ; dust and fume	TWA: 0.1 mg/m ³ ; STEL: 0.3 mg/m ³ ;	TWA: 0.01 mg/m ³ ; STEL: 0.03 mg/m ³ ;
Ci 77266	TWA: 3.5 mg/m ³ ; STEL: 7 mg/m ³ ;	TWA: 3 mg/m ³ ; inhalable particulate matter	TWA: 3.5 mg/m ³ ; STEL: 7 mg/m ³ ;	TWA: 3.5 mg/m ³ ; STEL: 7 mg/m ³ ;

Note See section 16 for terms and abbreviations.

Other information on limit values Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Biological occupational exposure limits

Chemical name	ACGIH
Isopropyl alcohol 67-63-0	40 mg/L - urine (Acetone) - end of shift at end of workweek
Triphenyl phosphate 115-86-6	60 % of baseline - plasma (Butyrylcholinesterase activity) - end of shift 70 % of baseline - red blood cells (Acetylcholinesterase activity) - end of shift

Appropriate engineering controls

Engineering controls Showers
 Eyewash stations
 Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Tight sealing safety goggles.

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Antistatic boots. Chemical resistant apron. Wear fire/flame resistant/retardant clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. Use appropriate respiratory protection. Consult with an industrial hygienist to determine the appropriate respiratory protection for your specific use of this material.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid
Color No information available
Odor (includes odor threshold) Odorless
 Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Boiling point (or initial boiling point or boiling range)	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	-4 °C / 25 °F	No data available
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
SADT (°C)	No data available	None known
pH	No data available	
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Solubility	No data available	None known

Water solubility	No data available	
Partition coefficient n-octanol/water (log value)	no data	
Vapor pressure (includes evaporation rate)	No data available	None known
Evaporation rate	No data available	None known
Density and/or relative density	1.0	
Bulk density	No data available	
Liquid Density	No data available	
Relative vapor density	No data available	None known
Particle characteristics		None known
Particle Size	No data available	
Particle Size Distribution	No data available	
Other information		
Miscible	No	

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Hazardous polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	None known based on information supplied.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness. May be harmful if inhaled.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. May cause sensitization by skin contact. (based on components). Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Prolonged contact may cause redness and irritation. Causes mild skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation.
Acute toxicity	No information available.

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	2,957.40 mg/kg
ATEmix (dermal)	34,501.50 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-vapor)	31.70 mg/l
ATEmix (inhalation-dust/mist)	7.08 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl acetate	= 5620 mg/kg (Rat)	> 18000 mg/kg (Rabbit)	= 4000 ppm (Rat) 4 h
Butyl acetate	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	>20 mg/L (Rat) 4 h
Nitrocellulose	> 5 g/kg (Rat)	-	-
Isopropyl alcohol	4710 - 5840 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	> 10000 ppm (Rat) 6 h
Acetyl tributyl citrate	> 31500 mg/kg (Rat)	-	-
Triphenyl phosphate	= 3500 mg/kg (Rat)	> 10000 mg/kg (Rabbit)	> 200000 mg/m ³ (Rat) 1 h
Ci 77820	> 2000 mg/kg (Rat)	> 2000 mg/kg (rat)	> 5.16 mg/L (Rat) 4 h
Ci 77266	> 10000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 4.6 mg/m ³ (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Causes mild skin irritation.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes serious eye irritation.
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No information available.
Carcinogenicity	Based on available data, the classification criteria are not met. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Nitrocellulose	-	Group 2A - Probably carcinogenic to humans	-	X
Isopropyl alcohol	A4 - Not classifiable as a human carcinogen	Group 3 - Not classifiable as to its carcinogenicity to humans	-	X
Triphenyl phosphate	A4 - Not classifiable as a human carcinogen	-	-	-
Ci 77266	A3 - Confirmed animal carcinogen (with unknown relevance to humans)	Group 2B - Possibly carcinogenic to humans	-	X

Reproductive toxicity	Contains a known or suspected reproductive toxin. Classification based on data available for ingredients. Suspected of damaging fertility or the unborn child.
STOT - single exposure	May cause drowsiness or dizziness.
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	No information available.

12. Ecological information**Ecotoxicity** Harmful to aquatic life with long lasting effects.**Aquatic ecotoxicity****Component Information**

Chemical name	Fish	Crustacea	Algae/aquatic plants	Toxicity to microorganisms
Ethyl acetate	96h LC50: 220 - 250 mg/L (Pimephales promelas) 96h LC50: = 484 mg/L (Oncorhynchus mykiss) 96h LC50: 352 - 500 mg/L (Oncorhynchus mykiss)	48h EC50: = 560 mg/L (Daphnia magna)	-	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h
Butyl acetate	96h LC50: = 100 mg/L (Lepomis macrochirus) 96h LC50: 17 - 19 mg/L (Pimephales promelas)	-	72h EC50: = 674.7 mg/L (Desmodesmus subspicatus)	EC50 = 70.0 mg/L 5 min EC50 = 82.2 mg/L 15 min EC50 = 959 mg/L 18 h EC50 = 98.9 mg/L 30 min
Isopropyl alcohol	96h LC50: = 9640 mg/L (Pimephales promelas) 96h LC50: = 11130 mg/L (Pimephales promelas) 96h LC50: > 1400000 µg/L (Lepomis macrochirus)	48h EC50: = 13299 mg/L (Daphnia magna)	96h EC50: > 1000 mg/L (Desmodesmus subspicatus) 72h EC50: > 1000 mg/L (Desmodesmus subspicatus)	-
Acetyl tributyl citrate	96h LC50: 38 - 60 mg/L (Lepomis macrochirus)	-	-	-
Triphenyl phosphate	96h LC50: 0.28 - 0.5 mg/L (Oncorhynchus mykiss) 96h LC50: 0.81 - 0.94 mg/L (Pimephales promelas) 96h LC50: 0.53 - 0.8 mg/L (Pimephales promelas) 96h LC50: 0.47 - 1.04 mg/L (Lepomis macrochirus) 96h LC50: = 1.2 mg/L (Oryzias latipes)	48h EC50: 0.86 - 1.2 mg/L (Daphnia magna)	96h EC50: 0.6 - 4 mg/L (Pseudokirchneriella subcapitata)	-
Ci 77820	96h LC50: 0.00155 - 0.00293 mg/L (Pimephales promelas) 96h LC50: = 0.0062 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.064 mg/L (Lepomis macrochirus)	48h EC50: = 0.00024 mg/L (Daphnia magna)	-	-

Persistence and degradability No information available.

Bioaccumulative potential

Chemical name	Partition coefficient	Bioconcentration factor (BCF)	Trophic magnification factor (TMF)
Ethyl acetate	0.73	30	-
Butyl acetate	2.3	-	-
Isopropyl alcohol	0.05	-	-
Acetyl tributyl citrate	4.92	-	-
Triphenyl phosphate	4.63	193	-

Mobility in soil No information available.

Other adverse effects No information available.

13. Disposal considerations

Disposal methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

California waste information This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information

DOT

UN number or ID number UN1263
 Proper shipping name PAINT
 Transport hazard class(es) 3
 Packing group II
 Reportable quantity (lbs) Butyl acetate: RQ (lb)= 5000.00, Ethyl acetate: RQ (lb)= 5000.00
 Reportable quantity (lbs) (calculated) Butyl acetate: RQ (lb)= 16667.00, Ethyl acetate: RQ (lb)= 16667.00
 Reportable quantity (kg) (Butyl acetate: RQ (kg)= 2270.00, Ethyl acetate: RQ (kg)= 2270.00)
 Reportable quantity (kg) (calculated) Butyl acetate: RQ (kg)= 7566.67, Ethyl acetate: RQ (kg)= 7566.67
 DOT Marine Pollutant NP
 Description UN1263, PAINT, 3, II, Limited Quantity
 Special Provisions 149, 367, 383, B52, B131, IB2, T4, TP1, TP8, TP28
 Emergency Response Guide Number 128

TDG

UN number or ID number UN1263
 UN proper shipping name PAINT
 Transport hazard class(es) 3
 Packing group II
 Description UN1263, PAINT, 3, II, Limited Quantity

MEX

UN number or ID number	UN1263
UN proper shipping name	PAINT
Transport hazard class(es)	3
Packing group	II
Description	UN1263, PAINT, 3, II
Special Provisions	163, 367

ICAO (air)

UN number or ID number	UN1263
UN proper shipping name	PAINT
Transport hazard class(es)	3
Packing group	II
Description	UN1263, PAINT, 3, II, Limited Quantity
Special Provisions	A3, A72, A192

IATA

UN number or ID number	UN1263
UN proper shipping name	PAINT
Transport hazard class(es)	3
Packing group	II
Environmental hazards	No
ERG Code	3L
Description	UN1263, PAINT, 3, II, Limited Quantity

IMDG

UN number or ID number	UN1263
UN proper shipping name	PAINT
Transport hazard class(es)	3
Packing group	II
Marine pollutant indicator	NP
EmS-No.	F-E <u>S-E</u> S-E
Underlined EMS codes indicate additional advice is given in the emergency response procedures	
Description	UN1263, PAINT, 3, II, Limited Quantity

15. Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture****International Regulations**

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Contact supplier for inventory compliance status.

DSL/NDL Contact supplier for inventory compliance status.

EINECS/ELINCS Contact supplier for inventory compliance status.

ENCS Contact supplier for inventory compliance status.

IECSC Contact supplier for inventory compliance status.

KECL Contact supplier for inventory compliance status.

PICCS Contact supplier for inventory compliance status.

AIIC Contact supplier for inventory compliance status.

NZIoC Contact supplier for inventory compliance status.
TCSI Contact supplier for inventory compliance status.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing Chemicals Inventory
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AIIC - Australian Inventory of Industrial Chemicals
NZIoC - New Zealand Inventory of Chemicals
TCSI - Taiwan Chemical Substance Inventory

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Isopropyl alcohol	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Butyl acetate	5000 lb	-	-	X

CAA (Clean Air Act)

This product does not contain any substances regulated as pollutants pursuant to Clean Air Act (CAA).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs
Butyl acetate	5000 lb	-
Ethyl acetate	5000 lb	-

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
Ci 77266	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Butyl acetate	X	X	X
Ethyl acetate	X	X	X
Isopropyl alcohol	X	X	X
Nitrocellulose	X	X	X
Ci 77820	X	X	X
C.I. 42090	-	X	-

Polydimethylsiloxane	X	-	-
Chromium oxide greens	X	X	X
Ci 77266	X	X	X
Propyl acetate	X	X	X
Triphenyl phosphate	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA Health hazards 2 Flammability 3 Instability 0 Special hazards -
HMIS Health hazards 2* Flammability 3 Physical hazards 0 Personal protection X
 Chronic Hazard Star Legend * = Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet

List may include phrases which are not applicable to this product

ACGIH	American Conference of Governmental Industrial Hygienists
ADN	Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Europe)
ADR	Agreement concerning the International Carriage of Dangerous Goods by Road (Europe)
AIIC	Australian Inventory of Industrial Chemicals
ATE	Acute Toxicity Estimate
ASTM	American Society for the Testing of Materials
bar	Biological Reference Values for Chemical Compounds in the Work Area
BAT	Biological tolerance values for occupational exposure
BEL	Biological exposure limits
bw	Body weight
Ceiling	Maximum limit value
CMR	Carcinogen, Mutagen or Reproductive Toxicant
DOT	Department of Transportation (United States)
DSL	Domestic Substances List (Canada)
EmS	Emergency Schedule
ENCS	Existing and New Chemical Substances (Japan)
EPA	Environmental Protection Agency
GHS	Globally Harmonized System
HMIS	Hazardous Materials Identification System
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO	International Civil Aviation Organization
IECSC	Inventory of Existing Chemical Substances in China
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
ISO	International Organization for Standardization
KECI	Korean Existing Chemicals Inventory
LC50	Lethal Concentration to 50% of a test population
LD50	Lethal Dose to 50% of a test population (Median Lethal Dose)
MARPOL	International Convention for the Prevention of Pollution from Ships
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety and Health
n.o.s.	Not Otherwise Specified
NOAEC	No Observed Adverse Effect Concentration
NOAEL	No Observed Adverse Effect Level

NOELR	No Observable Effect Loading Rate
NTP	National Toxicology Program (United States)
NZIoC	New Zealand Inventory of Chemicals
OECD	Organization for Economic Cooperation and Development
OEL	Occupational exposure limits
OSHA	Occupational Safety and Health Administration of the US Department of Labor
PBT	Persistent, Bioaccumulative and Toxic substance
PICCS	Philippines Inventory of Chemicals and Chemical Substances
PMT	Persistent, Mobile and Toxic
PPE	Personal protective equipment
QSAR	Quantitative Structure Activity Relationship
RID	Agreement concerning the International Carriage of Dangerous Goods by Rail (Europe)
SADT	Self-Accelerating Decomposition Temperature
SAR	Structure-activity relationship
SARA	Superfund Amendments and Reauthorization Act
SDS	Safety Data Sheet
SL	Surface Limit
STEL	Short Term Exposure Limit
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
TCSI	Taiwan Chemical Substance Inventory
TDG	Transport of Dangerous Goods (Canada)
TSCA	Toxic Substances Control Act (United States)
TWA	Time-Weighted Average
UN	United Nations
VOC	Volatile organic compounds
vPvB	Very Persistent and Very Bioaccumulative
vPvM	Very Persistent and Very Mobile
As	Allergenic substance
DS	Dermal Sensitizer
Ot	Ototoxicant
pOt	Ototoxicant - potential to cause hearing disorders
PS	Photosensitizer
RS	Respiratory Sensitizer
S	Sensitizer
poS	Sensitizer - capable of causing occupational asthma
Sa	Simple asphyxiant
Sd	Skin designation
pSd	Skin designation - potential for cutaneous absorption
Sdv	Skin designation - vacated
Sk	Skin notation
dSk	Skin notation - danger of cutaneous absorption
pSk	Skin notation - potential for cutaneous absorption

Key literature references and sources for data used to compile the SDS

U.S. Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
U.S. Environmental Protection Agency
Acute Exposure Guideline Level(s) (AELG(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
Japan National Institute of Technology and Evaluation (NITE)
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications
International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program
International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set
United Nations World Health Organization (WHO)

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501.

Revision date 13-Jan-2026

Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet