

SAFETY DATA SHEET

Issuing Date 12-May-2015

Revision Date 12-May-2015

Revision Number 3



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name TIANQIU Alkaline Button Cell LR41H

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Alkaline battery

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name GUANGZHOU TIANQIU ENTERPRISE CO., LTD.

Supplier Address 9/F TianQiu Business Building No.16-30, He Yi Rd., San Yuan Li Ave., GuangZhou China
GUANGZHOU
GUANDONG
510410
CN

Supplier Phone Number Phone:8620-36322277
Fax:8620-3633339
Contact Phone:8613825131170

Supplier Email qd@gztianqiu.com

Emergency telephone number

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.



Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Gases)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (repeated exposure)	Category 2

GHS Label elements, including precautionary statements**Emergency Overview**

Signal word	Danger
Hazard Statements Causes skin irritation Causes serious eye damage May cause damage to organs through prolonged or repeated exposure	
 This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture: the above hazards exist.	
Appearance	Silver
Physical state	Solid
Odor	Odorless

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Use only outdoors or in a well-ventilated area
Wear protective gloves/protective clothing/eye protection/face protection
Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label)
Get medical advice/attention if you feel unwell

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN: Wash with plenty of soap and water
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
Rinse mouth

Precautionary Statements - Storage

None

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

3% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Very toxic to aquatic life with long lasting effects

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Iron	7439-89-6	30 - 60	*
Manganese dioxide	1313-13-9	10 - 30	*
Zinc	7440-66-6	7 - 13	*
Potassium hydroxide	1310-58-3	1 - 5	*
Graphite	7782-42-5	1 - 5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures**General Advice**

This is a battery. In case of rupture:.. Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. Seek immediate medical attention/advice.

Skin contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.

Inhalation

Remove to fresh air. Get medical attention immediately if symptoms occur.



Ingestion Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects Burning sensation.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Hazardous Combustion Products

Carbon oxides.

Physical/Chemical Reaction Properties No data available.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Manganese dioxide 1313-13-9	TWA: 0.02 mg/m ³ Mn TWA: 0.1 mg/m ³ Mn	(vacated) Ceiling: 5 mg/m ³ Ceiling: 5 mg/m ³ Mn	IDLH: 500 mg/m ³ Mn TWA: 1 mg/m ³ Mn STEL: 3 mg/m ³ Mn
Zinc 7440-66-6	STEL: 10 mg/m ³ respirable fraction TWA: 2 mg/m ³ respirable fraction	TWA: 5 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	IDLH: 500 mg/m ³ Ceiling: 15 mg/m ³ dust TWA: 5 mg/m ³ dust and fume STEL: 10 mg/m ³ fume
Potassium hydroxide	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³



1310-58-3 Graphite 7782-42-5	TWA: 2 mg/m ³ respirable fraction all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust
------------------------------------	---	--	---

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection None required for consumer use. If there is a risk of contact: Tight sealing safety goggles.

Skin and body protection None required for consumer use. If there is a risk of contact: Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state	Solid	Odor	Odorless
Appearance	Silver	Odor Threshold	No information available
Color	No information available		
Property	Values	Remarks	Method
pH	No data available	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	



Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	Negligible	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing properties	No data available	

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:.
Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Severely irritating to eyes. Causes serious eye damage. May cause burns. May cause irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation.



Ingestion

Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed. (based on components).

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Iron 7439-89-6	= 984 mg/kg (Rat)	-	-
Manganese dioxide 1313-13-9	= 9000 mg/kg (Rat)	-	-
Potassium hydroxide 1310-58-3	= 214 mg/kg (Rat)	-	-
Graphite 7782-42-5	> 10000 mg/kg (Rat)	-	-

Information on toxicological effects**Symptoms**

Erythema (skin redness). May cause redness and tearing of the eyes. May cause blindness. Burning.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Sensitization**

No information available.

Mutagenic Effects

No information available.

Carcinogenicity

Contains no ingredient listed as a carcinogen.

Reproductive toxicity

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

Chronic Toxicity

Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone marrow and blood-forming system.

Target Organ Effects

Respiratory system. Eyes. Skin. Blood. Central Nervous System (CNS). Central Vascular System (CVS). Kidney. Cardiovascular system. Liver.

Aspiration Hazard

No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

969.00 mg/kg

ATEmix (inhalation-gas)

19,068.00 ppm (4 hr)

ATEmix (inhalation-dust/mist)

6.40 mg/l

ATEmix (inhalation-vapor)

47.00 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Iron 7439-89-6		96h LC50: = 13.6 mg/L (Morone saxatilis)		
Zinc 7440-66-6	96h EC50: 0.11 - 0.271 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.09 - 0.125 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 2.16 - 3.05 mg/L (Pimephales promelas) 96h LC50: 0.211 - 0.269 mg/L (Pimephales promelas) 96h LC50: = 2.66 mg/L (Pimephales promelas) 96h LC50: = 30 mg/L (Cyprinus carpio) 96h LC50: = 0.45 mg/L (Cyprinus carpio) 96h LC50: = 7.8 mg/L (Cyprinus carpio) 96h LC50: = 3.5 mg/L (Lepomis macrochirus) 96h LC50: = 0.24 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.59 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.41 mg/L (Oncorhynchus mykiss)		48h EC50: 0.139 - 0.908 mg/L
Potassium hydroxide 1310-58-3		96h LC50: = 80 mg/L (Gambusia affinis)		

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Manganese dioxide 1313-13-9	<0
Potassium hydroxide 1310-58-3	0.83

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 181

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Zinc 7440-66-6	Ignitable powder Toxic
Potassium hydroxide 1310-58-3	Toxic Corrosive

14. TRANSPORT INFORMATION

DOT
Proper Shipping Name NOT REGULATED
Hazard Class NON REGULATED
 N/A

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA
Proper Shipping Name Not regulated
Hazard Class NON REGULATED
 N/A

IMDG/IMO
Hazard Class Not regulated
 N/A

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies



DSL

All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Manganese dioxide - 1313-13-9	1313-13-9	10 - 30	1.0
Zinc - 7440-66-6	7440-66-6	7 - 13	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Zinc 7440-66-6		X	X	
Potassium hydroxide 1310-58-3	1000 lb			X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Zinc 7440-66-6	1000 lb		RQ 454 kg final RQ RQ 1000 lb final RQ
Potassium hydroxide 1310-58-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Manganese dioxide 1313-13-9			X	X	X
Zinc 7440-66-6	X	X	X	X	
Potassium hydroxide 1310-58-3	X	X	X	X	



Graphite 7782-42-5	X	X	X		
-----------------------	---	---	---	--	--

International Regulations**Mexico****National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Manganese dioxide 1313-13-9 (10 - 30)		Mexico: TWA= 0.2 mg/m ³
Graphite 7782-42-5 (1 - 5)		Mexico: TWA= 2 mg/m ³

*Mexico - Occupational Exposure Limits - Carcinogens***Canada****WHMIS Hazard Class**

Non-controlled

16. OTHER INFORMATION

NFPA	Health Hazards	1	Flammability	0	Instability	0	Physical and Chemical Hazards	-
HMIS	Health Hazards	0	Flammability	0	Physical Hazard	0	Personal Protection	X

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 12-May-2015
Revision Date 12-May-2015
Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet