



## Safety Data Sheet

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

Date of Revision: None  
Revision: 0

### Section 1 - Chemical Product and Company Identification

1.1 Product Name: 2025 WERCS Fuel Stabilizer with Ethanol Armor

1.2 Synonym: Blend

1.3 VP Racing Fuels, Inc., 7124 Richter Road, Elmendorf, TX 78112, 210.635.7744

1.4 Recommended Use: Fuel System Treatment.

1.5 **RESTRICTIONS on USE: THIS FUEL SYSTEM TREATMENT IS FOR GASOLINE ENGINES ONLY**

1.6 Emergency Response Number: CHEMTREC 1-800-424-9300

Local Emergency Telephone Number: 1-703-527-3887

### Section 2 - Hazards Identification

#### 2.1 GHS HAZARD

##### Hazard Classes

Specific Target Organs toxicity single exposure

Specific Target Organs toxicity repeat exposure

Eye Irritation

Skin Irritation

Acute Toxicity Inhalation

Mutagenicity

Carcinogen

Aspiration Hazard

Aquatic Chronic

##### Hazard Categories

Category 3

Category 1

Category 2A

Category 2

Category 4

Category 1B

Category 1B

Category 1

Category 2

GHS Classification Scale 1= severe hazard; 4= slight hazard

2.2 Signal Word: **Danger**

## 2025 WERCS Fuel Stabilizer with Ethanol Armor

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7



Health

Irritant

Aquatic Hazard

### 2.3 Pictograms:

### 2.4 Hazard Statements

#### PHYSICAL HAZARDS:

None

#### HEALTH HAZARDS:

**H304:** May be fatal if swallowed and enters airways.

**H315:** Causes skin irritation.

**H319:** Causes serious eye irritation.

**H332:** Harmful if inhaled.

**H335:** May cause respiratory irritation.

**H336:** May cause drowsiness or dizziness.

**H340:** May cause genetic defects.

**H350:** May cause cancer.

**H372:** Causes damage to organs through prolonged or repeated exposure.

#### ENVIRONMENTAL HAZARDS:

**H411:** Toxic to aquatic life with long-lasting effects.

#### PRECAUTIONARY STATEMENTS:

**P102:** Keep out of reach of children.

**P201:** Obtain special instructions before use.  
**READ SDS BEFORE USING.**

**P202:** Do not handle until all safety precautions have been read and understood.

**P261:** Avoid breathing vapor and mist.

**P264:** Wash hands thoroughly after handling.

**P270:** Do not eat, drink, or smoke when using this product.

**P271:** Use only outdoors or in a well-ventilated area.

**P273:** Avoid release to the environment.

**P280:** Wear protective gloves, clothing, and eye protection.

#### RESPONSE STATEMENTS:

**P301 +P310+ P331: IF SWALLOWED:**

Immediately call the National POISON CENTER at **800-222-1222**. DO NOT induce vomiting.

**P303+P252+P361: IF ON SKIN OR HAIR.** Take off Immediately all contaminated clothing. Rinse skin with water.

**P304+P340: IF INHALED:** Remove to fresh air and keep comfortable for breathing.

## 2025 WERCS Fuel Stabilizer with Ethanol Armor

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

**P305+P351: IF IN EYES: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present, and easy to do so. Continue rinsing.**

**P308+P313: If exposed or concerned, get medical attention.**

**P312: CALL the National POISON CENTER at 800-222-1222 if you feel unwell.**

**P313+P332: If skin irritation occurs. Get medical attention.**

**P313+P337: If eye irritation persists. Get medical attention.**

**P362+P364: Take off contaminated clothing and wash it before reusing.**

**P370+P378: In case of fire, use foam, carbon dioxide, or dry chemical to extinguish the fire.**

**P391: Collect spillage.**

### STORAGE STATEMENTS:

**P403+P235: Store in a well-ventilated place. Keep cool.**

**P405: Store locked up.**

### DISPOSAL STATEMENTS:

**P501: Dispose of content and container following local, regional, national, or international regulations.**

**2.5 Hazards not otherwise classified (HNOC) or not covered by GHS:** Eye irritation from vapor inflammation can occur. When splashed in the eye, the liquid may cause burning pain and transient corneal injury. **IF IN THE EYES: Rinse cautiously with water for at least 15 minutes.** Repeated liquid exposure may cause skin dryness or cracking.

### 2.6 Unknown acute toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity

0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

0 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

## Section 3 - Composition / Information on Ingredients

### 3.1

CAS #	Chemical Name	Synonyms	Percent	Classification
64742-47-8	Distillates (petroleum), hydrotreated light	Hydrotreated light distillate petroleum	80-100	Asp. Tox. 1 H304, Skin Irrit.2 H315, STOT SE H336, Aquatic Chronic 2 H411
Proprietary	Trade Secret	Trade Secret	1-5	Not classified

## 2025 WERCS Fuel Stabilizer with Ethanol Armor

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

Proprietary	Trade Secret	Trade Secret	0.6-1	Eye Irrit 2
64742-95-6	Solvent naphtha (petroleum), light arom.	HFAN	0.5-1	Asp.Tox1 H304, Muta 1B H340 Carc. 1B H350
95-63-6	1,2,4-trimethylbenzene	Pseudocumene	0.1-0.8	Flam. Liq.3 H226, Skin Irrit 2 H315, Eye Irrit 3 H319, Acute Tox,4 H332 STOT SE 3 H335, Aquatic Chronic 2 H411
108-67-8	1,3,5-trimethylbenzene	Mesitylene	0.1-0.5	Flam. Liq. 3 H226, STOT SE 3, aquatic Chronic 2 H411
71-43-2	Benzene	Benzol	0.07-0.1	Flam, Liq. 2 H225, Skin Irrit.2 H315, Eye Irrit. 2 H319. Asp. Tox. 1 H304, Muta 1B H340. Carc.1A H350, STOT RE 1 H372
103-65-1	Propylbenzene	Isocumene	0.01-0.07	Flam. Liq.3 H226, Asp. Tox 1. H304,STOT SE 3 H335, Aquatic Chronic 2 H411
1330-20-7	Xylene	Xylol	0.01-0.07	Flam. Liq.3 H226, Acute Tox. H312, Skin Irrit. 2 H315, Acute Tox.4 H332
611-14-3	2-ethyltoluene	o-Ethyltoluene	0.01-0.07	Flam. Liq.3 H226, Asp. Tox 1. H304
104-76-7	2-ethylhexan-1-ol	2-ethylhexanol	0.01-0.07	Skin Irrit 2 H315, Eye Irrit. H319, Acute Tox, H332, STOT SE3 H335
526-73-8	1,2,3-trimethylbenzene	Hemellitol	0.01-0.07	Flam. Liq. 3 Skin Irrit.2 H315, Eye Irrit. 2 H319

Note: Benzene is a component of Solvent naphtha (petroleum), light arom.

**3.2 Trade Secret Provision and Chemical Concentration Disclosure:** Per OSHA and GHS Regulations, we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a blend and applied to the hazards identified in this Safety Data Sheet.

## Section 4 - First Aid Measures

### 4.1 Description of First Aid Measures

**4.1.1 General information:** Ensure medical personnel know the material(s) involved and take precautions to protect themselves.

**4.1.2 Following Inhalation:** Remove the victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

**4.1.3 Following Skin contact:** Flush skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reusing.

**4.1.4 Following eye contact:** Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

**4.1.5 Following ingestion:** Do NOT induce vomiting. Get medical aid immediately.

## 2025 WERCS Fuel Stabilizer with Ethanol Armor

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

### 4.2 Most important symptoms and effects, both acute and delayed:

**4.2.1:** Contact with the eyes can cause serious irritation. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

**4.2.2:** Prolonged and repeated liquid contact with the skin can cause defatting and drying, leading to irritation and dermatitis.

**4.2.3:** Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting, leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided, as even small quantities can produce chemical pneumonia, pulmonary edema, and even death.

**4.2.4:** Prolonged breathing of high vapor concentrations can produce headaches, dizziness, nausea, and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage, and death resulting from respiratory failure.

**4.3 Indication of any immediate medical attention and special treatment needed:** The severity of the outcome following exposure may be related to the time between the exposure and treatment rather than the amount of the exposure. Therefore, rapid treatment of any exposure is necessary.

Note to Physicians: If you determine that a medical emergency exists. The specific chemical identity is necessary for emergency or first-aid treatment and will be immediately disclosed the specific chemical identity. Call CHEMTREC 800-424-9300 or +1-703-527-3887. We will require a written statement of need and a confidentiality agreement as soon as circumstances permit. In non-emergency situations, we will, upon written request, disclose a specific chemical identity.

## Section 5 - Fire-Fighting Measures

**General fire hazards:** This product is a Class III-B liquid with a flashpoint at or above 200°F (93°C).

### 5.1 Extinguishing media:

**Suitable extinguishing media:** Water fog. Alcohol-resistant foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media:** Do not use a water jet as an extinguisher, as this will spread the fire.

**5.2 Special hazards arising from the substance or mixture:** Vapors may form explosive mixtures with air. Vapors may travel a considerable distance to a source of ignition and flashback. During a fire, gases hazardous to health may be formed.

**5.3 Advice for firefighters:** Firefighters should wear a full-face, self-contained breathing apparatus and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

**Additional information:** Do not release runoff from fire to sewers or waterways.

## Section 6 - Accidental Release Measures

### 6.1 Personal precautions, protective equipment, and emergency procedures:

**6.1.1 For non-emergency personnel:** Keep unnecessary personnel away. Keep people away from and upwind of spills and leaks. Take precautionary measures against static discharge. Eliminate all ignition sources. No smoking, flames, sparks, or flames in the immediate area. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless you

## 2025 WERCS Fuel Stabilizer with Ethanol Armor

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

wear appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

**6.1.2 For emergency responders:** Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the SDS.

**6.2 Environmental precautions:** Avoid direct contact with the material. Stop leaking without risk. Move containers from the spill area. Prevent entry into sewers or waterways.

### 6.3 Methods and materials for containment and cleaning up:

**6.3.1 For containment:** Eliminate all ignition sources (no smoking, flares, sparks, or flames in the immediate area). Keep combustibles such as wood, paper, and oil away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will spread on the water's surface. Prevent entry into waterways, sewers, basements, or confined areas.

#### 6.3.2 For clean-up:

**6.3.2.1 Small spill:** Absorb using earth, sand, or other non-combustible material and transfer to containers for later disposal. Clean the surface thoroughly to remove residual contamination.

**6.3.2.2 Large spill:** Stop the material flow if this is without risk. Contain the spilled material where this is possible. Use a non-combustible material like vermiculite, sand, or earth to soak up the product and place it into a container for later disposal. Following product recovery, flush the area with water.

**6.3.3 Other information:** Never return spills to original containers for reuse. Put material in suitable, covered, labeled containers.

**6.4 Reference to other sections:** For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## Section 7 - Handling and Storage

**7.1 Precautions for safe handling:** Avoid breathing vapors. Avoid contact with eyes, skin, and clothing. Avoid contact with the eyes. Observe good industrial hygiene practices. Provide adequate ventilation. Take precautionary measures against static discharge. Eliminate all ignition sources. No smoking, flames, sparks, or flames in the immediate area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Launder contaminated clothing before reuse. Avoid release to the environment. Observe good industrial hygiene practices.

**7.1.1 Bonding and grounding plastic containers:** This product is a Class III-B liquid with a flashpoint at or above 200°F (93 °C). Combustible liquids are liquids with a flashpoint above 100°F (37.°C) that do not easily ignite. However, if raised to temperatures above its flashpoint, it will release enough vapor to form burnable mixtures with air. Hot combustible liquids can be as serious a fire hazard as flammable liquids.

When bonding and grounding two non-conductive containers, a static electrical charge can be generated when two dissimilar materials (Metal and Plastic) pass quickly by one another.

Many factors affect the size and strength of the static charge or potential that may develop, such as transfer speed, humidity, and container size. The concern is that any static charge between two containers is equalized if not eliminated, so no potential exists for a static discharge between the containers.

Transferring flammable and combustible liquids between small containers may not require special bonding and grounding techniques. As stated in NFPA 77-1993, containers of glass or other non-conductive

## 2025 WERCS Fuel Stabilizer with Ethanol Armor

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

materials of five gallons or less capacity are usually filled without special precautions." However, for larger containers, NFPA 77-1993 suggests that special techniques should be used to handle flammable and combustible liquids in plastic containers with capacities of 5 to 60 gallons.

**7.2 Conditions for safe storage, including incompatibilities:** Store locked up in a cool, dry, well-ventilated place out of direct sunlight. Keep away from heat, sparks, and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a tightly closed container. Store in a. away from incompatible materials (see section 10).

**7.3 Specific end use(s):** For gasoline engines only.

### Section 8 - Exposure Controls / Personal Protection

#### 8.1

Chemical Names	ACGIH- TLV	OSHA - PEL
Distillates (petroleum), hydrotreated light	5mg/m3 TWA	5mg/m3 TWA
Trade Secret	5mg/m3 TWA	5mg/m3 TWA
Trade Secret	10 ppm TWA	None Shown
Solvent naphtha (petroleum), light arom.	5mg/m3 TWA	5mg/m3 TWA
1,2,4-trimethylbenzene	10 ppm TWA	25 ppmTWA
1,3,5-trimethylbenzene	25 ppm TWA	25 ppm TWA
Benzene	0.5 ppm TWA	10 ppm TWA
Propylbenzene	None Shown	None shown
Xylene	100 ppm TWA	100 ppm TWA
2-ethyltoluene	None Shown	None Shown
2-ethylhexan-1-ol	None Shown	None Shown
1,2,3-trimethylbenzene	10 ppm TWA	None Shown

#### 8.2.

**ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits.**

**NOTE: TWA Means** "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour work week, which shall not be exceeded.

**8.3 Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs. Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

**8.4 Contaminated Equipment:** Separate contaminated work clothes from street clothes and launder them before reuse. Remove this material from your shoes and clean your personal protective equipment.

## 2025 WERCS Fuel Stabilizer with Ethanol Armor

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

### 8.5 Personal protective equipment

#### 8.5.1 Respiratory protection

Where risk assessment shows appropriate air-purifying respirators, use a full-face respirator with a multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### 8.5.2 Hand protection

Handle with gloves. Gloves must be inspected before use. Use proper glove removal techniques to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton

Splash contact: Viton

Registered trademark of The Chemours Company FC, LLC.

#### 8.5.3 Eye protection

Face shield and safety glasses: Use eye protection equipment tested and approved under appropriate government standards, such as NIOSH (US) or EN 166(EU).

#### 8.5.4 Skin and body protection

Impervious clothing, flame retardant, antistatic, protective clothing: The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### 8.6 Protective Clothing Pictograms



## Section 9 - Physical and Chemical Properties

### 9.1

**Physical state:** Liquid

**Color:** Various

**Odor:** Solvent Odor

**Odor threshold:** Not Available

**Melting point/freezing point:** Not Available

**Boiling point (or initial boiling point or boiling range):** Not Available

**Flammability:** None

**Lower explosion limit:** Not Available

**Upper explosion limit:** Not Available

**Flashpoint:** 116.6°C c.c. per D93

**Auto-ignition temperature:** Not Available

**Decomposition temperature:** Not Available

**pH:** None

**Kinematic viscosity:** <20.5mm<sup>2</sup>/s @40°C

**Dynamic viscosity:** Not Available

**Solubility:** Insoluble in water

**Partition coefficient n-octanol/water (log value):** Not Available

**2025 WERCS Fuel Stabilizer with Ethanol Armor**  
**Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7**

**Vapor pressure (includes evaporation rate):** Not Available

**Density:** >1 Estimated

**Relative density:** 0.813 @ 15.5°C per D4052

## Section 10 - Stability and Reactivity

**10.1 Stability:** Stable under ordinary conditions of use and storage.

**10.2 Polymerization:** Hazardous polymerization has not been reported.

**10.3 Chemical Incompatibilities:** Strong oxidizing agents.

**10.4 Hazardous Decomposition Products:** Combustion produces carbon monoxide and carbon dioxide.

**10.5 Conditions to Avoid:** Avoid heat, sparks, open flames, and other ignition sources.

## Section 11- Toxicological Information

### 11.1

Acute Toxicity Estimate for this blend (ATE)

ATE (Oral): 3090 mg/kg

ATE (Dermal): 2052 mg/kg

ATE (Inhalation vapor/mist): 4.7 mg/l mist

**11.1.1** OECD Guideline Test results in the European Chemical Agency Database show that no product's components cause Harmful Oral Toxicity.

**11.1.2** OECD Guideline Test results in the European Chemical Agency Database show that no product's components cause Harmful Dermal Toxicity.

**11.1.3** OECD Guideline Test results in the European Chemical Agency Database show that this product's components cause Harmful Inhalation Toxicity.

**11.2 Route of Entry:** Inhalation, Ingestion, Absorption, Skin and Eye Contact

**11.3 Aspiration Hazard:** The European Chemical Agency Database shows that components of this product may be fatal if swallowed and enter the airways.

**11.4 Mutagenicity:** OECD Guideline Test results in the European Chemical Agency Database show that components of this product cause genetic defects.

**11.5 Skin Corrosion/Irritation:** OECD Guideline Test results in the European Chemical Agency Database show that this product's components cause skin irritation. Repeated exposure may cause skin dryness or cracking.

**11.6 Serious Eye Damage/Irritation:** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause serious eye irritation.

**11.7 Reproductive toxicity:** OECD Guideline Test results in the European Chemical Agency Database show that no components of this product cause damage to fertility or the unborn child.

## 2025 WERCS Fuel Stabilizer with Ethanol Armor

**Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7**

**11.8 Skin Sensitisation** OECD Guideline Test results in the European Chemical Agency Database show that no components of this product cause skin sensitivity.

**11.9 Respiratory Sensitisation** OECD Guideline Test results in the European Chemical Agency Database show that no components of this product cause respiratory sensitivity.

**11.10 Specific Target Organ Toxicity (Single exposure):** The European Chemical Agency Database shows that components of this product may damage the central nervous system (CNS) and irritate the respiratory tract.

**11.11 Specific Target Organ Toxicity (Repeated Exposure):** Contains material that may cause damage to the following organs: kidneys, lungs, liver, upper respiratory tract, skin, eyes, and central nervous system (CNS).

**11.12 Signs and Symptoms:** Effects due to exposure may include Headache, Dizziness, Drowsiness, Metabolic Acidosis, Coma, and Seizures. Symptoms may be delayed.

**11.13 Carcinogenicity:** OECD Guideline Test results in the European Chemical Agency Database show that this product's components cause cancer.

## Section 12 - Ecological Information

### 12.1

Product Name	Results	Species	Exposure
Distillates (petroleum), hydrotreated light	No data available		
Trade secret	LC50 10600 mg/l	Fish	96 hours
Trade secret	EC50 169 mg/l	Algae	96 hours
Trade secret	LC50 1300 mg/l	Fish	96 hours
Trade secret	EC50 100 mg/l	Algae	96 hours
Trade secret	EC50 100 mg/l	Daphnia	48 hours
Solvent naphtha (petroleum), light arom.	LL50 9.3 mg/l	Fish	96 hours
Solvent naphtha (petroleum), light arom.	EL50 3.2 mg/l	Daphnia	48 hours
1,2,4-trimethylbenzene	EC50 3.6 mg/l	Daphnia	48 hours
1,3,5-trimethylbenzene	LC50 12.52 mg/l	Fish	96 hours
1,3,5-trimethylbenzene	EC50 6 mg/l	Daphnia	48 hours
1,3,5-trimethylbenzene	ErC50 53 mg/l	Algae	72 hours
Benzene	LC50 5.3 mg/l	Fish	96 hours
Benzene	EC50 8.76 mg/l	Daphnia	48 hours
Benzene	ErC50 29 mg/l	Algae	72 hours
Propylbenzene	No data available		
Xylene	LC50 16.1 mg/l	Fish	96 hours
Xylene	EC50 2.51 mg/l	Daphnia	48 hours
Xylene	EC50 4.73 mg/l	Algae	72 hours
2-ethyltoluene	No data available		
2-ethylhexan-1-ol	LC50 32 mg/l	Fish	96 hours
2-ethylhexan-1-ol	EC50 39 mg/l	Daphnia	48 hours
2-ethylhexan-1-ol	EC50 11.5 mg/l	Algae	72 hours
1,2,3-trimethylbenzene	No data available		

**Toxicity:** OECD Guideline Test results found in the European Chemical Agency Database show that components of this product cause long-term toxicity to aquatic life.

**2025 WERCS Fuel Stabilizer with Ethanol Armor**  
Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

**12.2 Mobility:** Floats on water

**12.3 Persistence/degradability:** Inconclusive technical data.

**12.4 Bioaccumulation:** Inconclusive technical data.

**12.5 Other adverse effects:** Inconclusive technical data.

**Section 13 - Disposal Considerations**

**13.1 Disposal: DO NOT REUSE EMPTY CONTAINER!** The container should be completely emptied before discarding it. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

**Section 14 - Transport Information**

**14.1 US Transport Information**

**Single container less than 119 gallons: Not regulated**

**Section 15 - Regulatory Information**

**15.1 US Regulations**

**The US. Toxic Substances Control Act:** All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

**Toxic Release Inventory (TRI):** This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372):

CAS Number	Chemical Name	Chemical percentage by weight not exceeding
95-63-6	1,2,4-trimethylbenzene	0.6%
1330-20-7	Xylene	0.5%
71-43-2	Benzene	<0.1%

This information must be included in all SDSs copied and distributed for this material.

**CERCLA Hazardous Substances and corresponding RQs:** Benzene 10 lbs. Xylene 100 lbs.

**SARA Community Right-to-Know Program:** All components of this blend.

**Clean Water Act:** None

**Clean Air Act:** None

**OSHA:** All ingredients are regulated by 1910.1200.

**State Regulations**

**California Prop. 65:**



**WARNING:** This product can expose you to chemicals. Benzene CAS # 71-43-2 is known to the State of California to cause cancer and birth defects, or other reproductive harm. CAS # 1330-20-7 Xylene is considered but not listed to cause reproductive toxicity. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**2025 WERCS Fuel Stabilizer with Ethanol Armor**  
**Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7**

Chemicals on the following State Right to Know Lists:

**Massachusetts:** All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements.

**New Jersey:** All components of this product are on the New Jersey inventory or are exempt from Inventory requirements.

**Pennsylvania:** All components of this product are on the Pennsylvania Inventory or are exempt from Inventory requirements.

### Section 16 - Other Information

**16.1 Disclaimer:** The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving it shall determine the product's suitability for their particular purpose and that they assume the risk of its use.

**16.2 References:** European Chemical Agency Database, MSDS, and SDS of chemicals in this mixture.

**16.3 SDS Preparation Date** 05/07/2025

**SDS Previous Issue Date:** None

Prepared by SJC Compliance Education, Inc.  
133 N Friendswood Dr. #181  
Friendswood TX. 77546  
[steve@sjcedu.org](mailto:steve@sjcedu.org)

END OF SAFETY DATA SHEET