

# 上海纳诺微新材料科技有限公司

Shanghai NNW New Materials Technology Co., Ltd.

## Safety Data Sheet

# Permanent Marker Ink

Version:1.1

Creation Date:2023/12/22

Revision Date:2023/12/22

Color: coloured

Country of Destination:US

\*Safety Data Sheet (US Regulations Relating to Labor 29 CFR 1910.1200, and is provided per attached )

### SECTION 1 Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product Name	Permanent Marker Ink
Synonyms	—
CAS NO.	—
Chemical Formula	—

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	To write
Uses advised against	—

#### 1.3 Details of the supplier of the Safety Data Sheet

Name of the company	Shanghai NNW New Materials Technology Co., Ltd.
Address of the company	ROOM 402, Building17, Lane 268, Lingxin Road, Changning District Shanghai, CHINA
Post code	200335
Telephone number	021-64476059
Fax number	021-64476096
Email	sales@nmwchina.com

#### 1.4 Emergency phone number

Emergency phone number	+8613311812200
------------------------	----------------

### SECTION 2 Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to OSHA Hazard Communication Standard (29 CFR 1910.1200)	 <b>GHS02</b>
Information concerning particular hazards for human and environment	H226 Flammable liquid and vapour; Category 3 The product has to be labeled due to the calculation procedure of OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification system	The classification is according to the latest edition of OSHA Hazard Communication Standard (29 CFR 1910.1200), and extended by company and literature data.

#### 2.2 Label elements

<b>Labelling according to OSHA Hazard Communication Standard (29 CFR 1910.1200)</b>	The product is classified and labelled according to the OSHA Hazard Communication Standard (29 CFR 1910.1200)
<b>Hazard pictogram(s)</b>	 <b>GHS02</b>
<b>Signal word</b>	<b>Warning!</b>
<b>Hazard-determining components of labelling</b>	Not Applicable
<b>Hazard statements</b>	H226 Flammable liquid and vapour.

**2.3 Precautionary statements**

➤ **Precautionary statement(s) Prevention**

<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P233</b>	Keep container tightly closed.
<b>P240</b>	Ground and bond container and receiving equipment.
<b>P241</b>	Use explosion-proof [electrical/ventilating/lighting] equipment.
<b>P242</b>	Use only non-sparking tools
<b>P243</b>	Take precautionary measures against static discharge.
<b>P261</b>	Avoid breathing dust/fume/gas/mist/vapours/spray.
<b>P271</b>	Use only outdoors or in a well-ventilated area.
<b>P280</b>	Wear protective gloves/protective clothing/eye protection/face protection.

➤ **Precautionary statement(s) Response**

<b>P303+P340</b>	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
<b>P303+P361+P353</b>	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
<b>P370+P378</b>	In case of fire: Use ... to extinguish.

➤ **Precautionary statement(s) Storage**

<b>P405</b>	Store locked up.
<b>P403+P235</b>	Store in a well-ventilated place. Keep cool.

➤ **Precautionary statement(s) Disposal**

<b>P501</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
-------------	---

**2.4 Other hazards**

**Hazards not otherwise classified (HNOC) :**No further relevant information available.

**SECTION 3 Composition/information on ingredients**

**3.1 Mixtures**

➤ **Description:**Mixture of substances listed.

CAS No	%[weight]	Name
<i>Common ingredients on each color</i>		
65997-05-9	35.0-45.0	<b>Polymerized Rosin</b>
57-55-6	8.0	<b>Propane-1,2-diol</b>
56-81-5	18.0	<b>Glycerol</b>
64-17-5	4.0-19.0	<b>Ethanol</b>
		 Flam Liqid Category 2; H225
107-98-2	14.0	<b>1-methoxypropan-2-ol</b>
		 Flam Liqid Category 3; H226  STOT SE Category 3; H336
<b>Black/Grey</b>		

2650-18-2	2.0	Acid Blue 9
12237-31-9	2.0	Solvent Yellow 79
12227-55-3	2.0	Solvent Red 122
<i>Light red/Red/Dark red</i>		
12227-55-3	8.0-10.0	Solvent Red 122
<i>Light green/Green/Dark</i>		
12237-24-0	3.0-4.0	Solvent Blue 70
12237-31-9	4.0-6.0	Solvent Yellow 79
<i>Light yellow/Yellow/Dark yellow</i>		
12237-31-9	4.0-6.0	Solvent Yellow 79
<i>Light orange/Orange/Dark orange</i>		
12237-31-9	4.0-6.0	Solvent Yellow 79
12227-55-3	2.0-4.0	Solvent Red 122
<i>Light pink/Pink/Dark pink/Rose</i>		
2650-18-2	4.0-6.0	Acid Blue 9
12227-55-3	4.0-6.0	Solvent Red 122
<i>Light purple/Purple/Dark purple</i>		
12237-24-0	3.0-5.0	Solvent Blue 70
12227-55-3	4.0-6.0	Solvent Red 122
<i>Light brown/Brown/Dark brown/Coffee</i>		
12227-55-3	2.0-3.0	Solvent Red 122
12237-24-0	2.0-3.0	Solvent Blue 70
12237-31-9	4.0-5.0	Solvent Yellow 79

**SECTION 4 First aid measures**

**4.1 Description of first aid measures**

<b>General advice</b>	Seek medical attention if necessary. Show this Safety Data Sheet (SDS) to the physician present.
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician if feel uncomfortable.
<b>Skin contact</b>	Take off contaminated clothing and shoes immediately. Wash off with plenty of water for at least 15 minutes and consult a physician if feel uncomfortable.
<b>Ingestion</b>	Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.
<b>Inhalation</b>	Move victim into fresh air. If breathing is difficult, give oxygen. Do not use mouth to mouth resuscitation if victim ingested or inhaled the substance. If not breathing, give artificial respiration and consult a physician immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available

**4.3 Indication of any immediate medical attention and special treatment needed**

<b>Treat symptomatically</b>	Periodic medical surveillance should be carried out on persons in occupations exposed to the manufacture or bulk handling of the product and this should include hepatic function tests and urinalysis examination. [ILO Encyclopaedia]
------------------------------	---

**For acute or short term repeated exposures to ethanol**

<b>1</b>	Acute ingestion in non-tolerant patients usually responds to supportive care with special attention to prevention of aspiration, replacement of fluid and correction of nutritional deficiencies (magnesium, thiamine pyridoxine, Vitamins C and K).
<b>2</b>	Give 50% dextrose (50-100 ml) IV to obtunded patients following blood draw for glucose determination.
<b>3</b>	Move victim into fresh air. If breathing is difficult, give oxygen. Do not use mouth to mouth resuscitation if victim ingested or inhaled the substance. If not breathing, give artificial respiration and consult a physician immediately.
<b>4</b>	Comatose patients should be treated with initial attention to airway, breathing, circulation and drugs of immediate importance (glucose, thiamine).
<b>5</b>	Decontamination is probably unnecessary more than 1 hour after a single observed ingestion. Cathartics and charcoal may be given but are probably not effective in single ingestions.
<b>6</b>	Fructose administration is contra-indicated due to side effects.

## SECTION 5 Firefighting measures

### 5.1 Extinguishing media

<i>Suitable extinguishing media</i>	<i>CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.</i>
<i>Unsuitable extinguishing media</i>	<i>Water with full jet.</i>

### 5.2 Special hazards arising from the substrate or mixture

*May form irritant vapor in air under fire.*

### 5.3 Advice for firefighters

<i>1</i>	<i>As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.</i>
<i>2</i>	<i>Fight fire from a safe distance, with adequate cover.</i>
<i>3</i>	<i>Prevent fire extinguishing water from contaminating surface water or the ground water system.</i>
<i>4</i>	<b>Hazardous Combustion Products:</b> <i>During a fire, smoke may contain the original material in addition to combustion products of varying composition which maybe toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.</i>

## SECTION 6 Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

<i>1</i>	<i>Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.</i>
<i>2</i>	<i>Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.</i>
<i>3</i>	<i>Use personal protective equipment. Avoid breathing vapours, mist, gas or dust.</i>
<i>4</i>	<i>Avoid contact with skin and eyes.</i>

### 6.2 Environmental precautions

<i>1</i>	<i>Do not allow to enter sewers/ surface or ground water.</i>
<i>2</i>	<i>Discharge into the environment must be avoided.</i>

### 6.3 Methods and material for containment and cleaning up

<i>1</i>	<i>Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).</i>
<i>2</i>	<i>Dispose contaminated material as waste according to item 13.</i>
<i>3</i>	<i>Ensure adequate ventilation.</i>

### 6.4 Reference to other sections

<i>1</i>	<i>See section 7 for information on safe handling.</i>
<i>2</i>	<i>See section 8 for information on personal protection equipment.</i>
<i>3</i>	<i>See section 13 for disposal information.</i>

## SECTION 7 Handling and storage

### 7.1 Precautions for handling

➤ **Protective measure**

<i>1</i>	<i>Ensure good ventilation/exhaustion at the workplace.</i>
<i>2</i>	<i>Keep receptacles tightly sealed.</i>
<i>3</i>	<i>Keep away from heat and direct sunlight.</i>
<i>4</i>	<i>Prevent formation of aerosols.</i>
<i>5</i>	<i>Avoid contact with skin and eyes.</i>

➤ **Information about fire - and explosion protection**

1	Keep ignition sources away - Do not smoke.
2	Protect against electrostatic charges.

**7.2 Conditions for safe storage, including any incompatibilities**

<b>Requirements to be met by storerooms</b>	<ul style="list-style-type: none"> <li>➤ Keep containers tightly closed .</li> <li>➤ Keep containers in a dry, cool and well-ventilated place.</li> <li>➤ Keep away from heat/sparks/open flames/hot surfaces.</li> <li>➤ Store away from incompatible materials and food stuff containers.</li> </ul>
<b>Storage incompatibility</b>	<p><b>Ethanol:</b></p> <ul style="list-style-type: none"> <li>➤ Are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents;</li> <li>➤ Reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen;</li> <li>➤ React with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzincs;</li> <li>➤ Dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium;</li> <li>➤ Should not be heated above 49 deg. C. when in contact with aluminium equipment;</li> <li>➤ Toxic gases are formed by mixing azo and azido compounds with acids, aldehydes, amides, carbamates, cyanides, inorganic fluorides, Halogenated;organics, isocyanates, ketones, metals, nitrides, peroxides, phenols, epoxides, acyl halides, and strong oxidising or reducing agents;</li> <li>➤ Flammable gases are formed by mixing azo and azido compounds with alkali metals;</li> </ul>

**7.3 Specific end use(s)**

In addition to use mentioned in the first parts, unforeseen other specific end uses.

**SECTION 8 Exposure controls/personal protection**

**8.1 Components with limit values that require monitoring at the workplace**

<b>Ethanol</b>	
<b>PEL (USA)</b>	Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm
<b>REL (USA)</b>	Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm
<b>TLV (USA)</b>	Short-term value: 1880 mg/m <sup>3</sup> , 1000 ppm
<b>1-methoxypropan-2-ol</b>	
<b>PEL (USA)</b>	Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm
<b>REL (USA)</b>	Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm
<b>TLV (USA)</b>	Short-term value: 1880 mg/m <sup>3</sup> , 1000 pp
<b>Glycerol</b>	
<b>PEL (USA)</b>	Long-term value: 15* 5** mg/m <sup>3</sup> mist; *total dust **respirable fraction
<b>TLV (USA)</b>	TLV withdrawn-insufficient data human occup. exp.
<b>Propane-1,2-diol</b>	
<b>WEEL (USA)</b>	Long-term value: 10 mg/m <sup>3</sup>

**\*Regulatory information**

- PEL (USA): Guide to Occupational Exposure Values (OSHA PELs)
- REL (USA): Guide to Occupational Exposure Values (NIOSH RELs)
- TLV (USA): Guide to Occupational Exposure Values (ACGIH)
- WEEL (USA): Guide to Occupational Exposure Values (AIHA WEELs)

**8.2 Engineering controls**

1	Ensure adequate ventilation, especially in confined areas.
2	Ensure that eyewash stations and safety showers are close to the workstation location.
3	Use explosion-proof electrical/ventilating/lighting/equipment.
4	Set up emergency exit and necessary risk-elimination area.

**8.3 Personal protection equipment**

<b>General requirement</b>	
<b>Eye protection</b>	Tightly fitting safety goggles (approved by EN166(EU) or NIOSH(US)).
<b>Hand protection</b>	Wear protective gloves(such as butyl rubber, passing the tests according to EN 374(EU),US F739 or AS/NZS 2161.1 standard.
<b>Respiratory protection</b>	If exposure limits are exceeded or if irritation or other symptoms are experienced, use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges.
<b>Skin and body protection</b>	Wear fire/flame resistant/retardant clothing and antistatic boots.
<b>Other protection</b>	No special equipment needed when handling small quantities.

## SECTION 9 Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>Appearance</b>	Coloured	<b>Viscosity</b>	<b>Dynamic</b>	Not determined
<b>Physical state</b>	Liquid		<b>Kinematic:</b>	Not determined
<b>Odour</b>	Odourless	<b>Vapour density (Air = 1)</b>		Not determined
<b>Odour threshold</b>	Not determined	<b>Density/Relative density</b>		Not determined
<b>pH (as supplied)</b>	Not determined	<b>Decomposition temperature</b>		Not determined
<b>Melting point/freezing point(°C)</b>	Not determined	<b>Particle Size</b>		Not determined
<b>Flash point(Closed cup, °C)</b>	23-24 °C	<b>Vapour pressure (kPa)</b>		Not determined
<b>Flammability</b>	Flammable liquid	<b>Relative vapor density</b>		Not determined
<b>Evaporation rate</b>	Not determined	<b>Partition coefficient n-octanol/ water</b>		Not determined
<b>Upper Explosive Limit (%)</b>	Not determined	<b>Auto-ignition temperature(°C)</b>		Not determined
<b>Lower Explosive Limit (%)</b>	Not determined	<b>Explosive properties</b>		Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
<b>Self-igniting</b>	Not determined	<b>Oxidising properties</b>		Not determined
<b>Taste</b>	Not determined	<b>Surface Tension (dyn/cm or mN/m)</b>		Not determined
<b>Volatile Component (%vol)</b>	Not determined	<b>Gas group</b>		Not determined
<b>pH as a solution (1%)</b>	Not determined	<b>VOC g/L</b>		Not determined

### 9.2 Other information

No further relevant information available

## SECTION 10 Stability and reactivity

### 10.1 Stability and reactivity

<b>Reactivity</b>	No further relevant information available.
<b>Chemical stability</b>	Stable under proper operation and storage conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reactions known.
<b>Conditions to avoid</b>	Incompatible materials, heat, flame and spark.
<b>Incompatible materials</b>	See section 7.2
<b>Hazardous decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11 Toxicological information

### 11.1 Information on toxicological effects

<b>Permanent Marker Ink</b>	<b>TOXICITY</b>
	Not data available

<b>Propane-1,2-diol</b>	<b>TOXICITY</b> Oral (rat) LD50:>20000 mg/kg Dermal (rabbit) LD50:20800 mg/kg
<b>Ethanol</b>	<b>TOXICITY</b> Oral (mouse) LD50:3450 mg/kg Oral (rat) LD50:7060 mg/kg Oral (rabbit) LD50:6300 mg/kg Inhalation(rat) LC50:20000 mg/l(4h)
<b>Glycerol</b>	<b>TOXICITY</b> Oral (rat) LD50:> 11500 mg/kg Inhalation(rat) LC50: > 5.85mg/l 4h Dermal (guinea pig) LD50: 45 ml/kg
<b>Polymerized Rosin</b>	<b>TOXICITY</b> Oral (rat) LD50:> 2000 mg/kg Dermal (rat) LD50: > 2000 mg/kg
<b>1-methoxypropan-2-ol</b>	<b>TOXICITY</b> Oral(rat)LD50:> 4016mg/kg Inhalation(rat) LC50: 6000-7000mg/l 6h Dermal (rat) LD50: >2000 mg/kg Dermal (rabbit) LD50: 13000 mg/kg
<b>Acid Blue 9</b>	<b>TOXICITY</b> Oral (rat) LD50: >1900 mg/kg

**11.2 Carcinogenicity**

<b>Component</b>	<b>Cas No.</b>	<b>IARC</b>	<b>NTP</b>
<b>Polymerized Rosin</b>	65997-05-9	Not Listed	Not Listed
<b>Ethanol</b>	64-17-5	I	Not Listed
<b>Propane-1,2-diol</b>	57-55-6	Not Listed	Not Listed
<b>Glycerol</b>	56-81-5	Not Listed	Not Listed
<b>1-methoxypropan-2-ol</b>	107-98-2	Not Listed	Not Listed
<b>Acid Blue 9</b>	2650-18-2	Not Listed	Not Listed
<b>Solvent Yellow 79</b>	12237-31-9	Not Listed	Not Listed
<b>Solvent Red 122</b>	12227-55-3	Not Listed	Not Listed
<b>Solvent Blue 70</b>	12237-24-0	Not Listed	Not Listed

**SECTION 12 Ecological information**

**12.1 Toxicity**

<b>Aquatic toxicity</b>	No further relevant information available
<b>Persistence and degradability</b>	No further relevant information available
<b>Bioaccumulative potential</b>	No further relevant information available
<b>Mobility in soil</b>	No further relevant information available
<b>Other adverse effects</b>	No further relevant information available

**12.2 Results of PBT and vPvB assessment**

<b>PBT</b>	Not Available
<b>vPvB</b>	Not Available

**SECTION 13 Disposal considerations**

**13.1 Waste treatment methods**

<b>Product / Packaging disposal</b>	<p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <ol style="list-style-type: none"> <li>1. Do not allow wash water from cleaning or process equipment to enter drains.</li> <li>2. It may be necessary to collect all wash water for treatment before disposal.</li> <li>3. Recycle wherever possible</li> <li>4. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> </ol>
<b>Waste treatment options</b>	Not Available
<b>Sewage disposal options</b>	Not Available

**SECTION 14 Transport information**

**14.1 UN-Number**

<b>ADR/RID/ADN, IMDG, IATA</b>	UN1993
--------------------------------	--------

**14.2 UN proper shipping name**

<b>ADR/RID/ADN, IMDG</b>	FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL), 1-METHOXY-2-PROPANOL)
<b>IATA</b>	FLAMMABLE LIQUID, N.O.S. (ETHANOL, 1-METHOXY-2-PROPANOL)

**14.3 Transport hazard class(es)**

<b>ADR/RID/ADN, IMDG, IATA</b>	
<b>Class</b>	3 Flammable liquids.
<b>Label</b>	3

**14.4 Packing group**

<b>ADR/RID/ADN, IMDG, IATA</b>	III
--------------------------------	-----

**14.5 Environmental hazards**

Not Applicable

**14.6 Special precautions for user**

<b>Warning</b>	Flammable liquids
<b>Hazard identification number (Kemler code)</b>	33
<b>EMS Number:</b>	F-E,S-D
<b>Stowage Category</b>	A

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not Applicable

**14.8 Transport/Additional information**

<b>UN "Model Regulation"</b>	UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL), 1-METHOXY-2-PROPANOL), 3, III
------------------------------	--

**SECTION 15 Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

> SARA

<b>Section 355 (extremely hazardous substances)</b>	None of the ingredient is listed
<b>Section 313 (Specific toxic chemical listings)</b>	None of the ingredient is listed

> TSCA (Toxic Substances Control Act)

<b>Polymerized Rosin</b>	ACTIVE
--------------------------	--------

Ethanol	ACTIVE
Propane-1,2-diol	ACTIVE
Glycerol	ACTIVE
1-methoxypropan-2-ol	ACTIVE
Acid Blue 9	ACTIVE

> Proposition 65

Chemicals known to cause cancer	None of the ingredient is listed
Chemicals known to cause reproductive toxicity for females	None of the ingredient is listed
Chemicals known to cause reproductive toxicity for males	None of the ingredient is listed
Chemicals known to cause developmental toxicity	Ethanol

> Cancerogenity categories

EPA (Environmental Protection Agency)	None of the ingredient is listed
TLV (Threshold Limit Value established by ACGIH)reproductive toxicity for females	Ethanol(A3)
NIOSH-Ca (National Institute for Occupational Safety and Health) reproductive toxicity for males	None of the ingredient is listed

15.2 Chemical safety assessment

A Chemical Safe Assessment has not been carried out.

15.3 International chemical inventory

Component	EINECS	TSCA	DSL	IECSC	NZIoC	PICCS	KECI	AICS
Propane-1,2-diol	Listed	Listed	Listed	Listed	Listed	Listed	Listed	Listed
Ethanol	Listed	Listed	Listed	Listed	Listed	Listed	Listed	Listed
Polymerized Rosin	Listed	Listed	Listed	Listed	Listed	Listed	Listed	Listed
Glycerol	Listed	Listed	Listed	Listed	Listed	Listed	Listed	Listed
1-methoxypropan-2-ol	Listed	Listed	Listed	Listed	Listed	Listed	Listed	Listed
Acid Blue 9	Listed	Listed	Listed	Listed	Listed	Listed	Listed	Listed
Solvent Yellow 79	Not Listed	Not Listed	Not Listed	Listed	Listed	Listed	Listed	Listed
Solvent Red 122	Not Listed	Not Listed	Not Listed	Listed	Listed	Listed	Not Listed	Listed
Solvent Blue 70	Not Listed	Not Listed	Not Listed	Listed	Listed	Listed	Listed	Listed

【EINECS】 European Inventory of Existing Commercial Chemical Substances

【TSCA】 United States Toxic Substances Control Act Inventory

【DSL】 Canadian Domestic Substances List

【IECSC】 China Inventory of Existing Chemical Substances

【NZIoC】 New Zealand Inventory of Chemicals

【PICCS】 Philippines Inventory of Chemicals and Chemical Substances

【KECI】 Existing and Evaluated Chemical Substances

【AICS】 Australia Inventory of Chemical Substances

SECTION 16 Other information

16.1 Information on revision

Creation Date	2023/12/22
Revision Date	2023/12/22
Reason for revision	—

16.2 Full text Risk and Hazard codes

<b>H225</b>	<i>Highly flammable liquid and vapour.</i>
<b>H226</b>	<i>Flammable liquid and vapour.</i>
<b>H336</b>	<i>May cause drowsiness or dizziness.</i>

**16.3 Abbreviations and acronyms**

**Cas** :Chemical Abstracts Service

**PC—TWA**: Permissible Concentration-Time Weighted Average

**PC—STEL**: Permissible Concentration-Short Term Exposure Limit

**IARC**: International Agency for Research on Cancer

**STEL**: Short Term Exposure Limit

**ADR**: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

**IMDG**: International Maritime Code for Dangerous Goods

**IATA**: International Air Transport Association

**GHS**: Globally Harmonised System of Classification and Labelling of Chemicals

**EINECS**: European Inventory of Existing Commercial Chemical Substances

**LC50**: Lethal concentration, 50 percent

**LD50**: Lethal dose, 50 percent

**PBT**: Persistent, Bioaccumulative and Toxic

**vPvB**: very Persistent and very Bioaccumulative

**16.4 Further information**

The contents and format of this SDS are in accordance with 29 CFR 1910.1200.

**DISCLAIMER OF LIABILITY:**

The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.