

SAFETY DATA SHEET

Issuing Date 26-Mar-2024

Revision Date 25-Mar-2024

Revision Number 1

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name Rechargeable Li-ion Battery L22X3PG4 by CosMX

Other means of identification

Product Code(s) 1787333

Recommended use of the chemical and restrictions on use

Recommended Use Lithium Ion Battery

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Identification Lenovo LNB laptops

Address Songtao Road 696
shanghai
shanghai
201203
CN

Telephone Phone:18116118603

E-mail yuanbb1@lenovo.com

Emergency telephone number

Company Emergency Phone Number 18116118603

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1B



Specific target organ toxicity (repeated exposure)	Category 1
--	------------

This is a battery. In case of rupture: the above hazards exist.

Appearance Black

Physical state Solid

Odor Odorless

GHS Label elements, including precautionary statements

Danger

Hazard statements

Causes severe skin burns and eye damage

May cause an allergic skin reaction

May cause cancer

Causes damage to organs through prolonged or repeated exposure



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Contaminated work clothing must not be allowed out of the workplace

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

Wash contaminated clothing before reuse

If skin irritation or rash occurs: Get medical advice/attention

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Immediately call a POISON CENTER or doctor

Ingestion

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

May be harmful if swallowed. May be harmful in contact with skin. Very toxic to aquatic life with long lasting effects.

Unknown acute toxicity 51 % of the mixture consists of ingredient(s) of unknown toxicity
48 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
51 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
51 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
51 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
51 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lithium Cobalt Oxide (CoLiO ₂)	12190-79-3	50	-	-
Graphite	7782-42-5	30	-	-
Propylene carbonate	108-32-7	10	-	-
Ethylene carbonate	96-49-1	10	-	-
Copper	7440-50-8	10	-	-
Aluminum	7429-90-5	10	-	-
Phosphate(1-), hexafluoro-, lithium	21324-40-3	5	-	-
Glass, oxide	65997-17-3	3	-	-
Nickel	7440-02-0	2	-	-
Carbon black	1333-86-4	2	-	-
Sodium carboxymethyl cellulose	9004-32-4	1	-	-
1,3-Propane sultone	1120-71-4	0.5	-	-
Acrylic acid	79-10-7	0.2	-	-
Titanium dioxide	13463-67-7	0.1	-	-

4. FIRST AID MEASURES

Description of first aid measures

General advice

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. First aid is upon rupture of sealed battery. In case of rupture:

Inhalation

Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get immediate medical advice/attention.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

	eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get immediate medical advice/attention. May cause an allergic skin reaction.
Ingestion	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Itching. Rashes. Hives.

Indication of any immediate medical attention and special treatment needed

Note to physicians Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause sensitization in susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.
Hazardous Combustion Products	Carbon oxides.
Explosion Data	
Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	None.
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe

areas. Keep people away from and upwind of spill/leak.

Other Information

Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide (CoLiO ₂) 12190-79-3	TWA: 0.02 mg/m ³	-	
Graphite 7782-42-5	TWA: 2 mg/m ³ respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf respirable dust natural (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust
Copper 7440-50-8	TWA: 0.2 mg/m ³ fume	TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ dust and mist (vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume

Aluminum 7429-90-5	TWA: 1 mg/m³ respirable particulate matter	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 15 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction	TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust	
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m³ F	TWA: 2.5 mg/m³ F (vacated) TWA: 2.5 mg/m³	IDLH: 250 mg/m³ F	
Glass, oxide 65997-17-3	TWA: 1 fiber/cm3 respirable fibers: length >5 µm, aspect ratio >=3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m³ inhalable fraction	-		
Nickel 7440-02-0	TWA: 1.5 mg/m³	TWA: 1 mg/m³ (vacated) TWA: 1 mg/m³	IDLH: 10 mg/m³ TWA: 0.015 mg/m³	
Carbon black 1333-86-4	TWA: 3 mg/m³ inhalable particulate matter	TWA: 3.5 mg/m³ (vacated) TWA: 3.5 mg/m³	IDLH: 1750 mg/m³ TWA: 3.5 mg/m³ TWA: 0.1 mg/m³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH	
Acrylic acid 79-10-7	TWA: 2 ppm S*	(vacated) TWA: 10 ppm (vacated) TWA: 30 mg/m³ (vacated) S*	TWA: 2 ppm TWA: 6 mg/m³	
Titanium dioxide 13463-67-7	TWA: 10 mg/m³	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust	IDLH: 5000 mg/m³	
Chemical name	Alberta	British Columbia	Ontario TWA/EV	Quebec
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	TWA: 0.02 mg/m³	TWA: 0.02 mg/m³	TWA: 0.02 mg/m³	TWA: 0.02 mg/m³
Graphite 7782-42-5	TWA: 2 mg/m³	TWA: 2 mg/m³	TWA: 2 mg/m³	TWA: 2 mg/m³
Copper 7440-50-8	TWA: 0.2 mg/m³ TWA: 1 mg/m³	TWA: 1 mg/m³ TWA: 0.2 mg/m³	TWA: 0.2 mg/m³ TWA: 1 mg/m³	TWA: 0.2 mg/m³ TWA: 1 mg/m³
Aluminum 7429-90-5	TWA: 10 mg/m³	TWA: 1.0 mg/m³	TWA: 1 mg/m³	TWA: 10 mg/m³
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m³	TWA: 2.5 mg/m³	TWA: 2.5 mg/m³	TWA: 2.5 mg/m³
Glass, oxide 65997-17-3	TWA: 5 mg/m³ TWA: 1 fibre/cm3	TWA: 1 fibre/cm3 TWA: 5 mg/m³	TWA: 1 fibre/cm3 TWA: 5 mg/m³	TWA: 1 fibre/cm3
Nickel 7440-02-0	TWA: 1.5 mg/m³	TWA: 0.05 mg/m³	TWA: 1 mg/m³	TWA: 1.5 mg/m³
Carbon black 1333-86-4	TWA: 3.5 mg/m³	TWA: 3 mg/m³	TWA: 3 mg/m³	TWA: 3 mg/m³
1,3-Propane sultone 1120-71-4		TWA:	TWA:	TWA:
Acrylic acid 79-10-7	TWA: 2 ppm TWA: 5.9 mg/m³ Skin	TWA: 2 ppm Skin	TWA: 2 ppm Skin	TWA: 2 ppm TWA: 5.9 mg/m³ Skin
Titanium dioxide	TWA: 10 mg/m³	TWA: 10 mg/m³	TWA: 10 mg/m³	TWA: 10 mg/m³

13463-67-7		TWA: 3 mg/m ³		
------------	--	--------------------------	--	--

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Face protection shield.

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Solid
Appearance Black
Odor Odorless
Color No information available
Odor Threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	No data available	None known
Water Solubility	Insoluble in water	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water¹		
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known

Dynamic viscosity	No data available	None known
-------------------	-------------------	------------

Other Information

Explosive properties	No information available
Oxidizing properties	No information available
Softening Point	No information available
Molecular Weight	No information available
VOC Content (%)	No information available
Liquid Density	No information available
Bulk Density	No information available
Particle Size	No information available
Particle Size Distribution	No information available

10. STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Exposure to air or moisture over prolonged periods.
Incompatible materials	Acids. Bases. Oxidizing agent.
Hazardous Decomposition Products	Carbon oxides.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Product Information	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:
Inhalation	Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal.
Eye contact	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May be harmful in contact with skin.
Ingestion	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the

mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Coughing and/ or wheezing. Itching. Rashes. Hives.

Numerical measures of toxicity**Acute toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 4,568.70 mg/kg

ATEmix (dermal) 2,940.00 mg/kg

Unknown acute toxicity 51 % of the mixture consists of ingredient(s) of unknown toxicity

48 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

51 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

51 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

51 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

51 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Product Information**Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Lithium Cobalt Oxide (CoLiO ₂)	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 5.05 mg/L (Rat) 4 h
Graphite	-	-	> 2000 mg/m ³ (Rat) 4 h
Propylene carbonate	= 29000 mg/kg (Rat)	> 3000 mg/kg (Rabbit)	-
Ethylene carbonate	= 10 g/kg (Rat)	> 26420 mg/kg (Rabbit)	> 730 mg/m ³ (Rat) 8 h
Copper	-	-	> 5.11 mg/L (Rat) 4 h
Aluminum	-	-	> 0.888 mg/L (Rat) 4 h
Nickel	> 9000 mg/kg (Rat)	-	> 10.2 mg/L (Rat) 1 h
Carbon black	> 15400 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 4.6 mg/m ³ (Rat) 4 h
Sodium carboxymethyl cellulose	= 27000 mg/kg (Rat)	-	> 5800 mg/m ³ (Rat) 4 h
1,3-Propane sultone	= 157 mg/kg (Rat)	-	-
Acrylic acid	= 193 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 11.1 mg/L (Rat) 1 h = 3.6 mg/L (Rat) 4 h
Titanium dioxide	> 10000 mg/kg (Rat)	-	= 5.09 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes burns.

Serious eye damage/eye irritation Classification based on data available for ingredients. Risk of serious damage to eyes. Causes burns.

Respiratory or skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer. This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide (CoLiO ₂) 12190-79-3	A3	Group 2B	Reasonably Anticipated	X
Glass, oxide 65997-17-3	-	Group 3	-	-
Nickel 7440-02-0	-	Group 2B	Reasonably Anticipated	X
Carbon black 1333-86-4	A3	Group 2B	-	X
1,3-Propane sultone 1120-71-4	A3	Group 2A	Reasonably Anticipated	X
Acrylic acid 79-10-7	-	Group 3	-	-
Titanium dioxide 13463-67-7	A3	Group 2B	-	X

Legend**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Very toxic to aquatic life with long lasting effects.
--------------------	---

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Graphite	No data available	96h LC50: > 100 mg/L (Danio rerio)	No data available	No data available
Propylene carbonate	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: > 1000 mg/L (Cyprinus carpio)	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L (Daphnia magna)
Ethylene carbonate	No data available	96h LC50: > 100 mg/L (Oncorhynchus mykiss)	No data available	No data available
Copper	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss)	No data available	48h EC50: = 0.03 mg/L (Daphnia magna)

	subcapitata)	96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus)		
Nickel	96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata) 72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio) 96h LC50: > 100 mg/L (Brachydanio rerio)	No data available	48h EC50: = 1 mg/L (Daphnia magna) 48h EC50: > 100 mg/L (Daphnia magna)
Acrylic acid	72h EC50: = 0.04 mg/L (Desmodesmus subspicatus) 96h EC50: = 0.17 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 222 mg/L (Brachydanio rerio)	No data available	48h EC50: = 95 mg/L (Daphnia magna)

Persistence and Degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Propylene carbonate	0.48
Ethylene carbonate	0.11
Acrylic acid	0.46

Mobility No information available.

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

California Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO ₂) 12190-79-3	Toxic



Aluminum 7429-90-5	Ignitable powder
Nickel 7440-02-0	Toxic powder Ignitable powder

14. TRANSPORT INFORMATION**Note:**

The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)

Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

DOT

Proper Shipping Name
Hazard Class
Emergency Response Guide
Number

NOT REGULATED
NON-REGULATED
N/A
147

TDG

Not applicable

MEX

Not applicable

ICAO

Not applicable

IATA

UN-No.
Proper Shipping Name
Hazard Class
ERG Code
Description

UN3480
LITHIUM ION BATTERIES
9
12FZ
UN3480, LITHIUM ION BATTERIES, 9

IMDG/IMO

Proper Shipping Name
Hazard Class
EmS-No.
Marine Pollutant

Not applicable
NON-REGULATED PER SP 188
N/A
F-A, S-I
This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO

RID

Not applicable

ADR

Not applicable

ADN

Not applicable

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture



International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA	Contact supplier for inventory compliance status.
DSL/NDSL	Contact supplier for inventory compliance status.
EINECS/ELINCS	Contact supplier for inventory compliance status.
ENCS	Contact supplier for inventory compliance status.
KECL	Contact supplier for inventory compliance status.
PICCS	Contact supplier for inventory compliance status.
AICS	Contact supplier for inventory compliance status.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Lithium Cobalt Oxide (CoLiO ₂) - 12190-79-3	12190-79-3	50	0.1
Copper - 7440-50-8	7440-50-8	10	1.0
Aluminum - 7429-90-5	7429-90-5	10	1.0
Nickel - 7440-02-0	7440-02-0	2	0.1
1,3-Propane sultone - 1120-71-4	1120-71-4	0.5	0.1
Acrylic acid - 79-10-7	79-10-7	0.2	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper 7440-50-8		X	X	
Nickel 7440-02-0		X	X	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
1,3-Propane sultone 1120-71-4	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ
Acrylic acid 79-10-7	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Carbon black - 1333-86-4	Carcinogen
Nickel - 7440-02-0	carcinogen, 10/1/1989 (metallic)
1,3-Propane sultone - 1120-71-4	carcinogen, 1/1/1988
Titanium dioxide - 13463-67-7	Carcinogen

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (CoLiO ₂) 12190-79-3	X		X	X	X
Graphite 7782-42-5	X	X	X		
Ethylene carbonate 96-49-1		X	X		
Copper 7440-50-8	X	X	X	X	X
Aluminum 7429-90-5	X	X	X	X	
Phosphate(1-), hexafluoro-, lithium 21324-40-3	X				
Nickel 7440-02-0	X	X	X	X	X
Carbon black 1333-86-4	X	X	X		X
1,3-Propane sultone 1120-71-4	X	X	X	X	X
Acrylic acid 79-10-7	X	X	X	X	X
Titanium dioxide 13463-67-7	X	X	X		

16. OTHER INFORMATION

<u>NFPA</u>	Health hazards 1	Flammability 0	Instability 0	Physical and Chemical Properties -
<u>HMIS</u>	Health hazards 0	Flammability 0	Physical hazards 0	Personal Protection X

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 26-Mar-2024

Revision Date 25-Mar-2024

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet