

# SAFETY DATA SHEET

Issuing Date 01-Oct-2024

Revision Date 27-Sep-2024

Revision Number 1

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is ©2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION

### Product identifier

**Product Name** Rechargeable Li-ion Battery L24D3PK2 by SUNWODA

### Other means of identification

**Product Code(s)** 1820748

### Recommended use of the chemical and restrictions on use

**Recommended Use** Lithium Ion Battery

**Restrictions on use** No information available

### Details of the supplier of the safety data sheet

**Supplier Identification** Lenovo LNB laptops

**Address** Songtao Road 696  
shanghai  
shanghai  
201203  
CN

**Telephone** Phone:18116118603

**E-mail** yuanbb1@lenovo.com

### Emergency telephone number

**Company Emergency Phone Number** 18116118603

## 2. HAZARDS IDENTIFICATION

### Classification

Acute toxicity - Inhalation (Vapors)	Category 1
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1



Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1

This is a battery. In case of rupture: the above hazards exist.

**Appearance** Black

**Physical state** Solid

**Odor** Odorless

**GHS Label elements, including precautionary statements**

**Danger**

**Hazard statements**

- Fatal if inhaled
- Causes severe skin burns and eye damage
- May cause an allergic skin reaction
- May cause cancer
- Causes damage to organs through prolonged or repeated exposure



**Precautionary Statements - Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Wear protective gloves/protective clothing/eye protection/face protection
- Do not breathe dust/fume/gas/mist/vapors/spray
- Use only outdoors or in a well-ventilated area
- Wear respiratory protection
- Wash face, hands and any exposed skin thoroughly after handling
- Contaminated work clothing must not be allowed out of the workplace
- Do not eat, drink or smoke when using this product

**Precautionary Statements - Response**

- Specific treatment is urgent (see supplemental first aid instructions on this label)
- Immediately call a POISON CENTER or doctor

**Eyes**

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- Immediately call a POISON CENTER or doctor

**Skin**

- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
- Wash contaminated clothing before reuse
- If skin irritation or rash occurs: Get medical advice/attention

**Inhalation**

- IF INHALED: Remove person to fresh air and keep comfortable for breathing
- Immediately call a POISON CENTER or doctor

**Ingestion**

- IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

**Precautionary Statements - Storage**

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other information**

May be harmful if swallowed. May be harmful in contact with skin. Very toxic to aquatic life with long lasting effects.

**Unknown acute toxicity** 52 % of the mixture consists of ingredient(s) of unknown toxicity

- 49 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
- 52 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
- 52 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
- 52 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
- 52 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Substance**

Not applicable.

**Mixture**

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Cobalt lithium manganese nickel oxide	182442-95-1	50	-	-
Graphite	7782-42-5	30	-	-
Ci 77400	7440-50-8	15	-	-
Propylene carbonate	108-32-7	10	-	-
Ethylene carbonate	96-49-1	10	-	-
Ci 77000	7429-90-5	10	-	-
Phosphate(1-), hexafluoro-, lithium	21324-40-3	5	-	-
Nickel	7440-02-0	2	-	-
Ci 77266	1333-86-4	2	-	-
Sodium carboxymethyl cellulose	9004-32-4	1	-	-
1,3-Propane sultone	1120-71-4	0.5	-	-

**4. FIRST AID MEASURES**

**Description of first aid measures**

**General advice**

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. First aid is upon rupture of sealed battery. In case of rupture:

**Inhalation**

If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Do not breathe dust. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get immediate medical advice/attention.



<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get immediate medical advice/attention. May cause an allergic skin reaction.
<b>Ingestion</b>	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Do not breathe dust. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

**Most important symptoms and effects, both acute and delayed**

<b>Symptoms</b>	Coughing and/ or wheezing. Difficulty in breathing. Burning sensation. Itching. Rashes. Hives.
-----------------	--

**Indication of any immediate medical attention and special treatment needed**

<b>Note to physicians</b>	Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause sensitization in susceptible persons. Treat symptomatically.
---------------------------	---

**5. FIRE-FIGHTING MEASURES**

<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Large Fire</b>	CAUTION: Use of water spray when fighting fire may be inefficient.
<b>Unsuitable extinguishing media</b>	Do not scatter spilled material with high pressure water streams.
<b>Specific hazards arising from the chemical</b>	The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.
<b>Hazardous Combustion Products</b>	Carbon oxides.
<b>Explosion Data</b>	
<b>Sensitivity to Mechanical Impact</b>	None.
<b>Sensitivity to Static Discharge</b>	None.
<b>Special protective equipment for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

**6. ACCIDENTAL RELEASE MEASURES**



**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Avoid generation of dust. Do not breathe dust. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Attention! Corrosive material.

**Other Information** Refer to protective measures listed in Sections 7 and 8.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not breathe dust. Avoid generation of dust. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Protect from moisture. Store away from other materials.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Cobalt lithium manganese nickel oxide 182442-95-1	TWA: 0.02 mg/m <sup>3</sup> Co inhalable particulate matter TWA: 0.02 mg/m <sup>3</sup> Mn respirable particulate matter TWA: 0.1 mg/m <sup>3</sup> Mn inhalable particulate matter	(vacated) Ceiling: 5 mg/m <sup>3</sup> Ceiling: 5 mg/m <sup>3</sup> Mn	IDLH: 500 mg/m <sup>3</sup> Mn IDLH: 10 mg/m <sup>3</sup> Ni TWA: 1 mg/m <sup>3</sup> Mn TWA: 0.015 mg/m <sup>3</sup> except Nickel carbonyl Ni STEL: 3 mg/m <sup>3</sup> Mn
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup> respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m <sup>3</sup> total dust synthetic TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf respirable dust natural (vacated) TWA: 2.5 mg/m <sup>3</sup> respirable dust natural (vacated) TWA: 10 mg/m <sup>3</sup> total dust synthetic	IDLH: 1250 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup> respirable dust



		(vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf natural		
Ci 77400 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> fume	TWA: 0.1 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> dust and mist (vacated) TWA: 0.1 mg/m <sup>3</sup> Cu dust, fume, mist	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume	
Ci 77000 7429-90-5	TWA: 1 mg/m <sup>3</sup> respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust	
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup> F (vacated) TWA: 2.5 mg/m <sup>3</sup>	IDLH: 250 mg/m <sup>3</sup> F	
Nickel 7440-02-0	TWA: 1.5 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> (vacated) TWA: 1 mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> TWA: 0.015 mg/m <sup>3</sup>	
Ci 77266 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH	
<b>Chemical name</b>	<b>Alberta</b>	<b>British Columbia</b>	<b>Ontario TWA/EV</b>	<b>Quebec</b>
Cobalt lithium manganese nickel oxide 182442-95-1	TWA: 0.02 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 0.05 mg/m <sup>3</sup> TWA: 0.02 mg/m <sup>3</sup>
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Ci 77400 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>
Ci 77000 7429-90-5	TWA: 10 mg/m <sup>3</sup>	TWA: 1.0 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>
Nickel 7440-02-0	TWA: 1.5 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 1.5 mg/m <sup>3</sup>
Ci 77266 1333-86-4	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>
1,3-Propane sultone 1120-71-4		TWA:	TWA:	TWA:

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

**Appropriate engineering controls**

**Engineering controls**

- Showers
- Eyewash stations
- Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Face protection shield.



<b>Hand protection</b>	Wear suitable gloves. Impervious gloves.
<b>Skin and body protection</b>	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.
<b>Respiratory protection</b>	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
<b>General hygiene considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not breathe dust. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	Solid
<b>Appearance</b>	Black
<b>Odor</b>	Odorless
<b>Color</b>	No information available
<b>Odor Threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
<b>pH</b>	No data available	None known
<b>Melting / freezing point</b>	No data available	None known
<b>Boiling point / boiling range</b>	No data available	None known
<b>Flash Point</b>	No data available	None known
<b>Evaporation Rate</b>	No data available	None known
<b>Flammability (solid, gas)</b>	No data available	None known
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit</b>	No data available	
<b>Lower flammability limit</b>	No data available	
<b>Vapor pressure</b>	No data available	None known
<b>Vapor density</b>	No data available	None known
<b>Relative density</b>	No data available	None known
<b>Water Solubility</b>	Insoluble in water	
<b>Solubility(ies)</b>	No data available	None known
<b>Partition coefficient: n-octanol/water<sup>1</sup></b>		
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>	No data available	None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	No data available	None known

### Other Information

<b>Explosive properties</b>	No information available
<b>Oxidizing properties</b>	No information available
<b>Softening Point</b>	No information available
<b>Molecular Weight</b>	No information available
<b>VOC Content (%)</b>	No information available
<b>Liquid Density</b>	No information available
<b>Bulk Density</b>	No information available
<b>Particle Size</b>	No information available
<b>Particle Size Distribution</b>	No information available

## 10. STABILITY AND REACTIVITY



<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of Hazardous Reactions</b>	None under normal processing.
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Excessive heat. Exposure to air or moisture over prolonged periods.
<b>Incompatible materials</b>	Acids. Bases. Oxidizing agent.
<b>Hazardous Decomposition Products</b>	Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:
<b>Inhalation</b>	Specific test data for the substance or mixture is not available. Fatal if inhaled. (based on components). Corrosive by inhalation. Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May be harmful in contact with skin.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Symptoms</b>	Coughing and/ or wheezing. Difficulty in breathing. Redness. Burning. May cause blindness. Itching. Rashes. Hives.
-----------------	--

### Numerical measures of toxicity

#### Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document  
ATEmix (oral) 4,495.40 mg/kg

ATEmix (dermal) 2,880.00 mg/kg  
ATEmix (inhalation-vapor) 0.481 mg/L

**Unknown acute toxicity** 52 % of the mixture consists of ingredient(s) of unknown toxicity  
 49 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
 52 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
 52 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
 52 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
 52 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Product Information			
Component Information			
Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Graphite	-	-	> 2000 mg/m <sup>3</sup> ( Rat ) 4 h
Ci 77400	-	-	> 5.11 mg/L ( Rat ) 4 h
Propylene carbonate	= 29000 mg/kg ( Rat )	> 3000 mg/kg ( Rabbit )	-
Ethylene carbonate	= 10 g/kg ( Rat )	> 26420 mg/kg ( Rabbit )	> 730 mg/m <sup>3</sup> ( Rat ) 8 h
Ci 77000	-	-	> 0.888 mg/L ( Rat ) 4 h
Nickel	> 9000 mg/kg ( Rat )	-	> 10.2 mg/L ( Rat ) 1 h
Ci 77266	> 10000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 4.6 mg/m <sup>3</sup> ( Rat ) 4 h
Sodium carboxymethyl cellulose	= 27000 mg/kg ( Rat )	-	> 5800 mg/m <sup>3</sup> ( Rat ) 4 h
1,3-Propane sultone	= 157 mg/kg ( Rat )	-	-

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes burns.  
**Serious eye damage/eye irritation** Classification based on data available for ingredients. Risk of serious damage to eyes. Causes burns.  
**Respiratory or skin sensitization** May cause sensitization by skin contact.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Cobalt lithium manganese nickel oxide 182442-95-1	A3	Group 2B Group 1	Reasonably Anticipated Known	X
Nickel 7440-02-0	-	Group 2B	Reasonably Anticipated	X
Ci 77266 1333-86-4	A3	Group 2B	-	X
1,3-Propane sultone 1120-71-4	A3	Group 2A	Reasonably Anticipated	X

**Legend**

**ACGIH (American Conference of Governmental Industrial Hygienists)**  
 A3 - Animal Carcinogen  
**IARC (International Agency for Research on Cancer)**  
 Group 1 - Carcinogenic to Humans  
 Group 2A - Probably Carcinogenic to Humans  
 Group 2B - Possibly Carcinogenic to Humans



**NTP (National Toxicology Program)**

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

<b>Reproductive toxicity</b>	No information available.
<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	No information available.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Graphite	No data available	96h LC50: > 100 mg/L (Danio rerio)	No data available	No data available
Ci 77400	72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 0.112 mg/L (Poecilia reticulata)	No data available	48h EC50: = 0.03 mg/L (Daphnia magna)
Propylene carbonate	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: > 1000 mg/L (Cyprinus carpio)	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L (Daphnia magna)
Ethylene carbonate	No data available	96h LC50: > 100 mg/L (Oncorhynchus mykiss)	No data available	No data available
Nickel	72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 100 mg/L (Brachydanio rerio) 96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio)	No data available	48h EC50: > 100 mg/L (Daphnia magna) 48h EC50: = 1 mg/L (Daphnia magna)

**Persistence and Degradability** No information available.

**Bioaccumulation**



**Component Information**

Chemical name	Partition coefficient
Propylene carbonate	0.48
Ethylene carbonate	0.11

**Mobility** No information available.

**Other adverse effects** No information available.

**13. DISPOSAL CONSIDERATIONS**

Waste treatment methods

**Waste from residues/unused products** Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Do not reuse empty containers.

**California Waste Codes** 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Cobalt lithium manganese nickel oxide 182442-95-1	Toxic
Ci 77000 7429-90-5	Ignitable powder
Nickel 7440-02-0	Toxic powder Ignitable powder

**14. TRANSPORT INFORMATION**

**Note:** The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)  
Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

**DOT** NOT REGULATED  
**Proper Shipping Name** NON-REGULATED  
**Hazard Class** N/A  
**Emergency Response Guide Number** 147

**TDG** Not applicable



<b>MEX</b>	Not applicable
<b>ICAO</b>	Not applicable
<b>IATA</b>	
<b>UN-No.</b>	UN3480
<b>Proper Shipping Name</b>	LITHIUM ION BATTERIES
<b>Hazard Class</b>	9
<b>ERG Code</b>	12FZ
<b>Description</b>	UN3480, LITHIUM ION BATTERIES, 9
<b>IMDG/IMO</b>	Not applicable
<b>Proper Shipping Name</b>	NON-REGULATED PER SP 188
<b>Hazard Class</b>	N/A
<b>EmS-No.</b>	F-A, S-I
<b>Marine Pollutant</b>	This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO
<b>RID</b>	Not applicable
<b>ADR</b>	Not applicable
<b>ADN</b>	Not applicable

## 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Regulations

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

#### International Inventories

<b>TSCA</b>	Contact supplier for inventory compliance status.
<b>DSL/NDSL</b>	Contact supplier for inventory compliance status.
<b>EINECS/ELINCS</b>	Contact supplier for inventory compliance status.
<b>ENCS</b>	Contact supplier for inventory compliance status.
<b>KECL</b>	Contact supplier for inventory compliance status.
<b>PICCS</b>	Contact supplier for inventory compliance status.
<b>AICS</b>	Contact supplier for inventory compliance status.

#### Legend

<b>TSCA</b>	- United States Toxic Substances Control Act Section 8(b) Inventory
<b>DSL/NDSL</b>	- Canadian Domestic Substances List/Non-Domestic Substances List
<b>EINECS/ELINCS</b>	- European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
<b>ENCS</b>	- Japan Existing and New Chemical Substances
<b>KECL</b>	- Korean Existing and Evaluated Chemical Substances
<b>PICCS</b>	- Philippines Inventory of Chemicals and Chemical Substances
<b>AICS</b>	- Australian Inventory of Chemical Substances

#### US Federal Regulations

##### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical



or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Cobalt lithium manganese nickel oxide - 182442-95-1	182442-95-1	50	1.0 0.1
Ci 77400 - 7440-50-8	7440-50-8	15	1.0
Ci 77000 - 7429-90-5	7429-90-5	10	1.0
Nickel - 7440-02-0	7440-02-0	2	0.1
1,3-Propane sultone - 1120-71-4	1120-71-4	0.5	0.1

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Cobalt lithium manganese nickel oxide 182442-95-1		X		
Ci 77400 7440-50-8		X	X	
Nickel 7440-02-0		X	X	

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ci 77400 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
1,3-Propane sultone 1120-71-4	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Cobalt lithium manganese nickel oxide - 182442-95-1	carcinogen, 5/7/2004
Nickel - 7440-02-0	carcinogen, 10/1/1989 (metallic)
Ci 77266 - 1333-86-4	carcinogen, 2/21/2003 (airborne, unbound particles of respirable size)
1,3-Propane sultone - 1120-71-4	carcinogen, 1/1/1988

**U.S. State Right-to-Know Regulations**

This product may contain substances regulated by state right-to-know regulations.



Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Cobalt lithium manganese nickel oxide 182442-95-1	X		X	X	X
Graphite 7782-42-5	X	X	X		
Ci 77400 7440-50-8	X	X	X	X	X
Ethylene carbonate 96-49-1		X	X		
Ci 77000 7429-90-5	X	X	X	X	
Phosphate(1-), hexafluoro-, lithium 21324-40-3	X				
Nickel 7440-02-0	X	X	X	X	X
Ci 77266 1333-86-4	X	X	X		X
1,3-Propane sultone 1120-71-4	X	X	X	X	X

## 16. OTHER INFORMATION

**NFPA** Health hazards 1 Flammability 0 Instability 0 Physical and Chemical Properties -  
**HMIS** Health hazards 0 Flammability 0 Physical hazards 0 Personal Protection X

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Issuing Date** 01-Oct-2024

**Revision Date** 27-Sep-2024

**Revision Note** No information available

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**



# SAFETY DATA SHEET

Issuing Date 26-Sep-2024

Revision Date 24-Sep-2024

Revision Number 1

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is ©2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION

### Product identifier

**Product Name** Rechargeable Li-ion Battery L24M3PK2 by Simplo

### Other means of identification

**Product Code(s)** 1820048

### Recommended use of the chemical and restrictions on use

**Recommended Use** Lithium Ion Battery

**Restrictions on use** No information available

### Details of the supplier of the safety data sheet

**Supplier Identification** Lenovo LNB laptops

**Address** Songtao Road 696  
shanghai  
shanghai  
201203  
CN

**Telephone** Phone:18116118603

**E-mail** yuanbb1@lenovo.com

### Emergency telephone number

**Company Emergency Phone Number** 18116118603

## 2. HAZARDS IDENTIFICATION

### Classification

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 1B



This is a battery. In case of rupture: the above hazards exist.

**Appearance** Black

**Physical state** Solid

**Odor** Odorless

**GHS Label elements, including precautionary statements**

**Danger**

**Hazard statements**

Causes serious eye irritation

May cause an allergic skin reaction

May cause cancer



**Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

**Skin**

IF ON SKIN: Wash with plenty of water and soap

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

**Precautionary Statements - Storage**

Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other information**

Causes mild skin irritation. Very toxic to aquatic life with long lasting effects.

**Unknown acute toxicity**

33.03 % of the mixture consists of ingredient(s) of unknown toxicity

29.55 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

33.03 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

33.03 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

33.03 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

33.03 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Substance**

Not applicable.

**Mixture**

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lithium Cobalt Oxide (CoLiO2)	12190-79-3	47.15	-	-
Graphite	7782-42-5	25.25	-	-
Copper	7440-50-8	6.82	-	-
Ci 77000	7429-90-5	4.31	-	-
Propylene carbonate	108-32-7	2.15	-	-
Ethylene carbonate	96-49-1	2.15	-	-
Nickel	7440-02-0	0.5	-	-
1,3-Propane sultone	1120-71-4	0.48	-	-

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. First aid is upon rupture of sealed battery. In case of rupture: Remove to fresh air.
<b>Inhalation</b>	
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.
<b>Self-protection of the first aider</b>	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

**Most important symptoms and effects, both acute and delayed**

**Symptoms** Itching. Rashes. Hives. Burning sensation.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** May cause sensitization in susceptible persons. Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.



---

<b>Large Fire</b>	CAUTION: Use of water spray when fighting fire may be inefficient.
<b>Unsuitable extinguishing media</b>	Do not scatter spilled material with high pressure water streams.
<b>Specific hazards arising from the chemical</b>	Product is or contains a sensitizer. May cause sensitization by skin contact.
<b>Hazardous Combustion Products</b>	Carbon oxides.
<b>Explosion Data</b>	
<b>Sensitivity to Mechanical Impact</b>	None.
<b>Sensitivity to Static Discharge</b>	None.
<b>Special protective equipment for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Other Information** Refer to protective measures listed in Sections 7 and 8.

### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

**Exposure Limits**



Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	TWA: 0.02 mg/m <sup>3</sup>	-		
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup> respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m <sup>3</sup> total dust synthetic TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf respirable dust natural (vacated) TWA: 2.5 mg/m <sup>3</sup> respirable dust natural (vacated) TWA: 10 mg/m <sup>3</sup> total dust synthetic (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup> respirable dust	
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> fume	TWA: 0.1 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> dust and mist (vacated) TWA: 0.1 mg/m <sup>3</sup> Cu dust, fume, mist	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume	
Ci 77000 7429-90-5	TWA: 1 mg/m <sup>3</sup> respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust	
Nickel 7440-02-0	TWA: 1.5 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> (vacated) TWA: 1 mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> TWA: 0.015 mg/m <sup>3</sup>	
Chemical name	Alberta	British Columbia	Ontario TWAEV	Quebec
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>
Ci 77000 7429-90-5	TWA: 10 mg/m <sup>3</sup>	TWA: 1.0 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
Nickel 7440-02-0	TWA: 1.5 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 1.5 mg/m <sup>3</sup>
1,3-Propane sultone 1120-71-4		TWA:	TWA:	TWA:

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

**Appropriate engineering controls**

**Engineering controls**

Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Wear safety glasses with side shields (or goggles).



<b>Hand protection</b>	Wear suitable gloves.
<b>Skin and body protection</b>	Wear suitable protective clothing.
<b>Respiratory protection</b>	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
<b>General hygiene considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	Solid
<b>Appearance</b>	Black
<b>Odor</b>	Odorless
<b>Color</b>	No information available
<b>Odor Threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
<b>pH</b>	No data available	None known	
<b>Melting / freezing point</b>	No data available	None known	
<b>Boiling point / boiling range</b>	No data available	None known	
<b>Flash Point</b>	No data available	None known	
<b>Evaporation Rate</b>	No data available	None known	
<b>Flammability (solid, gas)</b>	No data available	None known	
<b>Flammability Limit in Air</b>			
<b>Upper flammability limit</b>	No data available		
<b>Lower flammability limit</b>	No data available		
<b>Vapor pressure</b>	No data available	None known	
<b>Vapor density</b>	No data available	None known	
<b>Relative density</b>	No data available	None known	
<b>Water Solubility</b>	Insoluble in water		
<b>Solubility(ies)</b>	No data available	None known	
<b>Partition coefficient: n-octanol/water<sup>1</sup></b>			
<b>Autoignition temperature</b>	No data available	None known	
<b>Decomposition temperature</b>	No data available	None known	
<b>Kinematic viscosity</b>	No data available	None known	
<b>Dynamic viscosity</b>	No data available	None known	

### Other Information

<b>Explosive properties</b>	No information available
<b>Oxidizing properties</b>	No information available
<b>Softening Point</b>	No information available
<b>Molecular Weight</b>	No information available
<b>VOC Content (%)</b>	No information available
<b>Liquid Density</b>	No information available
<b>Bulk Density</b>	No information available
<b>Particle Size</b>	No information available
<b>Particle Size Distribution</b>	No information available

## 10. STABILITY AND REACTIVITY

<b>Reactivity</b>	No information available.
-------------------	---------------------------



<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of Hazardous Reactions</b>	None under normal processing.
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	None known based on information supplied.
<b>Incompatible materials</b>	None known based on information supplied.
<b>Hazardous Decomposition Products</b>	Carbon oxides.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

<b>Product Information</b>	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:
<b>Inhalation</b>	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. May cause sensitization by skin contact. (based on components). Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May cause irritation. Prolonged contact may cause redness and irritation.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms** Itching. Rashes. Hives. May cause redness and tearing of the eyes.

**Numerical measures of toxicity**

**Acute toxicity**

**Unknown acute toxicity** 33.03 % of the mixture consists of ingredient(s) of unknown toxicity  
 29.55 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
 33.03 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
 33.03 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
 33.03 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
 33.03 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

**Product Information**

**Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Lithium Cobalt Oxide (CoLiO2)	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	> 5.05 mg/L ( Rat ) 4 h
Graphite	-	-	> 2000 mg/m <sup>3</sup> ( Rat ) 4 h
Copper	-	-	> 5.11 mg/L ( Rat ) 4 h
Ci 77000	-	-	> 0.888 mg/L ( Rat ) 4 h



Propylene carbonate	= 29000 mg/kg ( Rat )	> 3000 mg/kg ( Rabbit )	-
Ethylene carbonate	= 10 g/kg ( Rat )	> 26420 mg/kg ( Rabbit )	> 730 mg/m <sup>3</sup> ( Rat ) 8 h
Nickel	> 9000 mg/kg ( Rat )	-	> 10.2 mg/L ( Rat ) 1 h
1,3-Propane sultone	= 157 mg/kg ( Rat )	-	-

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Skin corrosion/irritation</b>	May cause skin irritation.
<b>Serious eye damage/eye irritation</b>	Classification based on data available for ingredients. Causes serious eye irritation.
<b>Respiratory or skin sensitization</b>	May cause sensitization by skin contact.
<b>Germ cell mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	A3	Group 2B	Reasonably Anticipated	X
Nickel 7440-02-0	-	Group 2B	Reasonably Anticipated	X
1,3-Propane sultone 1120-71-4	A3	Group 2A	Reasonably Anticipated	X

**Legend**

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

**NTP (National Toxicology Program)**

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

<b>Reproductive toxicity</b>	No information available.
<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	No information available.
<b>Aspiration hazard</b>	No information available.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Graphite	No data available	96h LC50: > 100 mg/L (Danio rerio)	No data available	No data available



Copper	72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 0.112 mg/L (Poecilia reticulata)	No data available	48h EC50: = 0.03 mg/L (Daphnia magna)
Propylene carbonate	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: > 1000 mg/L (Cyprinus carpio)	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L (Daphnia magna)
Ethylene carbonate	No data available	96h LC50: > 100 mg/L (Oncorhynchus mykiss)	No data available	No data available
Nickel	72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 100 mg/L (Brachydanio rerio) 96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio)	No data available	48h EC50: > 100 mg/L (Daphnia magna) 48h EC50: = 1 mg/L (Daphnia magna)

**Persistence and Degradability** No information available.

**Bioaccumulation**

**Component Information**

Chemical name	Partition coefficient
Propylene carbonate	0.48
Ethylene carbonate	0.11

**Mobility** No information available.

**Other adverse effects** No information available.

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Waste from residues/unused products** Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Do not reuse empty containers.

**California Waste Codes** 141



This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	Toxic
Ci 77000 7429-90-5	Ignitable powder
Nickel 7440-02-0	Toxic powder Ignitable powder

**14. TRANSPORT INFORMATION**

**Note:** The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule) Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

**DOT** NOT REGULATED  
**Proper Shipping Name** NON-REGULATED  
**Hazard Class** N/A  
**Emergency Response Guide Number** 147

**TDG** Not applicable

**MEX** Not applicable

**ICAO** Not applicable

**IATA**  
**UN-No.** UN3480  
**Proper Shipping Name** LITHIUM ION BATTERIES  
**Hazard Class** 9  
**ERG Code** 12FZ  
**Description** UN3480, LITHIUM ION BATTERIES, 9

**IMDG/IMO** Not applicable  
**Proper Shipping Name** NON-REGULATED PER SP 188  
**Hazard Class** N/A  
**EmS-No.** F-A, S-I

**RID** Not applicable

**ADR** Not applicable

**ADN** Not applicable



**15. REGULATORY INFORMATION**

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

**International Regulations**

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

**International Inventories**

**TSCA** Contact supplier for inventory compliance status.  
**DSL/NDSL** Contact supplier for inventory compliance status.  
**EINECS/ELINCS** Contact supplier for inventory compliance status.  
**ENCS** Contact supplier for inventory compliance status.  
**KECL** Contact supplier for inventory compliance status.  
**PICCS** Contact supplier for inventory compliance status.  
**AICS** Contact supplier for inventory compliance status.

**Legend**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Lithium Cobalt Oxide (CoLiO2) - 12190-79-3	12190-79-3	47.15	0.1
Copper - 7440-50-8	7440-50-8	6.82	1.0
Ci 77000 - 7429-90-5	7429-90-5	4.31	1.0
Nickel - 7440-02-0	7440-02-0	0.5	0.1
1,3-Propane sultone - 1120-71-4	1120-71-4	0.48	0.1

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper 7440-50-8		X	X	



Nickel 7440-02-0		X	X	
---------------------	--	---	---	--

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
1,3-Propane sultone 1120-71-4	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Nickel - 7440-02-0	carcinogen, 10/1/1989 (metallic)
1,3-Propane sultone - 1120-71-4	carcinogen, 1/1/1988

**U.S. State Right-to-Know Regulations**

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	X		X	X	X
Graphite 7782-42-5	X	X	X		
Copper 7440-50-8	X	X	X	X	X
Ci 77000 7429-90-5	X	X	X	X	
Ethylene carbonate 96-49-1		X	X		
Nickel 7440-02-0	X	X	X	X	X
1,3-Propane sultone 1120-71-4	X	X	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health hazards 1	Flammability 0	Instability 0	Physical and Chemical Properties - Personal Protection X
<b>HMIS</b>	Health hazards 0	Flammability 0	Physical hazards 0	

Prepared By Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501



<b>Issuing Date</b>	26-Sep-2024
<b>Revision Date</b>	24-Sep-2024
<b>Revision Note</b>	No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**

# SAFETY DATA SHEET

Issuing Date 26-Sep-2024

Revision Date 24-Sep-2024

Revision Number 1

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is ©2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION

### Product identifier

**Product Name** Rechargeable Li-ion Battery L24N3PK1 by NVT

### Other means of identification

**Product Code(s)** 1820037

### Recommended use of the chemical and restrictions on use

**Recommended Use** Lithium Ion Battery

**Restrictions on use** No information available

### Details of the supplier of the safety data sheet

**Supplier Identification** Lenovo LNB laptops

**Address** Songtao Road 696  
shanghai  
shanghai  
201203  
CN

**Telephone** Phone:18116118603

**E-mail** yuanbb1@lenovo.com

### Emergency telephone number

**Company Emergency Phone Number** 18116118603

## 2. HAZARDS IDENTIFICATION

### Classification

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Vapors)	Category 2
Skin corrosion/irritation	Category 1 Sub-category B



Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1

This is a battery. In case of rupture: the above hazards exist.

**Appearance** Black

**Physical state** Solid

**Odor** Odorless

**GHS Label elements, including precautionary statements**

**Danger**

**Hazard statements**

- Harmful if swallowed
- Harmful in contact with skin
- Fatal if inhaled
- Causes severe skin burns and eye damage
- May cause cancer
- May cause respiratory irritation. May cause drowsiness or dizziness
- Causes damage to organs through prolonged or repeated exposure



**Precautionary Statements - Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Wear protective gloves/protective clothing/eye protection/face protection
- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Do not breathe dust/fume/gas/mist/vapors/spray
- Use only outdoors or in a well-ventilated area
- Wear respiratory protection

**Precautionary Statements - Response**

- Specific treatment is urgent (see supplemental first aid instructions on this label)
- Immediately call a POISON CENTER or doctor

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Immediately call a POISON CENTER or doctor

**Skin**

Call a POISON CENTER or doctor if you feel unwell  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower  
Wash contaminated clothing before reuse

**Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing  
Immediately call a POISON CENTER or doctor

**Ingestion**

IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell  
Rinse mouth

Do NOT induce vomiting

#### Precautionary Statements - Storage

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

#### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

#### Other information

Very toxic to aquatic life with long lasting effects.

**Unknown acute toxicity** 30 % of the mixture consists of ingredient(s) of unknown toxicity  
25 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
30 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
30 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
30 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
30 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance

Not applicable.

#### Mixture

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Cobalt lithium manganese nickel oxide	182442-95-1	40	-	-
Copper	7440-50-8	30	-	-
Aluminum foil	7429-90-5	30	-	-
Graphite	7782-42-5	25	-	-
Propylene carbonate	108-32-7	15	-	-
Phosphate(1-), hexafluoro-, lithium	21324-40-3	15	-	-
Ethylene carbonate	96-49-1	15	-	-
1,3-Propane sultone	1120-71-4	1	-	-

### 4. FIRST AID MEASURES

#### Description of first aid measures

##### General advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required. IF exposed or concerned: Get medical advice/attention. First aid is upon rupture of sealed battery. In case of rupture:

##### Inhalation

If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Do not breathe dust. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get immediate medical advice/attention.



---

<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get immediate medical advice/attention.
<b>Ingestion</b>	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Do not breathe dust. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

**Most important symptoms and effects, both acute and delayed**

<b>Symptoms</b>	Coughing and/ or wheezing. Difficulty in breathing. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
-----------------	---

**Indication of any immediate medical attention and special treatment needed**

<b>Note to physicians</b>	Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure.
---------------------------	--

**5. FIRE-FIGHTING MEASURES**

<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Large Fire</b>	CAUTION: Use of water spray when fighting fire may be inefficient.
<b>Unsuitable extinguishing media</b>	Do not scatter spilled material with high pressure water streams.
<b>Specific hazards arising from the chemical</b>	The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.
<b>Hazardous Combustion Products</b>	Carbon oxides.
<b>Explosion Data</b>	
<b>Sensitivity to Mechanical Impact</b>	None.
<b>Sensitivity to Static Discharge</b>	None.
<b>Special protective equipment for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

---

**Personal precautions** Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Avoid generation of dust. Do not breathe dust. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Attention! Corrosive material.

**Other Information** Refer to protective measures listed in Sections 7 and 8.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid breathing vapors or mists.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Store locked up. Protect from moisture. Store away from other materials.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Cobalt lithium manganese nickel oxide 182442-95-1	TWA: 0.02 mg/m <sup>3</sup> Co inhalable particulate matter TWA: 0.02 mg/m <sup>3</sup> Mn respirable particulate matter TWA: 0.1 mg/m <sup>3</sup> Mn inhalable particulate matter	(vacated) Ceiling: 5 mg/m <sup>3</sup> Ceiling: 5 mg/m <sup>3</sup> Mn	IDLH: 500 mg/m <sup>3</sup> Mn IDLH: 10 mg/m <sup>3</sup> Ni TWA: 1 mg/m <sup>3</sup> Mn TWA: 0.015 mg/m <sup>3</sup> except Nickel carbonyl Ni STEL: 3 mg/m <sup>3</sup> Mn
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> fume	TWA: 0.1 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> dust and mist (vacated) TWA: 0.1 mg/m <sup>3</sup> Cu dust, fume, mist	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume
Aluminum foil 7429-90-5	TWA: 1 mg/m <sup>3</sup> respirable particulate matter	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust



Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup> respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m <sup>3</sup> total dust synthetic TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf respirable dust natural (vacated) TWA: 2.5 mg/m <sup>3</sup> respirable dust natural (vacated) TWA: 10 mg/m <sup>3</sup> total dust synthetic (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup> respirable dust	
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup> F (vacated) TWA: 2.5 mg/m <sup>3</sup>	IDLH: 250 mg/m <sup>3</sup> F	
<b>Chemical name</b>	<b>Alberta</b>	<b>British Columbia</b>	<b>Ontario TWAEV</b>	<b>Quebec</b>
Cobalt lithium manganese nickel oxide 182442-95-1	TWA: 0.02 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 0.05 mg/m <sup>3</sup> TWA: 0.02 mg/m <sup>3</sup>
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>
Aluminum foil 7429-90-5	TWA: 10 mg/m <sup>3</sup>	TWA: 1.0 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>
1,3-Propane sultone 1120-71-4		TWA:	TWA:	TWA:

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

**Appropriate engineering controls**

**Engineering controls**

Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Face protection shield.

**Hand protection**

Wear suitable gloves. Impervious gloves.

**Skin and body protection**

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

**Respiratory protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not breathe dust. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Remove and wash contaminated



clothing and gloves, including the inside, before re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state	Solid
Appearance	Black
Odor	Odorless
Color	No information available
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	No data available	None known
Water Solubility	Insoluble in water	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water <sup>1</sup>		
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

### Other Information

Explosive properties	No information available
Oxidizing properties	No information available
Softening Point	No information available
Molecular Weight	No information available
VOC Content (%)	No information available
Liquid Density	No information available
Bulk Density	No information available
Particle Size	No information available
Particle Size Distribution	No information available

## 10. STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Excessive heat. Exposure to air or moisture over prolonged periods.
Incompatible materials	Acids. Bases. Oxidizing agent.

Hazardous Decomposition Products Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:
<b>Inhalation</b>	Specific test data for the substance or mixture is not available. Fatal if inhaled. (based on components). Corrosive by inhalation. Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause drowsiness or dizziness.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns. May be absorbed through the skin in harmful amounts. Harmful in contact with skin.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Symptoms</b>	Coughing and/ or wheezing. Difficulty in breathing. Redness. Burning. May cause blindness. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
-----------------	---

### Numerical measures of toxicity

#### Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

<b>ATEmix (oral)</b>	1,943.10 mg/kg
<b>ATEmix (dermal)</b>	1,375.00 mg/kg
<b>ATEmix (inhalation-vapor)</b>	0.877 mg/L

<b>Unknown acute toxicity</b>	30 % of the mixture consists of ingredient(s) of unknown toxicity
	25 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
	30 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
	30 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
	30 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
	30 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Product Information
---------------------

<b>Component Information</b>
------------------------------

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
---------------	-----------	-------------	-----------------



Copper	-	-	> 5.11 mg/L ( Rat ) 4 h
Aluminum foil	-	-	> 0.888 mg/L ( Rat ) 4 h
Graphite	-	-	> 2000 mg/m <sup>3</sup> ( Rat ) 4 h
Propylene carbonate	= 29000 mg/kg ( Rat )	> 3000 mg/kg ( Rabbit )	-
Ethylene carbonate	= 10 g/kg ( Rat )	> 26420 mg/kg ( Rabbit )	> 730 mg/m <sup>3</sup> ( Rat ) 8 h
1,3-Propane sultone	= 157 mg/kg ( Rat )	-	-

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

- Skin corrosion/irritation** Classification based on data available for ingredients. Causes burns.
- Serious eye damage/eye irritation** Classification based on data available for ingredients. Risk of serious damage to eyes. Causes burns.
- Respiratory or skin sensitization** No information available.
- Germ cell mutagenicity** No information available.
- Carcinogenicity** Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Cobalt lithium manganese nickel oxide 182442-95-1	A3	Group 2B Group 1	Reasonably Anticipated Known	X
1,3-Propane sultone 1120-71-4	A3	Group 2A	Reasonably Anticipated	X

**Legend**

- ACGIH (American Conference of Governmental Industrial Hygienists)**  
A3 - Animal Carcinogen
- IARC (International Agency for Research on Cancer)**  
Group 1 - Carcinogenic to Humans  
Group 2A - Probably Carcinogenic to Humans  
Group 2B - Possibly Carcinogenic to Humans
- NTP (National Toxicology Program)**  
Known - Known Carcinogen  
Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
- OSHA (Occupational Safety and Health Administration of the US Department of Labor)**  
X - Present

- Reproductive toxicity** No information available.
- STOT - single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.
- STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure.
- Aspiration hazard** No information available.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
---------------	----------------------	------	-------------	-----------



			microorganisms	
Copper	72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 0.112 mg/L (Poecilia reticulata)	No data available	48h EC50: = 0.03 mg/L (Daphnia magna)
Graphite	No data available	96h LC50: > 100 mg/L (Danio rerio)	No data available	No data available
Propylene carbonate	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: > 1000 mg/L (Cyprinus carpio)	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L (Daphnia magna)
Ethylene carbonate	No data available	96h LC50: > 100 mg/L (Oncorhynchus mykiss)	No data available	No data available

**Persistence and Degradability** No information available.

**Bioaccumulation**

**Component Information**

Chemical name	Partition coefficient
Propylene carbonate	0.48
Ethylene carbonate	0.11

**Mobility** No information available.

**Other adverse effects** No information available.

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Waste from residues/unused products** Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Do not reuse empty containers.

**California Waste Codes** 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Cobalt lithium manganese nickel oxide	Toxic



182442-95-1	
Aluminum foil 7429-90-5	Ignitable powder

**14. TRANSPORT INFORMATION**

**Note:** The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)  
Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

**DOT**  
**Proper Shipping Name** NOT REGULATED  
**Hazard Class** NON-REGULATED  
**Emergency Response Guide Number** N/A  
 147

**TDG** Not applicable

**MEX** Not applicable

**ICAO** Not applicable

**IATA**  
**UN-No.** UN3480  
**Proper Shipping Name** LITHIUM ION BATTERIES  
**Hazard Class** 9  
**ERG Code** 12FZ  
**Description** UN3480, LITHIUM ION BATTERIES, 9

**IMDG/IMO**  
**Proper Shipping Name** Not applicable  
**Hazard Class** NON-REGULATED PER SP 188  
**EmS-No.** N/A  
**Marine Pollutant** F-A, S-I  
 This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO

**RID** Not applicable

**ADR** Not applicable

**ADN** Not applicable

**15. REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture



**International Regulations**

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

**International Inventories**

**TSCA** Contact supplier for inventory compliance status.  
**DSL/NDSL** Contact supplier for inventory compliance status.  
**EINECS/ELINCS** Contact supplier for inventory compliance status.  
**ENCS** Contact supplier for inventory compliance status.  
**KECL** Contact supplier for inventory compliance status.  
**PICCS** Contact supplier for inventory compliance status.  
**AICS** Contact supplier for inventory compliance status.

**Legend**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Cobalt lithium manganese nickel oxide - 182442-95-1	182442-95-1	40	1.0 0.1
Copper - 7440-50-8	7440-50-8	30	1.0
Aluminum foil - 7429-90-5	7429-90-5	30	1.0
1,3-Propane sultone - 1120-71-4	1120-71-4	1	0.1

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Cobalt lithium manganese nickel oxide 182442-95-1		X		
Copper 7440-50-8		X	X	

**CERCLA**



This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Aluminum foil 7429-90-5			
1,3-Propane sultone 1120-71-4	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Cobalt lithium manganese nickel oxide - 182442-95-1	carcinogen, 5/7/2004
1,3-Propane sultone - 1120-71-4	carcinogen, 1/1/1988

**U.S. State Right-to-Know Regulations**

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Cobalt lithium manganese nickel oxide 182442-95-1	X		X	X	X
Copper 7440-50-8	X	X	X	X	X
Aluminum foil 7429-90-5	X	X	X	X	
Graphite 7782-42-5	X	X	X		
Phosphate(1-), hexafluoro-, lithium 21324-40-3	X				
Ethylene carbonate 96-49-1		X	X		
1,3-Propane sultone 1120-71-4	X	X	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health hazards</b> 1	<b>Flammability</b> 0	<b>Instability</b> 0	<b>Physical and Chemical Properties</b> -
<b>HMIS</b>	<b>Health hazards</b> 0	<b>Flammability</b> 0	<b>Physical hazards</b> 0	<b>Personal Protection</b> X

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Issuing Date** 26-Sep-2024

**Revision Date** 24-Sep-2024



**Revision Note**

No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**

# SAFETY DATA SHEET

Issuing Date 30-Sep-2024

Revision Date 30-Sep-2024

Revision Number 2

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is ©2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION

### Product identifier

**Product Name** Rechargeable Li-ion Battery L24X3PK1 by CosMX

### Other means of identification

**Product Code(s)** 1820025

### Recommended use of the chemical and restrictions on use

**Recommended Use** Lithium Ion Battery

**Restrictions on use** No information available

### Details of the supplier of the safety data sheet

**Supplier Identification** Lenovo LNB laptops

**Address** Songtao Road 696  
shanghai  
shanghai  
201203  
CN

**Telephone** Phone:18116118603

**E-mail** yuanbb1@lenovo.com

### Emergency telephone number

**Company Emergency Phone Number** 18116118603

## 2. HAZARDS IDENTIFICATION

### Classification

Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1B



Specific target organ toxicity (repeated exposure)	Category 1
--	------------

This is a battery. In case of rupture: the above hazards exist.

**Appearance** Black

**Physical state** Solid

**Odor** Odorless

**GHS Label elements, including precautionary statements**

**Danger**

**Hazard statements**

- Causes severe skin burns and eye damage
- May cause an allergic skin reaction
- May cause cancer
- Causes damage to organs through prolonged or repeated exposure



**Precautionary Statements - Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Wear protective gloves/protective clothing/eye protection/face protection
- Wash face, hands and any exposed skin thoroughly after handling
- Contaminated work clothing must not be allowed out of the workplace
- Do not breathe dust/fume/gas/mist/vapors/spray
- Do not eat, drink or smoke when using this product

**Precautionary Statements - Response**

- Immediately call a POISON CENTER or doctor
- Specific treatment (see supplemental first aid instructions on this label)

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Immediately call a POISON CENTER or doctor

**Skin**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower  
Wash contaminated clothing before reuse  
If skin irritation or rash occurs: Get medical advice/attention

**Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing  
Immediately call a POISON CENTER or doctor

**Ingestion**

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

**Precautionary Statements - Storage**

Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other information**



May be harmful if swallowed. May be harmful in contact with skin. Very toxic to aquatic life with long lasting effects.

**Unknown acute toxicity** 51 % of the mixture consists of ingredient(s) of unknown toxicity  
 48 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
 51 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
 51 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
 51 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
 51 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Substance**

Not applicable.

**Mixture**

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lithium Cobalt Oxide (CoLiO <sub>2</sub> )	12190-79-3	50	-	-
Graphite	7782-42-5	30	-	-
Propylene carbonate	108-32-7	10	-	-
Ethylene carbonate	96-49-1	10	-	-
Copper	7440-50-8	10	-	-
Aluminum	7429-90-5	10	-	-
Phosphate(1-), hexafluoro-, lithium	21324-40-3	5	-	-
Glass, oxide	65997-17-3	3	-	-
Nickel	7440-02-0	2	-	-
Carbon black	1333-86-4	2	-	-
Sodium carboxymethyl cellulose	9004-32-4	1	-	-
1,3-Propane sultone	1120-71-4	0.5	-	-
Acrylic acid	79-10-7	0.2	-	-
Titanium dioxide	13463-67-7	0.1	-	-
Oxirane, 2,2'-4-butyliidenebisphenyleneoxymethylene (DGEBA)	25085-99-8	0.1	-	-

### 4. FIRST AID MEASURES

**Description of first aid measures**

**General advice**

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. First aid is upon rupture of sealed battery. In case of rupture:

**Inhalation**

Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel



should) give oxygen. Delayed pulmonary edema may occur. Get immediate medical advice/attention.

<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get immediate medical advice/attention. May cause an allergic skin reaction.
<b>Ingestion</b>	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Wear personal protective clothing (see section 8).

**Most important symptoms and effects, both acute and delayed**

**Symptoms** Burning sensation. Itching. Rashes. Hives.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause sensitization in susceptible persons. Treat symptomatically.

**5. FIRE-FIGHTING MEASURES**

<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Large Fire</b>	CAUTION: Use of water spray when fighting fire may be inefficient.
<b>Unsuitable extinguishing media</b>	Do not scatter spilled material with high pressure water streams.
<b>Specific hazards arising from the chemical</b>	The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.
<b>Hazardous Combustion Products</b>	Carbon oxides.
<b>Explosion Data</b>	
<b>Sensitivity to Mechanical Impact</b>	None.
<b>Sensitivity to Static Discharge</b>	None.
<b>Special protective equipment for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

**6. ACCIDENTAL RELEASE MEASURES**



**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Other Information** Refer to protective measures listed in Sections 7 and 8.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	TWA: 0.02 mg/m <sup>3</sup>	-	
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup> respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m <sup>3</sup> total dust synthetic TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf respirable dust natural (vacated) TWA: 2.5 mg/m <sup>3</sup> respirable dust natural (vacated) TWA: 10 mg/m <sup>3</sup> total dust synthetic (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup> respirable dust
Copper	TWA: 0.2 mg/m <sup>3</sup> fume	TWA: 0.1 mg/m <sup>3</sup> fume	IDLH: 100 mg/m <sup>3</sup> dust, fume



7440-50-8		TWA: 1 mg/m <sup>3</sup> dust and mist (vacated) TWA: 0.1 mg/m <sup>3</sup> Cu dust, fume, mist	and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume	
Aluminum 7429-90-5	TWA: 1 mg/m <sup>3</sup> respirable particulate matter	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust	
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup> F (vacated) TWA: 2.5 mg/m <sup>3</sup>	IDLH: 250 mg/m <sup>3</sup> F	
Glass, oxide 65997-17-3	TWA: 1 fiber/cm <sup>3</sup> respirable fibers: length >5 µm, aspect ratio >=3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m <sup>3</sup> inhalable fraction	-		
Nickel 7440-02-0	TWA: 1.5 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> (vacated) TWA: 1 mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> TWA: 0.015 mg/m <sup>3</sup>	
Carbon black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH	
Acrylic acid 79-10-7	TWA: 2 ppm S*	(vacated) TWA: 10 ppm (vacated) TWA: 30 mg/m <sup>3</sup> (vacated) S*	TWA: 2 ppm TWA: 6 mg/m <sup>3</sup>	
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>	
Chemical name	Alberta	British Columbia	Ontario TWA/EV	Quebec
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>
Aluminum 7429-90-5	TWA: 10 mg/m <sup>3</sup>	TWA: 1.0 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>
Glass, oxide 65997-17-3	TWA: 5 mg/m <sup>3</sup> TWA: 1 fibre/cm <sup>3</sup>	TWA: 1 fibre/cm <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	TWA: 1 fibre/cm <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	TWA: 1 fibre/cm <sup>3</sup> TWA: 5 mg/m <sup>3</sup>
Nickel 7440-02-0	TWA: 1.5 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 1.5 mg/m <sup>3</sup>
Carbon black 1333-86-4	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>
1,3-Propane sultone 1120-71-4		TWA:	TWA:	TWA:
Acrylic acid	TWA: 2 ppm	TWA: 2 ppm	TWA: 2 ppm	TWA: 2 ppm

79-10-7	TWA: 5.9 mg/m <sup>3</sup> Skin	Skin	Skin	TWA: 5.9 mg/m <sup>3</sup> Skin
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

**Appropriate engineering controls**

**Engineering controls** Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Face protection shield.

**Hand protection** Wear suitable gloves. Impervious gloves.

**Skin and body protection** Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

**Respiratory protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

**Physical state** Solid  
**Appearance** Black  
**Odor** Odorless  
**Color** No information available  
**Odor Threshold** No information available

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	No data available	None known
Water Solubility	Insoluble in water	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water <sup>1</sup>		



<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>	No data available	None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	No data available	None known

**Other Information**

<b>Explosive properties</b>	No information available
<b>Oxidizing properties</b>	No information available
<b>Softening Point</b>	No information available
<b>Molecular Weight</b>	No information available
<b>VOC Content (%)</b>	No information available
<b>Liquid Density</b>	No information available
<b>Bulk Density</b>	No information available
<b>Particle Size</b>	No information available
<b>Particle Size Distribution</b>	No information available

**10. STABILITY AND REACTIVITY**

<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of Hazardous Reactions</b>	None under normal processing.
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Exposure to air or moisture over prolonged periods.
<b>Incompatible materials</b>	Acids. Bases. Oxidizing agent.
<b>Hazardous Decomposition Products</b>	Carbon oxides.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

<b>Product Information</b>	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:
<b>Inhalation</b>	Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May be harmful in contact with skin.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms** Redness. Burning. May cause blindness. Coughing and/ or wheezing. Itching. Rashes. Hives.

**Numerical measures of toxicity**

**Acute toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)** 4,583.60 mg/kg  
**ATEmix (dermal)** 2,940.00 mg/kg

**Unknown acute toxicity** 51 % of the mixture consists of ingredient(s) of unknown toxicity  
48 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
51 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
51 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
51 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
51 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

**Product Information**

**Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Lithium Cobalt Oxide (CoLiO2)	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	> 5.05 mg/L ( Rat ) 4 h
Graphite	-	-	> 2000 mg/m <sup>3</sup> ( Rat ) 4 h
Propylene carbonate	= 29000 mg/kg ( Rat )	> 3000 mg/kg ( Rabbit )	-
Ethylene carbonate	= 10 g/kg ( Rat )	> 26420 mg/kg ( Rabbit )	> 730 mg/m <sup>3</sup> ( Rat ) 8 h
Copper	-	-	> 5.11 mg/L ( Rat ) 4 h
Aluminum	-	-	> 0.888 mg/L ( Rat ) 4 h
Nickel	> 9000 mg/kg ( Rat )	-	> 10.2 mg/L ( Rat ) 1 h
Carbon black	> 10000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 4.6 mg/m <sup>3</sup> ( Rat ) 4 h
Sodium carboxymethyl cellulose	= 27000 mg/kg ( Rat )	-	> 5800 mg/m <sup>3</sup> ( Rat ) 4 h
1,3-Propane sultone	= 157 mg/kg ( Rat )	-	-
Acrylic acid	= 193 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3.6 mg/L ( Rat ) 4 h = 11.1 mg/L ( Rat ) 1 h
Titanium dioxide	> 2000 mg/kg ( Rat )	-	> 5.09 mg/L ( Rat ) 4 h

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes burns.

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Risk of serious damage to eyes. Causes burns.

**Respiratory or skin sensitization** May cause sensitization by skin contact.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer. This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product.



The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	A3	Group 2B	Reasonably Anticipated	X
Glass, oxide 65997-17-3	-	Group 3	-	-
Nickel 7440-02-0	-	Group 2B	Reasonably Anticipated	X
Carbon black 1333-86-4	A3	Group 2B	-	X
1,3-Propane sultone 1120-71-4	A3	Group 2A	Reasonably Anticipated	X
Acrylic acid 79-10-7	-	Group 3	-	-
Titanium dioxide 13463-67-7	A3	Group 2B	-	X

**Legend**

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

**NTP (National Toxicology Program)**

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

<b>Reproductive toxicity</b>	No information available.
<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	No information available.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Graphite	No data available	96h LC50: > 100 mg/L (Danio rerio)	No data available	No data available
Propylene carbonate	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: > 1000 mg/L (Cyprinus carpio)	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L (Daphnia magna)
Ethylene carbonate	No data available	96h LC50: > 100 mg/L (Oncorhynchus mykiss)	No data available	No data available
Copper	72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L	No data available	48h EC50: = 0.03 mg/L (Daphnia magna)



	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata)	(Pimephales promelas) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 0.112 mg/L (Poecilia reticulata)		
Nickel	72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 100 mg/L (Brachydanio rerio) 96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio)	No data available	48h EC50: > 100 mg/L (Daphnia magna) 48h EC50: = 1 mg/L (Daphnia magna)
Acrylic acid	96h EC50: = 0.17 mg/L (Pseudokirchneriella subcapitata) 72h EC50: = 0.04 mg/L (Desmodesmus subspicatus)	96h LC50: = 222 mg/L (Brachydanio rerio)	No data available	48h EC50: = 95 mg/L (Daphnia magna)

**Persistence and Degradability** No information available.

**Bioaccumulation**

**Component Information**

Chemical name	Partition coefficient
Propylene carbonate	0.48
Ethylene carbonate	0.11
Acrylic acid	0.46

**Mobility** No information available.

**Other adverse effects** No information available.

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Waste from residues/unused products** Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Do not reuse empty containers.

**California Waste Codes** 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.



Chemical name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	Toxic
Aluminum 7429-90-5	Ignitable powder
Nickel 7440-02-0	Toxic powder Ignitable powder

**14. TRANSPORT INFORMATION**

**Note:** The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)  
Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

**DOT**  
**Proper Shipping Name**  
**Hazard Class**  
**Emergency Response Guide Number**

NOT REGULATED  
 NON-REGULATED  
 N/A  
 147

**TDG** Not applicable

**MEX** Not applicable

**ICAO** Not applicable

**IATA**  
**UN-No.** UN3480  
**Proper Shipping Name** LITHIUM ION BATTERIES  
**Hazard Class** 9  
**ERG Code** 12FZ  
**Description** UN3480, LITHIUM ION BATTERIES, 9

**IMDG/IMO**  
**Proper Shipping Name** Not applicable  
**Hazard Class** NON-REGULATED PER SP 188  
**EmS-No.** N/A  
**Marine Pollutant** F-A, S-I  
 This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO

**RID** Not applicable

**ADR** Not applicable  
**Tunnel restriction code** (E)

**ADN** Not applicable



## 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Regulations

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

#### International Inventories

<b>TSCA</b>	Contact supplier for inventory compliance status.
<b>DSL/NDSL</b>	Contact supplier for inventory compliance status.
<b>EINECS/ELINCS</b>	Contact supplier for inventory compliance status.
<b>ENCS</b>	Contact supplier for inventory compliance status.
<b>KECL</b>	Contact supplier for inventory compliance status.
<b>PICCS</b>	Contact supplier for inventory compliance status.
<b>AICS</b>	Contact supplier for inventory compliance status.

#### Legend

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

#### US Federal Regulations

##### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) - 12190-79-3	12190-79-3	50	0.1
Copper - 7440-50-8	7440-50-8	10	1.0
Aluminum - 7429-90-5	7429-90-5	10	1.0
Nickel - 7440-02-0	7440-02-0	2	0.1
1,3-Propane sultone - 1120-71-4	1120-71-4	0.5	0.1
Acrylic acid - 79-10-7	79-10-7	0.2	1.0

##### **SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

##### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper		X	X	



7440-50-8			
Nickel 7440-02-0		X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
1,3-Propane sultone 1120-71-4	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ
Acrylic acid 79-10-7	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Carbon black - 1333-86-4	Carcinogen
Nickel - 7440-02-0	carcinogen, 10/1/1989 (metallic)
1,3-Propane sultone - 1120-71-4	carcinogen, 1/1/1988
Titanium dioxide - 13463-67-7	Carcinogen

**U.S. State Right-to-Know Regulations**

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	X		X	X	X
Graphite 7782-42-5	X	X	X		
Ethylene carbonate 96-49-1		X	X		
Copper 7440-50-8	X	X	X	X	X
Aluminum 7429-90-5	X	X	X	X	
Phosphate(1-), hexafluoro-, lithium 21324-40-3	X				
Nickel 7440-02-0	X	X	X	X	X
Carbon black 1333-86-4	X	X	X		X
1,3-Propane sultone 1120-71-4	X	X	X	X	X
Acrylic acid 79-10-7	X	X	X	X	X
Titanium dioxide	X	X	X		



---

13463-67-7					
------------	--	--	--	--	--

**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health hazards</b> 1	<b>Flammability</b> 0	<b>Instability</b> 0	<b>Physical and Chemical Properties</b> -
<b>HMIS</b>	<b>Health hazards</b> 0	<b>Flammability</b> 0	<b>Physical hazards</b> 0	<b>Personal Protection</b> X

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Issuing Date** 30-Sep-2024

**Revision Date** 30-Sep-2024

**Revision Note** No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**



# SAFETY DATA SHEET

Issuing Date 26-Sep-2024

Revision Date 24-Sep-2024

Revision Number 1

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is ©2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION

### Product identifier

**Product Name** Rechargeable Li-ion Battery L24B3PK2 by BYD

### Other means of identification

**Product Code(s)** 1820021

### Recommended use of the chemical and restrictions on use

**Recommended Use** Lithium Ion Battery

**Restrictions on use** No information available

### Details of the supplier of the safety data sheet

**Supplier Identification** Lenovo LNB laptops

**Address** Songtao Road 696  
shanghai  
shanghai  
201203  
CN

**Telephone** Phone:18116118603

**E-mail** yuanbb1@lenovo.com

### Emergency telephone number

**Company Emergency Phone Number** 18116118603

## 2. HAZARDS IDENTIFICATION

### Classification

Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1B



Specific target organ toxicity (repeated exposure)	Category 1
--	------------

This is a battery. In case of rupture: the above hazards exist.

**Appearance** Black

**Physical state** Solid

**Odor** Odorless

**GHS Label elements, including precautionary statements**

**Danger**

**Hazard statements**

Causes severe skin burns and eye damage  
May cause an allergic skin reaction  
May cause cancer  
Causes damage to organs through prolonged or repeated exposure



**Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Wear protective gloves/protective clothing/eye protection/face protection  
Wash face, hands and any exposed skin thoroughly after handling  
Contaminated work clothing must not be allowed out of the workplace  
Do not breathe dust/fume/gas/mist/vapors/spray  
Do not eat, drink or smoke when using this product

**Precautionary Statements - Response**

Immediately call a POISON CENTER or doctor  
Specific treatment (see supplemental first aid instructions on this label)

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Immediately call a POISON CENTER or doctor

**Skin**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower  
Wash contaminated clothing before reuse  
If skin irritation or rash occurs: Get medical advice/attention

**Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing  
Immediately call a POISON CENTER or doctor

**Ingestion**

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

**Precautionary Statements - Storage**

Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other information**



May be harmful in contact with skin. Very toxic to aquatic life with long lasting effects.

**Unknown acute toxicity** 34 % of the mixture consists of ingredient(s) of unknown toxicity  
 27 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
 34 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
 34 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
 34 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
 34 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Substance**

Not applicable.

**Mixture**

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lithium Cobalt Oxide (CoLiO2)	12190-79-3	45	-	-
Graphite	7782-42-5	25	-	-
Propylene carbonate	108-32-7	10	-	-
Propyl propionate	106-36-5	10	-	-
Ethylene carbonate	96-49-1	10	-	-
Copper	7440-50-8	10	-	-
Phosphate(1-), hexafluoro-, lithium	21324-40-3	5	-	-
Nickel	7440-02-0	5	-	-
Aluminum	7429-90-5	5	-	-
Ci 77266	1333-86-4	2	-	-

### 4. FIRST AID MEASURES

**Description of first aid measures**

**General advice**

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. First aid is upon rupture of sealed battery. In case of rupture:

**Inhalation**

Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get immediate medical advice/attention.

**Eye contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

**Skin contact**

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get immediate medical advice/attention. May cause an allergic skin reaction.



---

<b>Ingestion</b>	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Wear personal protective clothing (see section 8).

**Most important symptoms and effects, both acute and delayed**

**Symptoms** Burning sensation. Itching. Rashes. Hives.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause sensitization in susceptible persons. Treat symptomatically.

**5. FIRE-FIGHTING MEASURES**

<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Large Fire</b>	CAUTION: Use of water spray when fighting fire may be inefficient.
<b>Unsuitable extinguishing media</b>	Do not scatter spilled material with high pressure water streams.
<b>Specific hazards arising from the chemical</b>	The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.
<b>Hazardous Combustion Products</b>	Carbon oxides.
<b>Explosion Data</b>	
<b>Sensitivity to Mechanical Impact</b>	None.
<b>Sensitivity to Static Discharge</b>	None.
<b>Special protective equipment for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Other Information** Refer to protective measures listed in Sections 7 and 8.

**Methods and material for containment and cleaning up**



**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	TWA: 0.02 mg/m <sup>3</sup>	-	
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup> respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m <sup>3</sup> total dust synthetic TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf respirable dust natural (vacated) TWA: 2.5 mg/m <sup>3</sup> respirable dust natural (vacated) TWA: 10 mg/m <sup>3</sup> total dust synthetic (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup> respirable dust
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> fume	TWA: 0.1 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> dust and mist (vacated) TWA: 0.1 mg/m <sup>3</sup> Cu dust, fume, mist	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup> F (vacated) TWA: 2.5 mg/m <sup>3</sup>	IDLH: 250 mg/m <sup>3</sup> F
Nickel 7440-02-0	TWA: 1.5 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> (vacated) TWA: 1 mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> TWA: 0.015 mg/m <sup>3</sup>
Aluminum	TWA: 1 mg/m <sup>3</sup> respirable	TWA: 15 mg/m <sup>3</sup> total dust	TWA: 10 mg/m <sup>3</sup> total dust



7429-90-5	particulate matter	TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 5 mg/m <sup>3</sup> respirable dust	
Ci 77266 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH	
Chemical name	Alberta	British Columbia	Ontario TWAEV	Quebec
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>
Nickel 7440-02-0	TWA: 1.5 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 1.5 mg/m <sup>3</sup>
Aluminum 7429-90-5	TWA: 10 mg/m <sup>3</sup>	TWA: 1.0 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
Ci 77266 1333-86-4	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

**Appropriate engineering controls**

**Engineering controls**

Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Face protection shield.

**Hand protection**

Wear suitable gloves. Impervious gloves.

**Skin and body protection**

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

**Respiratory protection**

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**General hygiene considerations**

Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES**



**Information on basic physical and chemical properties**

Physical state	Solid
Appearance	Black
Odor	Odorless
Color	No information available
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	No data available	None known
Water Solubility	Insoluble in water	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water <sup>1</sup>		
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

**Other Information**

Explosive properties	No information available
Oxidizing properties	No information available
Softening Point	No information available
Molecular Weight	No information available
VOC Content (%)	No information available
Liquid Density	No information available
Bulk Density	No information available
Particle Size	No information available
Particle Size Distribution	No information available

**10. STABILITY AND REACTIVITY**

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Exposure to air or moisture over prolonged periods.
Incompatible materials	Acids. Bases. Oxidizing agent.
Hazardous Decomposition Products	Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:
<b>Inhalation</b>	Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May be harmful in contact with skin.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Symptoms</b>	Redness. Burning. May cause blindness. Coughing and/ or wheezing. Itching. Rashes. Hives.
-----------------	---

### Numerical measures of toxicity

#### Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

<b>ATEmix (oral)</b>	5,424.30 mg/kg
<b>ATEmix (dermal)</b>	3,816.50 mg/kg
<b>ATEmix (inhalation-gas)</b>	29,700.00 ppm
<b>ATEmix (inhalation-dust/mist)</b>	9.90 mg/L
<b>ATEmix (inhalation-vapor)</b>	72.60 mg/L

<b>Unknown acute toxicity</b>	34 % of the mixture consists of ingredient(s) of unknown toxicity
	27 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
	34 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
	34 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
	34 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
	34 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

#### Product Information

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Lithium Cobalt Oxide (CoLiO2)	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	> 5.05 mg/L ( Rat ) 4 h
Graphite	-	-	> 2000 mg/m <sup>3</sup> ( Rat ) 4 h



Propylene carbonate	= 29000 mg/kg ( Rat )	> 3000 mg/kg ( Rabbit )	-
Propyl propionate	= 10331 mg/kg ( Rat )	= 16 mL/kg ( Rabbit )	-
Ethylene carbonate	= 10 g/kg ( Rat )	> 26420 mg/kg ( Rabbit )	> 730 mg/m <sup>3</sup> ( Rat ) 8 h
Copper	-	-	> 5.11 mg/L ( Rat ) 4 h
Nickel	> 9000 mg/kg ( Rat )	-	> 10.2 mg/L ( Rat ) 1 h
Aluminum	-	-	> 0.888 mg/L ( Rat ) 4 h
Ci 77266	> 10000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 4.6 mg/m <sup>3</sup> ( Rat ) 4 h

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Skin corrosion/irritation</b>	Classification based on data available for ingredients. Causes burns.
<b>Serious eye damage/eye irritation</b>	Classification based on data available for ingredients. Risk of serious damage to eyes. Causes burns.
<b>Respiratory or skin sensitization</b>	May cause sensitization by skin contact.
<b>Germ cell mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	A3	Group 2B	Reasonably Anticipated	X
Nickel 7440-02-0	-	Group 2B	Reasonably Anticipated	X
Ci 77266 1333-86-4	A3	Group 2B	-	X

**Legend**

- ACGIH (American Conference of Governmental Industrial Hygienists)**  
A3 - Animal Carcinogen
- IARC (International Agency for Research on Cancer)**  
Group 2B - Possibly Carcinogenic to Humans
- NTP (National Toxicology Program)**  
Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
- OSHA (Occupational Safety and Health Administration of the US Department of Labor)**  
X - Present

<b>Reproductive toxicity</b>	No information available.
<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	No information available.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
---------------	----------------------	------	-------------	-----------



			microorganisms	
Graphite	No data available	96h LC50: > 100 mg/L (Danio rerio)	No data available	No data available
Propylene carbonate	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: > 1000 mg/L (Cyprinus carpio)	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L (Daphnia magna)
Ethylene carbonate	No data available	96h LC50: > 100 mg/L (Oncorhynchus mykiss)	No data available	No data available
Copper	72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 0.112 mg/L (Poecilia reticulata)	No data available	48h EC50: = 0.03 mg/L (Daphnia magna)
Nickel	72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 100 mg/L (Brachydanio rerio) 96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio)	No data available	48h EC50: > 100 mg/L (Daphnia magna) 48h EC50: = 1 mg/L (Daphnia magna)

**Persistence and Degradability** No information available.

**Bioaccumulation**

**Component Information**

Chemical name	Partition coefficient
Propylene carbonate	0.48
Ethylene carbonate	0.11

**Mobility** No information available.

**Other adverse effects** No information available.

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Waste from residues/unused products** Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Do not reuse empty containers.



**California Waste Codes** 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	Toxic
Nickel 7440-02-0	Toxic powder Ignitable powder
Aluminum 7429-90-5	Ignitable powder

**14. TRANSPORT INFORMATION**

**Note:** The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)  
Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

**DOT** NOT REGULATED  
**Proper Shipping Name** NON-REGULATED  
**Hazard Class** N/A  
**Emergency Response Guide Number** 147

**TDG** Not applicable

**MEX** Not applicable

**ICAO** Not applicable

**IATA**  
**UN-No.** UN3480  
**Proper Shipping Name** LITHIUM ION BATTERIES  
**Hazard Class** 9  
**ERG Code** 12FZ  
**Description** UN3480, LITHIUM ION BATTERIES, 9

**IMDG/IMO** Not applicable  
**Proper Shipping Name** NON-REGULATED PER SP 188  
**Hazard Class** N/A  
**EmS-No.** F-A, S-I  
**Marine Pollutant** This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO

**RID** Not applicable



**ADR** Not applicable

**ADN** Not applicable

**15. REGULATORY INFORMATION**

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

**International Regulations**

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

**International Inventories**

**TSCA** Contact supplier for inventory compliance status.  
**DSL/NDSL** Contact supplier for inventory compliance status.  
**EINECS/ELINCS** Contact supplier for inventory compliance status.  
**ENCS** Contact supplier for inventory compliance status.  
**KECL** Contact supplier for inventory compliance status.  
**PICCS** Contact supplier for inventory compliance status.  
**AICS** Contact supplier for inventory compliance status.

**Legend**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Lithium Cobalt Oxide (CoLiO2) - 12190-79-3	12190-79-3	45	0.1
Copper - 7440-50-8	7440-50-8	10	1.0
Nickel - 7440-02-0	7440-02-0	5	0.1
Aluminum - 7429-90-5	7429-90-5	5	1.0

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable	CWA - Toxic Pollutants	CWA - Priority	CWA - Hazardous
---------------	------------------	------------------------	----------------	-----------------



	Quantities		Pollutants	Substances
Copper 7440-50-8		X	X	
Nickel 7440-02-0		X	X	

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Nickel - 7440-02-0	carcinogen, 10/1/1989 (metallic)
Ci 77266 - 1333-86-4	carcinogen, 2/21/2003 (airborne, unbound particles of respirable size)

**U.S. State Right-to-Know Regulations**

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	X		X	X	X
Graphite 7782-42-5	X	X	X		
Propyl propionate 106-36-5		X	X		
Ethylene carbonate 96-49-1		X	X		
Copper 7440-50-8	X	X	X	X	X
Phosphate(1-), hexafluoro-, lithium 21324-40-3	X				
Nickel 7440-02-0	X	X	X	X	X
Aluminum 7429-90-5	X	X	X	X	
Ci 77266 1333-86-4	X	X	X		X

**16. OTHER INFORMATION**

**NFPA** Health hazards 1 Flammability 0 Instability 0 Physical and Chemical Properties -



---

**HMIS**                      **Health hazards** 0                      **Flammability** 0                      **Physical hazards** 0                      **Personal Protection** X

**Prepared By**                      Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Issuing Date**                      26-Sep-2024

**Revision Date**                      24-Sep-2024

**Revision Note**                      No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**

# SAFETY DATA SHEET

Issuing Date 25-Oct-2024

Revision Date 27-Sep-2024

Revision Number 1

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is ©2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION

### Product identifier

**Product Name** Rechargeable Li-ion Battery L24D3PK3 by SUNWODA

### Other means of identification

**Product Code(s)** 1820762

### Recommended use of the chemical and restrictions on use

**Recommended Use** Lithium Ion Battery

**Restrictions on use** No information available

### Details of the supplier of the safety data sheet

**Supplier Identification** Lenovo LNB laptops

**Address** Songtao Road 696  
shanghai  
shanghai  
201203  
CN

**Telephone** Phone:18116118603

**E-mail** yuanbb1@lenovo.com

### Emergency telephone number

**Company Emergency Phone Number** 18116118603

## 2. HAZARDS IDENTIFICATION

### Classification

Acute toxicity - Inhalation (Vapors)	Category 1
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1



Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1

This is a battery. In case of rupture: the above hazards exist.

**Appearance** No information available

**Physical state** Solid

**Odor** No information available

**GHS Label elements, including precautionary statements**

**Danger**

**Hazard statements**

- Fatal if inhaled
- Causes severe skin burns and eye damage
- May cause an allergic skin reaction
- May cause cancer
- Causes damage to organs through prolonged or repeated exposure



**Precautionary Statements - Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Wear protective gloves/protective clothing/eye protection/face protection
- Do not breathe dust/fume/gas/mist/vapors/spray
- Use only outdoors or in a well-ventilated area
- Wear respiratory protection
- Wash face, hands and any exposed skin thoroughly after handling
- Contaminated work clothing must not be allowed out of the workplace
- Do not eat, drink or smoke when using this product

**Precautionary Statements - Response**

- Specific treatment is urgent (see supplemental first aid instructions on this label)
- Immediately call a POISON CENTER or doctor

**Eyes**

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- Immediately call a POISON CENTER or doctor

**Skin**

- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
- Wash contaminated clothing before reuse
- If skin irritation or rash occurs: Get medical advice/attention

**Inhalation**

- IF INHALED: Remove person to fresh air and keep comfortable for breathing
- Immediately call a POISON CENTER or doctor

**Ingestion**

- IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

**Precautionary Statements - Storage**

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other information**

May be harmful if swallowed. May be harmful in contact with skin. Very toxic to aquatic life with long lasting effects.

**Unknown acute toxicity** 52 % of the mixture consists of ingredient(s) of unknown toxicity

- 49 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
- 52 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
- 52 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
- 52 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
- 52 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Substance**

Not applicable.

**Mixture**

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Cobalt lithium manganese nickel oxide	182442-95-1	50	-	-
Graphite	7782-42-5	30	-	-
Ci 77400	7440-50-8	15	-	-
Propylene carbonate	108-32-7	10	-	-
Ethylene carbonate	96-49-1	10	-	-
Ci 77000	7429-90-5	10	-	-
Phosphate(1-), hexafluoro-, lithium	21324-40-3	5	-	-
Nickel	7440-02-0	2	-	-
Ci 77266	1333-86-4	2	-	-
Sodium carboxymethyl cellulose	9004-32-4	1	-	-
1,3-Propane sultone	1120-71-4	0.5	-	-

**4. FIRST AID MEASURES**

**Description of first aid measures**

**General advice**

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. First aid is upon rupture of sealed battery. In case of rupture:

**Inhalation**

If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Do not breathe dust. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get immediate medical advice/attention.



---

<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get immediate medical advice/attention. May cause an allergic skin reaction.
<b>Ingestion</b>	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Do not breathe dust. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

**Most important symptoms and effects, both acute and delayed**

<b>Symptoms</b>	Coughing and/ or wheezing. Difficulty in breathing. Burning sensation. Itching. Rashes. Hives.
-----------------	--

**Indication of any immediate medical attention and special treatment needed**

<b>Note to physicians</b>	Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause sensitization in susceptible persons. Treat symptomatically.
---------------------------	---

**5. FIRE-FIGHTING MEASURES**

<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Large Fire</b>	CAUTION: Use of water spray when fighting fire may be inefficient.
<b>Unsuitable extinguishing media</b>	Do not scatter spilled material with high pressure water streams.
<b>Specific hazards arising from the chemical</b>	The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.
<b>Hazardous Combustion Products</b>	Carbon oxides.
<b>Explosion Data</b>	
<b>Sensitivity to Mechanical Impact</b>	None.
<b>Sensitivity to Static Discharge</b>	None.
<b>Special protective equipment for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

**6. ACCIDENTAL RELEASE MEASURES**



**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Avoid generation of dust. Do not breathe dust. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Other Information** Refer to protective measures listed in Sections 7 and 8.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not breathe dust. Avoid generation of dust. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Protect from moisture. Store away from other materials.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Cobalt lithium manganese nickel oxide 182442-95-1	TWA: 0.02 mg/m <sup>3</sup> Co inhalable particulate matter TWA: 0.02 mg/m <sup>3</sup> Mn respirable particulate matter TWA: 0.1 mg/m <sup>3</sup> Mn inhalable particulate matter	(vacated) Ceiling: 5 mg/m <sup>3</sup> Ceiling: 5 mg/m <sup>3</sup> Mn	IDLH: 500 mg/m <sup>3</sup> Mn IDLH: 10 mg/m <sup>3</sup> Ni TWA: 1 mg/m <sup>3</sup> Mn TWA: 0.015 mg/m <sup>3</sup> except Nickel carbonyl Ni STEL: 3 mg/m <sup>3</sup> Mn
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup> respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m <sup>3</sup> total dust synthetic TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf respirable dust natural (vacated) TWA: 2.5 mg/m <sup>3</sup> respirable dust natural (vacated) TWA: 10 mg/m <sup>3</sup> total dust synthetic	IDLH: 1250 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup> respirable dust



		(vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf natural		
Ci 77400 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> fume	TWA: 0.1 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> dust and mist (vacated) TWA: 0.1 mg/m <sup>3</sup> Cu dust, fume, mist	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume	
Ci 77000 7429-90-5	TWA: 1 mg/m <sup>3</sup> respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust	
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup> F (vacated) TWA: 2.5 mg/m <sup>3</sup>	IDLH: 250 mg/m <sup>3</sup> F	
Nickel 7440-02-0	TWA: 1.5 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> (vacated) TWA: 1 mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> TWA: 0.015 mg/m <sup>3</sup>	
Ci 77266 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH	
<b>Chemical name</b>	<b>Alberta</b>	<b>British Columbia</b>	<b>Ontario TWA/EV</b>	<b>Quebec</b>
Cobalt lithium manganese nickel oxide 182442-95-1	TWA: 0.02 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 0.05 mg/m <sup>3</sup> TWA: 0.02 mg/m <sup>3</sup>
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Ci 77400 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>
Ci 77000 7429-90-5	TWA: 10 mg/m <sup>3</sup>	TWA: 1.0 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>
Nickel 7440-02-0	TWA: 1.5 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 1.5 mg/m <sup>3</sup>
Ci 77266 1333-86-4	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>
1,3-Propane sultone 1120-71-4		TWA:	TWA:	TWA:

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

**Appropriate engineering controls**

**Engineering controls**

- Showers
- Eyewash stations
- Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Face protection shield.



<b>Hand protection</b>	Wear suitable gloves. Impervious gloves.
<b>Skin and body protection</b>	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.
<b>Respiratory protection</b>	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
<b>General hygiene considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not breathe dust. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	Solid
<b>Appearance</b>	No information available
<b>Odor</b>	No information available
<b>Color</b>	No information available
<b>Odor Threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
<b>pH</b>	No data available	None known
<b>Melting / freezing point</b>	No data available	None known
<b>Boiling point / boiling range</b>	No data available	None known
<b>Flash Point</b>	No data available	None known
<b>Evaporation Rate</b>	No data available	None known
<b>Flammability (solid, gas)</b>	No data available	None known
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit</b>	No data available	
<b>Lower flammability limit</b>	No data available	
<b>Vapor pressure</b>	No data available	None known
<b>Vapor density</b>	No data available	None known
<b>Relative density</b>	No data available	None known
<b>Water Solubility</b>	Insoluble in water	
<b>Solubility(ies)</b>	No data available	None known
<b>Partition coefficient: n-octanol/water<sup>1</sup></b>		
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>	No data available	None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	No data available	None known

### Other Information

<b>Explosive properties</b>	No information available
<b>Oxidizing properties</b>	No information available
<b>Softening Point</b>	No information available
<b>Molecular Weight</b>	No information available
<b>VOC Content (%)</b>	No information available
<b>Liquid Density</b>	No information available
<b>Bulk Density</b>	No information available
<b>Particle Size</b>	No information available
<b>Particle Size Distribution</b>	No information available

## 10. STABILITY AND REACTIVITY

<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of Hazardous Reactions</b>	None under normal processing.
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Excessive heat. Exposure to air or moisture over prolonged periods.
<b>Incompatible materials</b>	Acids. Bases. Oxidizing agent.
<b>Hazardous Decomposition Products</b>	Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:
<b>Inhalation</b>	Specific test data for the substance or mixture is not available. Fatal if inhaled. (based on components). Corrosive by inhalation. Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May be harmful in contact with skin.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Symptoms</b>	Coughing and/ or wheezing. Difficulty in breathing. Redness. Burning. May cause blindness. Itching. Rashes. Hives.
-----------------	--

### Numerical measures of toxicity

#### Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document  
ATEmix (oral) 4,495.40 mg/kg

ATEmix (dermal) 2,880.00 mg/kg  
ATEmix (inhalation-vapor) 0.481 mg/L

**Unknown acute toxicity** 52 % of the mixture consists of ingredient(s) of unknown toxicity  
49 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
52 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
52 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
52 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
52 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Product Information			
Component Information			
Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Graphite	-	-	> 2000 mg/m <sup>3</sup> ( Rat ) 4 h
Ci 77400	-	-	> 5.11 mg/L ( Rat ) 4 h
Propylene carbonate	= 29000 mg/kg ( Rat )	> 3000 mg/kg ( Rabbit )	-
Ethylene carbonate	= 10 g/kg ( Rat )	> 26420 mg/kg ( Rabbit )	> 730 mg/m <sup>3</sup> ( Rat ) 8 h
Ci 77000	-	-	> 0.888 mg/L ( Rat ) 4 h
Nickel	> 9000 mg/kg ( Rat )	-	> 10.2 mg/L ( Rat ) 1 h
Ci 77266	> 10000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 4.6 mg/m <sup>3</sup> ( Rat ) 4 h
Sodium carboxymethyl cellulose	= 27000 mg/kg ( Rat )	-	> 5800 mg/m <sup>3</sup> ( Rat ) 4 h
1,3-Propane sultone	= 157 mg/kg ( Rat )	-	-

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes burns.  
**Serious eye damage/eye irritation** Classification based on data available for ingredients. Risk of serious damage to eyes. Causes burns.  
**Respiratory or skin sensitization** May cause sensitization by skin contact.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Cobalt lithium manganese nickel oxide 182442-95-1	A3	Group 2B Group 1	Reasonably Anticipated Known	X
Nickel 7440-02-0	-	Group 2B	Reasonably Anticipated	X
Ci 77266 1333-86-4	A3	Group 2B	-	X
1,3-Propane sultone 1120-71-4	A3	Group 2A	Reasonably Anticipated	X

**Legend**

**ACGIH (American Conference of Governmental Industrial Hygienists)**  
A3 - Animal Carcinogen  
**IARC (International Agency for Research on Cancer)**  
Group 1 - Carcinogenic to Humans  
Group 2A - Probably Carcinogenic to Humans  
Group 2B - Possibly Carcinogenic to Humans



**NTP (National Toxicology Program)**

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

<b>Reproductive toxicity</b>	No information available.
<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	No information available.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Graphite	No data available	96h LC50: > 100 mg/L (Danio rerio)	No data available	No data available
Ci 77400	72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 0.112 mg/L (Poecilia reticulata)	No data available	48h EC50: = 0.03 mg/L (Daphnia magna)
Propylene carbonate	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: > 1000 mg/L (Cyprinus carpio)	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L (Daphnia magna)
Ethylene carbonate	No data available	96h LC50: > 100 mg/L (Oncorhynchus mykiss)	No data available	No data available
Nickel	72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 100 mg/L (Brachydanio rerio) 96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio)	No data available	48h EC50: > 100 mg/L (Daphnia magna) 48h EC50: = 1 mg/L (Daphnia magna)

**Persistence and Degradability** No information available.

**Bioaccumulation**



**Component Information**

Chemical name	Partition coefficient
Propylene carbonate	0.48
Ethylene carbonate	0.11

**Mobility** No information available.

**Other adverse effects** No information available.

**13. DISPOSAL CONSIDERATIONS**

Waste treatment methods

**Waste from residues/unused products** Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Do not reuse empty containers.

**California Waste Codes** 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Cobalt lithium manganese nickel oxide 182442-95-1	Toxic
Ci 77000 7429-90-5	Ignitable powder
Nickel 7440-02-0	Toxic powder Ignitable powder

**14. TRANSPORT INFORMATION**

**Note:** The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)  
Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

**DOT** NOT REGULATED  
**Proper Shipping Name** NON-REGULATED  
**Hazard Class** N/A  
**Emergency Response Guide Number** 147

**TDG** Not applicable



<b><u>MEX</u></b>	Not applicable
<b><u>ICAO</u></b>	Not applicable
<b><u>IATA</u></b>	
<b>UN-No.</b>	UN3480
<b>Proper Shipping Name</b>	LITHIUM ION BATTERIES
<b>Hazard Class</b>	9
<b>ERG Code</b>	12FZ
<b>Description</b>	UN3480, LITHIUM ION BATTERIES, 9
<b><u>IMDG/IMO</u></b>	Not applicable
<b>Proper Shipping Name</b>	NON-REGULATED PER SP 188
<b>Hazard Class</b>	N/A
<b>EmS-No.</b>	F-A, S-I
<b>Marine Pollutant</b>	This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO
<b><u>RID</u></b>	Not applicable
<b><u>ADR</u></b>	Not applicable
<b>Tunnel restriction code</b>	(E)
<b><u>ADN</u></b>	Not applicable

## 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Regulations

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

#### International Inventories

<b>TSCA</b>	Contact supplier for inventory compliance status.
<b>DSL/NDSL</b>	Contact supplier for inventory compliance status.
<b>EINECS/ELINCS</b>	Contact supplier for inventory compliance status.
<b>ENCS</b>	Contact supplier for inventory compliance status.
<b>KECL</b>	Contact supplier for inventory compliance status.
<b>PICCS</b>	Contact supplier for inventory compliance status.
<b>AICS</b>	Contact supplier for inventory compliance status.

#### Legend

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

#### US Federal Regulations

**SARA 313**



Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Cobalt lithium manganese nickel oxide - 182442-95-1	182442-95-1	50	1.0 0.1
Ci 77400 - 7440-50-8	7440-50-8	15	1.0
Ci 77000 - 7429-90-5	7429-90-5	10	1.0
Nickel - 7440-02-0	7440-02-0	2	0.1
1,3-Propane sultone - 1120-71-4	1120-71-4	0.5	0.1

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Cobalt lithium manganese nickel oxide 182442-95-1		X		
Ci 77400 7440-50-8		X	X	
Nickel 7440-02-0		X	X	

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ci 77400 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
1,3-Propane sultone 1120-71-4	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Cobalt lithium manganese nickel oxide - 182442-95-1	carcinogen, 5/7/2004
Nickel - 7440-02-0	carcinogen, 10/1/1989 (metallic)
Ci 77266 - 1333-86-4	carcinogen, 2/21/2003 (airborne, unbound particles of respirable size)
1,3-Propane sultone - 1120-71-4	carcinogen, 1/1/1988

**U.S. State Right-to-Know Regulations**



This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Cobalt lithium manganese nickel oxide 182442-95-1	X		X	X	X
Graphite 7782-42-5	X	X	X		
Ci 77400 7440-50-8	X	X	X	X	X
Ethylene carbonate 96-49-1		X	X		
Ci 77000 7429-90-5	X	X	X	X	
Phosphate(1-), hexafluoro-, lithium 21324-40-3	X				
Nickel 7440-02-0	X	X	X	X	X
Ci 77266 1333-86-4	X	X	X		X
1,3-Propane sultone 1120-71-4	X	X	X	X	X

### 16. OTHER INFORMATION

<b>NFPA</b>	<b>Health hazards</b> 1	<b>Flammability</b> 0	<b>Instability</b> 0	<b>Physical and Chemical Properties</b> -
<b>HMIS</b>	<b>Health hazards</b> 0	<b>Flammability</b> 0	<b>Physical hazards</b> 0	<b>Personal Protection</b> X

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Issuing Date** 25-Oct-2024

**Revision Date** 27-Sep-2024

**Revision Note** No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**



# SAFETY DATA SHEET

Issuing Date No data available

Revision Date 24-Sep-2024

Revision Number 1

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is ©2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION

### Product identifier

**Product Name** Rechargeable Li-ion Battery L24M3PK3 by Simplo

### Other means of identification

**Product Code(s)** 1820050

### Recommended use of the chemical and restrictions on use

**Recommended Use** Lithium Ion Battery

**Restrictions on use** No information available

### Details of the supplier of the safety data sheet

**Supplier Identification** Lenovo LNB laptops

**Address** Songtao Road 696  
shanghai  
shanghai  
201203  
CN

**Telephone** Phone:18116118603

**E-mail** yuanbb1@lenovo.com

### Emergency telephone number

**Company Emergency Phone Number** 18116118603

## 2. HAZARDS IDENTIFICATION

### Classification

Skin sensitization	Category 1
Carcinogenicity	Category 1B

This is a battery. In case of rupture: the above hazards exist.



Appearance Black

Physical state Solid

Odor Odorless

**GHS Label elements, including precautionary statements**

**Danger**

**Hazard statements**

May cause an allergic skin reaction

May cause cancer



**Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

**Skin**

IF ON SKIN: Wash with plenty of water and soap

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

**Precautionary Statements - Storage**

Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other information**

Very toxic to aquatic life with long lasting effects.

**Unknown acute toxicity** 33.03 % of the mixture consists of ingredient(s) of unknown toxicity

29.55 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

33.03 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

33.03 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

33.03 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

33.03 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Substance**

Not applicable.

**Mixture**

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lithium Cobalt Oxide (CoLiO <sub>2</sub> )	12190-79-3	47.15	-	-
Graphite	7782-42-5	25.25	-	-
Ci 77400	7440-50-8	6.82	-	-
Ci 77000	7429-90-5	4.31	-	-
Propylene carbonate	108-32-7	2.15	-	-
Ethylene carbonate	96-49-1	2.15	-	-
Nickel	7440-02-0	0.5	-	-
1,3-Propane sultone	1120-71-4	0.48	-	-

**4. FIRST AID MEASURES**

**Description of first aid measures**

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. First aid is upon rupture of sealed battery. In case of rupture: Remove to fresh air.
<b>Inhalation</b>	Remove to fresh air.
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
<b>Skin contact</b>	Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water.

**Most important symptoms and effects, both acute and delayed**

**Symptoms** Itching. Rashes. Hives.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** May cause sensitization in susceptible persons. Treat symptomatically.

**5. FIRE-FIGHTING MEASURES**

<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Large Fire</b>	CAUTION: Use of water spray when fighting fire may be inefficient.
<b>Unsuitable extinguishing media</b>	Do not scatter spilled material with high pressure water streams.
<b>Specific hazards arising from the chemical</b>	Product is or contains a sensitizer. May cause sensitization by skin contact.
<b>Hazardous Combustion Products</b>	Carbon oxides.



**Explosion Data**

Sensitivity to Mechanical Impact None.  
Sensitivity to Static Discharge None.

**Special protective equipment for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

**6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Other Information** Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

**7. HANDLING AND STORAGE**

Precautions for safe handling

**Advice on safe handling** In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Control parameters

**Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	TWA: 0.02 mg/m <sup>3</sup>	-	
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup> respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m <sup>3</sup> total dust synthetic TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf respirable dust	IDLH: 1250 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup> respirable dust



		natural (vacated) TWA: 2.5 mg/m <sup>3</sup> respirable dust natural (vacated) TWA: 10 mg/m <sup>3</sup> total dust synthetic (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf natural		
Ci 77400 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> fume	TWA: 0.1 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> dust and mist (vacated) TWA: 0.1 mg/m <sup>3</sup> Cu dust, fume, mist	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume	
Ci 77000 7429-90-5	TWA: 1 mg/m <sup>3</sup> respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust	
Nickel 7440-02-0	TWA: 1.5 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> (vacated) TWA: 1 mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> TWA: 0.015 mg/m <sup>3</sup>	
<b>Chemical name</b>	<b>Alberta</b>	<b>British Columbia</b>	<b>Ontario TWAEV</b>	<b>Quebec</b>
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Ci 77400 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>
Ci 77000 7429-90-5	TWA: 10 mg/m <sup>3</sup>	TWA: 1.0 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
Nickel 7440-02-0	TWA: 1.5 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 1.5 mg/m <sup>3</sup>
1,3-Propane sultone 1120-71-4		TWA:	TWA:	TWA:

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

**Appropriate engineering controls**

**Engineering controls**

Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Hand protection**

Wear suitable gloves.

**Skin and body protection**

Wear suitable protective clothing.

**Respiratory protection**

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling



the product.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	Solid
<b>Appearance</b>	Black
<b>Odor</b>	Odorless
<b>Color</b>	No information available
<b>Odor Threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	No data available	None known
Water Solubility	Insoluble in water	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water <sup>1</sup>		
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

### Other Information

<b>Explosive properties</b>	No information available
<b>Oxidizing properties</b>	No information available
<b>Softening Point</b>	No information available
<b>Molecular Weight</b>	No information available
<b>VOC Content (%)</b>	No information available
<b>Liquid Density</b>	No information available
<b>Bulk Density</b>	No information available
<b>Particle Size</b>	No information available
<b>Particle Size Distribution</b>	No information available

## 10. STABILITY AND REACTIVITY

<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of Hazardous Reactions</b>	None under normal processing.
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	None known based on information supplied.
<b>Incompatible materials</b>	None known based on information supplied.



Hazardous Decomposition Products Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:
<b>Inhalation</b>	Specific test data for the substance or mixture is not available.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. May cause sensitization by skin contact. (based on components). Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available.

### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Itching. Rashes. Hives.

### Numerical measures of toxicity

#### Acute toxicity

**Unknown acute toxicity** 33.03 % of the mixture consists of ingredient(s) of unknown toxicity  
 29.55 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
 33.03 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
 33.03 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
 33.03 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
 33.03 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Product Information			
Component Information			
Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Lithium Cobalt Oxide (CoLiO2)	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	> 5.05 mg/L ( Rat ) 4 h
Graphite	-	-	> 2000 mg/m <sup>3</sup> ( Rat ) 4 h
Ci 77400	-	-	> 5.11 mg/L ( Rat ) 4 h
Ci 77000	-	-	> 0.888 mg/L ( Rat ) 4 h
Propylene carbonate	= 29000 mg/kg ( Rat )	> 3000 mg/kg ( Rabbit )	-
Ethylene carbonate	= 10 g/kg ( Rat )	> 26420 mg/kg ( Rabbit )	> 730 mg/m <sup>3</sup> ( Rat ) 8 h
Nickel	> 9000 mg/kg ( Rat )	-	> 10.2 mg/L ( Rat ) 1 h
1,3-Propane sultone	= 157 mg/kg ( Rat )	-	-

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Skin corrosion/irritation</b>	No information available.
<b>Serious eye damage/eye irritation</b>	No information available.
<b>Respiratory or skin sensitization</b>	May cause sensitization by skin contact.
<b>Germ cell mutagenicity</b>	No information available.



**Carcinogenicity** Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	A3	Group 2B	Reasonably Anticipated	X
Nickel 7440-02-0	-	Group 2B	Reasonably Anticipated	X
1,3-Propane sultone 1120-71-4	A3	Group 2A	Reasonably Anticipated	X

**Legend**

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

**NTP (National Toxicology Program)**

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

**Reproductive toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Aspiration hazard** No information available.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Graphite	No data available	96h LC50: > 100 mg/L (Danio rerio)	No data available	No data available
Ci 77400	72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio)	No data available	48h EC50: = 0.03 mg/L (Daphnia magna)



		96h LC50: = 0.112 mg/L (Poecilia reticulata)		
Propylene carbonate	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: > 1000 mg/L (Cyprinus carpio)	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L (Daphnia magna)
Ethylene carbonate	No data available	96h LC50: > 100 mg/L (Oncorhynchus mykiss)	No data available	No data available
Nickel	72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 100 mg/L (Brachydanio rerio) 96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio)	No data available	48h EC50: > 100 mg/L (Daphnia magna) 48h EC50: = 1 mg/L (Daphnia magna)

**Persistence and Degradability** No information available.

**Bioaccumulation**

**Component Information**

Chemical name	Partition coefficient
Propylene carbonate	0.48
Ethylene carbonate	0.11

**Mobility** No information available.

**Other adverse effects** No information available.

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Waste from residues/unused products** Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Do not reuse empty containers.

**California Waste Codes** 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	Toxic
Ci 77000 7429-90-5	Ignitable powder
Nickel 7440-02-0	Toxic powder Ignitable powder

**14. TRANSPORT INFORMATION**

**Note:** The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must



meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule) Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

<b>DOT</b>	NOT REGULATED
<b>Proper Shipping Name</b>	NON-REGULATED
<b>Hazard Class</b>	N/A
<b>Emergency Response Guide Number</b>	147
<b>TDG</b>	Not applicable
<b>MEX</b>	Not applicable
<b>ICAO</b>	Not applicable
<b>IATA</b>	
<b>UN-No.</b>	UN3480
<b>Proper Shipping Name</b>	LITHIUM ION BATTERIES
<b>Hazard Class</b>	9
<b>ERG Code</b>	12FZ
<b>Description</b>	UN3480, LITHIUM ION BATTERIES, 9
<b>IMDG/IMO</b>	Not applicable
<b>Proper Shipping Name</b>	NON-REGULATED PER SP 188
<b>Hazard Class</b>	N/A
<b>EmS-No.</b>	F-A, S-I
<b>RID</b>	Not applicable
<b>ADR</b>	Not applicable
<b>ADN</b>	Not applicable

**15. REGULATORY INFORMATION**

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

**International Regulations**

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

**International Inventories**

<b>TSCA</b>	Contact supplier for inventory compliance status.
<b>DSL/NDSL</b>	Contact supplier for inventory compliance status.
<b>EINECS/ELINCS</b>	Contact supplier for inventory compliance status.



ENCS Contact supplier for inventory compliance status.  
 KECL Contact supplier for inventory compliance status.  
 PICCS Contact supplier for inventory compliance status.  
 AICS Contact supplier for inventory compliance status.

**Legend**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Lithium Cobalt Oxide (CoLiO2) - 12190-79-3	12190-79-3	47.15	0.1
Ci 77400 - 7440-50-8	7440-50-8	6.82	1.0
Ci 77000 - 7429-90-5	7429-90-5	4.31	1.0
Nickel - 7440-02-0	7440-02-0	0.5	0.1
1,3-Propane sultone - 1120-71-4	1120-71-4	0.48	0.1

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ci 77400 7440-50-8		X	X	
Nickel 7440-02-0		X	X	

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ci 77400 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
1,3-Propane sultone 1120-71-4	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ



**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Nickel - 7440-02-0	carcinogen, 10/1/1989 (metallic)
1,3-Propane sultone - 1120-71-4	carcinogen, 1/1/1988

**U.S. State Right-to-Know Regulations**

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	X		X	X	X
Graphite 7782-42-5	X	X	X		
Ci 77400 7440-50-8	X	X	X	X	X
Ci 77000 7429-90-5	X	X	X	X	
Ethylene carbonate 96-49-1		X	X		
Nickel 7440-02-0	X	X	X	X	X
1,3-Propane sultone 1120-71-4	X	X	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health hazards 1	Flammability 0	Instability 0	Physical and Chemical Properties - Personal Protection X
<b>HMIS</b>	Health hazards 0	Flammability 0	Physical hazards 0	

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Revision Date** 24-Sep-2024

**Revision Note** No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**



# SAFETY DATA SHEET

Issuing Date 26-Sep-2024

Revision Date 24-Sep-2024

Revision Number 1

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is ©2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION

### Product identifier

**Product Name** Rechargeable Li-ion Battery L24N3PK2 by NVT

### Other means of identification

**Product Code(s)** 1820044

### Recommended use of the chemical and restrictions on use

**Recommended Use** Lithium Ion Battery

**Restrictions on use** No information available

### Details of the supplier of the safety data sheet

**Supplier Identification** Lenovo LNB laptops

**Address** Songtao Road 696  
shanghai  
shanghai  
201203  
CN

**Telephone** Phone:18116118603

**E-mail** yuanbb1@lenovo.com

### Emergency telephone number

**Company Emergency Phone Number** 18116118603

## 2. HAZARDS IDENTIFICATION

### Classification

Acute toxicity - Inhalation (Vapors)	Category 2
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 1B



Specific target organ toxicity (repeated exposure)	Category 1
--	------------

This is a battery. In case of rupture: the above hazards exist.

**Appearance** Black

**Physical state** Solid

**Odor** Odorless

**GHS Label elements, including precautionary statements**

**Danger**

**Hazard statements**

- Fatal if inhaled
- Causes severe skin burns and eye damage
- May cause cancer
- Causes damage to organs through prolonged or repeated exposure



**Precautionary Statements - Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Wear protective gloves/protective clothing/eye protection/face protection
- Do not breathe dust/fume/gas/mist/vapors/spray
- Use only outdoors or in a well-ventilated area
- Wear respiratory protection
- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product

**Precautionary Statements - Response**

- Specific treatment is urgent (see supplemental first aid instructions on this label)
- Immediately call a POISON CENTER or doctor

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Immediately call a POISON CENTER or doctor

**Skin**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower  
Wash contaminated clothing before reuse

**Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing  
Immediately call a POISON CENTER or doctor

**Ingestion**

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

**Precautionary Statements - Storage**

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other information**

May be harmful if swallowed. May be harmful in contact with skin. Very toxic to aquatic life with long lasting effects.

**Unknown acute toxicity** 18.5 % of the mixture consists of ingredient(s) of unknown toxicity  
16 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
18.5 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
18.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
18.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
18.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

**3. COMPOSITION/INFORMATION ON INGREDIENTS****Substance**

Not applicable.

**Mixture**

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Cobalt lithium manganese nickel oxide	182442-95-1	27.5	-	-
Ci 77400	7440-50-8	20	-	-
Aluminum foil	7429-90-5	20	-	-
Graphite	7782-42-5	16	-	-
Propylene carbonate	108-32-7	7.5	-	-
Phosphate(1-), hexafluoro-, lithium	21324-40-3	7.5	-	-
Ethylene carbonate	96-49-1	7.5	-	-
1,3-Propane sultone	1120-71-4	0.5	-	-

**4. FIRST AID MEASURES****Description of first aid measures****General advice**

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. First aid is upon rupture of sealed battery. In case of rupture:

**Inhalation**

If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Do not breathe dust. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get immediate medical advice/attention.

**Eye contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

**Skin contact**

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get immediate medical advice/attention.

**Ingestion**

Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water.



Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

**Self-protection of the first aider** Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Do not breathe dust. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

**Most important symptoms and effects, both acute and delayed**

**Symptoms** Coughing and/ or wheezing. Difficulty in breathing. Burning sensation.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Large Fire** CAUTION: Use of water spray when fighting fire may be inefficient.

**Unsuitable extinguishing media** Do not scatter spilled material with high pressure water streams.

**Specific hazards arising from the chemical** The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.

**Hazardous Combustion Products** Carbon oxides.

**Explosion Data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

**Special protective equipment for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Avoid generation of dust. Do not breathe dust. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Attention! Corrosive material.

**Other Information** Refer to protective measures listed in Sections 7 and 8.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.



**Methods for cleaning up** Pick up and transfer to properly labeled containers.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling**

In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not breathe dust. Avoid generation of dust. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Protect from moisture. Store away from other materials.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

**Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Cobalt lithium manganese nickel oxide 182442-95-1	TWA: 0.02 mg/m <sup>3</sup> Co inhalable particulate matter TWA: 0.02 mg/m <sup>3</sup> Mn respirable particulate matter TWA: 0.1 mg/m <sup>3</sup> Mn inhalable particulate matter	(vacated) Ceiling: 5 mg/m <sup>3</sup> Ceiling: 5 mg/m <sup>3</sup> Mn	IDLH: 500 mg/m <sup>3</sup> Mn IDLH: 10 mg/m <sup>3</sup> Ni TWA: 1 mg/m <sup>3</sup> Mn TWA: 0.015 mg/m <sup>3</sup> except Nickel carbonyl Ni STEL: 3 mg/m <sup>3</sup> Mn
Ci 77400 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> fume	TWA: 0.1 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> dust and mist (vacated) TWA: 0.1 mg/m <sup>3</sup> Cu dust, fume, mist	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume
Aluminum foil 7429-90-5	TWA: 1 mg/m <sup>3</sup> respirable particulate matter	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup> respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m <sup>3</sup> total dust synthetic TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf respirable dust natural (vacated) TWA: 2.5 mg/m <sup>3</sup> respirable dust natural (vacated) TWA: 10 mg/m <sup>3</sup> total dust synthetic	IDLH: 1250 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup> respirable dust



		(vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf natural		
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup> F (vacated) TWA: 2.5 mg/m <sup>3</sup>	IDLH: 250 mg/m <sup>3</sup> F	
Chemical name	Alberta	British Columbia	Ontario TWAEV	Quebec
Cobalt lithium manganese nickel oxide 182442-95-1	TWA: 0.02 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 0.05 mg/m <sup>3</sup> TWA: 0.02 mg/m <sup>3</sup>
Ci 77400 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>
Aluminum foil 7429-90-5	TWA: 10 mg/m <sup>3</sup>	TWA: 1.0 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>
1,3-Propane sultone 1120-71-4		TWA:	TWA:	TWA:

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

**Appropriate engineering controls**

**Engineering controls**

Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Face protection shield.

**Hand protection**

Wear suitable gloves. Impervious gloves.

**Skin and body protection**

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

**Respiratory protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not breathe dust. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

**Physical state** Solid  
**Appearance** Black  
**Odor** Odorless



**Color** No information available  
**Odor Threshold** No information available

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
<b>pH</b>	No data available	None known
<b>Melting / freezing point</b>	No data available	None known
<b>Boiling point / boiling range</b>	No data available	None known
<b>Flash Point</b>	No data available	None known
<b>Evaporation Rate</b>	No data available	None known
<b>Flammability (solid, gas)</b>	No data available	None known
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit</b>	No data available	
<b>Lower flammability limit</b>	No data available	
<b>Vapor pressure</b>	No data available	None known
<b>Vapor density</b>	No data available	None known
<b>Relative density</b>	No data available	None known
<b>Water Solubility</b>	Insoluble in water	
<b>Solubility(ies)</b>	No data available	None known
<b>Partition coefficient: n-octanol/water<sup>1</sup></b>		
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>	No data available	None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	No data available	None known

**Other Information**

**Explosive properties** No information available  
**Oxidizing properties** No information available  
**Softening Point** No information available  
**Molecular Weight** No information available  
**VOC Content (%)** No information available  
**Liquid Density** No information available  
**Bulk Density** No information available  
**Particle Size** No information available  
**Particle Size Distribution** No information available

**10. STABILITY AND REACTIVITY**

**Reactivity** No information available.  
**Chemical stability** Stable under normal conditions.  
**Possibility of Hazardous Reactions** None under normal processing.  
**Hazardous Polymerization** Hazardous polymerization does not occur.  
**Conditions to avoid** Excessive heat. Exposure to air or moisture over prolonged periods.  
**Incompatible materials** Acids. Bases. Oxidizing agent.  
**Hazardous Decomposition Products** Carbon oxides.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

**Product Information** Product does not present an acute toxicity hazard based on known or supplied information.



In case of rupture:

- Inhalation** Specific test data for the substance or mixture is not available. Fatal if inhaled. (based on components). Corrosive by inhalation. Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal.
- Eye contact** Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.
- Skin contact** Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns. May be harmful in contact with skin.
- Ingestion** Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms** Coughing and/ or wheezing. Difficulty in breathing. Redness. Burning. May cause blindness.

**Numerical measures of toxicity**

**Acute toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

- ATEmix (oral)** 4,384.60 mg/kg
- ATEmix (dermal)** 3,260.00 mg/kg
- ATEmix (inhalation-vapor)** 1.485 mg/L

- Unknown acute toxicity** 18.5 % of the mixture consists of ingredient(s) of unknown toxicity
- 16 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
  - 18.5 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
  - 18.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
  - 18.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
  - 18.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

**Product Information**

**Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ci 77400	-	-	> 5.11 mg/L ( Rat ) 4 h
Aluminum foil	-	-	> 0.888 mg/L ( Rat ) 4 h
Graphite	-	-	> 2000 mg/m <sup>3</sup> ( Rat ) 4 h
Propylene carbonate	= 29000 mg/kg ( Rat )	> 3000 mg/kg ( Rabbit )	-
Ethylene carbonate	= 10 g/kg ( Rat )	> 26420 mg/kg ( Rabbit )	> 730 mg/m <sup>3</sup> ( Rat ) 8 h
1,3-Propane sultone	= 157 mg/kg ( Rat )	-	-

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes burns.



<b>Serious eye damage/eye irritation</b>	Classification based on data available for ingredients. Risk of serious damage to eyes. Causes burns.
<b>Respiratory or skin sensitization</b>	No information available.
<b>Germ cell mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Cobalt lithium manganese nickel oxide 182442-95-1	A3	Group 2B Group 1	Reasonably Anticipated Known	X
1,3-Propane sultone 1120-71-4	A3	Group 2A	Reasonably Anticipated	X

**Legend**

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

**NTP (National Toxicology Program)**

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

<b>Reproductive toxicity</b>	No information available.
<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	No information available.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ci 77400	72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 1.25 mg/L (Lepomis macrochirus)	No data available	48h EC50: = 0.03 mg/L (Daphnia magna)



		96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 0.112 mg/L (Poecilia reticulata)		
Graphite	No data available	96h LC50: > 100 mg/L (Danio rerio)	No data available	No data available
Propylene carbonate	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: > 1000 mg/L (Cyprinus carpio)	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L (Daphnia magna)
Ethylene carbonate	No data available	96h LC50: > 100 mg/L (Oncorhynchus mykiss)	No data available	No data available

**Persistence and Degradability** No information available.

**Bioaccumulation**

**Component Information**

Chemical name	Partition coefficient
Propylene carbonate	0.48
Ethylene carbonate	0.11

**Mobility** No information available.

**Other adverse effects** No information available.

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Waste from residues/unused products** Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Do not reuse empty containers.

**California Waste Codes** 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Cobalt lithium manganese nickel oxide 182442-95-1	Toxic
Aluminum foil 7429-90-5	Ignitable powder

**14. TRANSPORT INFORMATION**

**Note:** The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation



listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)  
Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

<b>DOT</b>	NOT REGULATED
<b>Proper Shipping Name</b>	NON-REGULATED
<b>Hazard Class</b>	N/A
<b>Emergency Response Guide Number</b>	147
<b>TDG</b>	Not applicable
<b>MEX</b>	Not applicable
<b>ICAO</b>	Not applicable
<b>IATA</b>	
<b>UN-No.</b>	UN3480
<b>Proper Shipping Name</b>	LITHIUM ION BATTERIES
<b>Hazard Class</b>	9
<b>ERG Code</b>	12FZ
<b>Description</b>	UN3480, LITHIUM ION BATTERIES, 9
<b>IMDG/IMO</b>	Not applicable
<b>Proper Shipping Name</b>	NON-REGULATED PER SP 188
<b>Hazard Class</b>	N/A
<b>EmS-No.</b>	F-A, S-I
<b>Marine Pollutant</b>	This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO
<b>RID</b>	Not applicable
<b>ADR</b>	Not applicable
<b>ADN</b>	Not applicable

## 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Regulations

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

#### International Inventories

<b>TSCA</b>	Contact supplier for inventory compliance status.
<b>DSL/NDSL</b>	Contact supplier for inventory compliance status.
<b>EINECS/ELINCS</b>	Contact supplier for inventory compliance status.
<b>ENCS</b>	Contact supplier for inventory compliance status.



**KECL** Contact supplier for inventory compliance status.  
**PICCS** Contact supplier for inventory compliance status.  
**AICS** Contact supplier for inventory compliance status.

**Legend**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Cobalt lithium manganese nickel oxide - 182442-95-1	182442-95-1	27.5	1.0 0.1
Ci 77400 - 7440-50-8	7440-50-8	20	1.0
Aluminum foil - 7429-90-5	7429-90-5	20	1.0
1,3-Propane sultone - 1120-71-4	1120-71-4	0.5	0.1

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Cobalt lithium manganese nickel oxide 182442-95-1		X		
Ci 77400 7440-50-8		X	X	

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ci 77400 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Aluminum foil 7429-90-5			
1,3-Propane sultone 1120-71-4	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ



**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Cobalt lithium manganese nickel oxide - 182442-95-1	carcinogen, 5/7/2004
1,3-Propane sultone - 1120-71-4	carcinogen, 1/1/1988

**U.S. State Right-to-Know Regulations**

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Cobalt lithium manganese nickel oxide 182442-95-1	X		X	X	X
Ci 77400 7440-50-8	X	X	X	X	X
Aluminum foil 7429-90-5	X	X	X	X	
Graphite 7782-42-5	X	X	X		
Phosphate(1-), hexafluoro-, lithium 21324-40-3	X				
Ethylene carbonate 96-49-1		X	X		
1,3-Propane sultone 1120-71-4	X	X	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health hazards 1	Flammability 0	Instability 0	Physical and Chemical Properties -
<b>HMIS</b>	Health hazards 0	Flammability 0	Physical hazards 0	Personal Protection X

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Issuing Date** 26-Sep-2024

**Revision Date** 24-Sep-2024

**Revision Note** No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**



# SAFETY DATA SHEET

Issuing Date 26-Sep-2024

Revision Date 24-Sep-2024

Revision Number 1

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is ©2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION

### Product identifier

**Product Name** Rechargeable Li-ion Battery L24X3PK2 by CosMX

### Other means of identification

**Product Code(s)** 1820028

### Recommended use of the chemical and restrictions on use

**Recommended Use** Lithium Ion Battery

**Restrictions on use** No information available

### Details of the supplier of the safety data sheet

**Supplier Identification** Lenovo LNB laptops

**Address** Songtao Road 696  
shanghai  
shanghai  
201203  
CN

**Telephone** Phone:18116118603

**E-mail** yuanbb1@lenovo.com

### Emergency telephone number

**Company Emergency Phone Number** 18116118603

## 2. HAZARDS IDENTIFICATION

### Classification

Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1B



Specific target organ toxicity (repeated exposure)	Category 1
--	------------

This is a battery. In case of rupture: the above hazards exist.

**Appearance** Black

**Physical state** Solid

**Odor** Odorless

**GHS Label elements, including precautionary statements**

**Danger**

**Hazard statements**

- Causes severe skin burns and eye damage
- May cause an allergic skin reaction
- May cause cancer
- Causes damage to organs through prolonged or repeated exposure



**Precautionary Statements - Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Wear protective gloves/protective clothing/eye protection/face protection
- Wash face, hands and any exposed skin thoroughly after handling
- Contaminated work clothing must not be allowed out of the workplace
- Do not breathe dust/fume/gas/mist/vapors/spray
- Do not eat, drink or smoke when using this product

**Precautionary Statements - Response**

- Immediately call a POISON CENTER or doctor
- Specific treatment (see supplemental first aid instructions on this label)

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Immediately call a POISON CENTER or doctor

**Skin**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower  
Wash contaminated clothing before reuse  
If skin irritation or rash occurs: Get medical advice/attention

**Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing  
Immediately call a POISON CENTER or doctor

**Ingestion**

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

**Precautionary Statements - Storage**

Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other information**



May be harmful if swallowed. May be harmful in contact with skin. Very toxic to aquatic life with long lasting effects.

**Unknown acute toxicity** 54 % of the mixture consists of ingredient(s) of unknown toxicity  
 51 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
 54 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
 54 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
 54 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
 54 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Substance**

Not applicable.

**Mixture**

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lithium Cobalt Oxide (CoLiO <sub>2</sub> )	12190-79-3	50	-	-
Graphite	7782-42-5	30	-	-
Propylene carbonate	108-32-7	10	-	-
Ethylene carbonate	96-49-1	10	-	-
Copper	7440-50-8	10	-	-
Aluminum	7429-90-5	10	-	-
Phosphate(1-), hexafluoro-, lithium	21324-40-3	5	-	-
Glass fiber	65997-17-3	3	-	-
Nickel	7440-02-0	2	-	-
Carbon black	1333-86-4	2	-	-
Sodium carboxymethyl cellulose	9004-32-4	1	-	-
1,3-Propane sultone	1120-71-4	0.5	-	-
Acrylic acid	79-10-7	0.2	-	-
Titanium dioxide	13463-67-7	0.1	-	-
Oxirane, 2,2'-4-butyliidenebisphenyleneoxymethylene (DGEBA)	25085-99-8	0.1	-	-

### 4. FIRST AID MEASURES

**Description of first aid measures**

**General advice**

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. First aid is upon rupture of sealed battery. In case of rupture:

**Inhalation**

Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel



should) give oxygen. Delayed pulmonary edema may occur. Get immediate medical advice/attention.

<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get immediate medical advice/attention. May cause an allergic skin reaction.
<b>Ingestion</b>	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Wear personal protective clothing (see section 8).

**Most important symptoms and effects, both acute and delayed**

**Symptoms** Burning sensation. Itching. Rashes. Hives.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause sensitization in susceptible persons. Treat symptomatically.

**5. FIRE-FIGHTING MEASURES**

<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Large Fire</b>	CAUTION: Use of water spray when fighting fire may be inefficient.
<b>Unsuitable extinguishing media</b>	Do not scatter spilled material with high pressure water streams.
<b>Specific hazards arising from the chemical</b>	The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.
<b>Hazardous Combustion Products</b>	Carbon oxides.
<b>Explosion Data</b>	
<b>Sensitivity to Mechanical Impact</b>	None.
<b>Sensitivity to Static Discharge</b>	None.
<b>Special protective equipment for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

**6. ACCIDENTAL RELEASE MEASURES**



**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Other Information** Refer to protective measures listed in Sections 7 and 8.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	TWA: 0.02 mg/m <sup>3</sup>	-	
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup> respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m <sup>3</sup> total dust synthetic TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf respirable dust natural (vacated) TWA: 2.5 mg/m <sup>3</sup> respirable dust natural (vacated) TWA: 10 mg/m <sup>3</sup> total dust synthetic (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup> respirable dust
Copper	TWA: 0.2 mg/m <sup>3</sup> fume	TWA: 0.1 mg/m <sup>3</sup> fume	IDLH: 100 mg/m <sup>3</sup> dust, fume



7440-50-8		TWA: 1 mg/m <sup>3</sup> dust and mist (vacated) TWA: 0.1 mg/m <sup>3</sup> Cu dust, fume, mist	and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume	
Aluminum 7429-90-5	TWA: 1 mg/m <sup>3</sup> respirable particulate matter	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust	
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup> F (vacated) TWA: 2.5 mg/m <sup>3</sup>	IDLH: 250 mg/m <sup>3</sup> F	
Glass fiber 65997-17-3	TWA: 1 fiber/cm <sup>3</sup> respirable fibers: length >5 µm, aspect ratio >=3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m <sup>3</sup> inhalable particulate matter	-		
Nickel 7440-02-0	TWA: 1.5 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> (vacated) TWA: 1 mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> TWA: 0.015 mg/m <sup>3</sup>	
Carbon black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH	
Acrylic acid 79-10-7	TWA: 2 ppm S*	(vacated) TWA: 10 ppm (vacated) TWA: 30 mg/m <sup>3</sup> (vacated) S*	TWA: 2 ppm TWA: 6 mg/m <sup>3</sup>	
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>	
Chemical name	Alberta	British Columbia	Ontario TWA/EV	Quebec
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>
Aluminum 7429-90-5	TWA: 10 mg/m <sup>3</sup>	TWA: 1.0 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>
Glass fiber 65997-17-3	TWA: 5 mg/m <sup>3</sup> TWA: 1 fibre/cm <sup>3</sup>	TWA: 1 fibre/cm <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	TWA: 1 fibre/cm <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	TWA: 1 fibre/cm <sup>3</sup> TWA: 5 mg/m <sup>3</sup>
Nickel 7440-02-0	TWA: 1.5 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 1.5 mg/m <sup>3</sup>
Carbon black 1333-86-4	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>
1,3-Propane sultone 1120-71-4		TWA:	TWA:	TWA:
Acrylic acid	TWA: 2 ppm	TWA: 2 ppm	TWA: 2 ppm	TWA: 2 ppm



79-10-7	TWA: 5.9 mg/m <sup>3</sup> Skin	Skin	Skin	TWA: 5.9 mg/m <sup>3</sup> Skin
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

**Appropriate engineering controls**

**Engineering controls** Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Face protection shield.

**Hand protection** Wear suitable gloves. Impervious gloves.

**Skin and body protection** Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

**Respiratory protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

**Physical state** Solid  
**Appearance** Black  
**Odor** Odorless  
**Color** No information available  
**Odor Threshold** No information available

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	No data available	None known
Water Solubility	Insoluble in water	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water <sup>1</sup>		



<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>	No data available	None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	No data available	None known

**Other Information**

<b>Explosive properties</b>	No information available
<b>Oxidizing properties</b>	No information available
<b>Softening Point</b>	No information available
<b>Molecular Weight</b>	No information available
<b>VOC Content (%)</b>	No information available
<b>Liquid Density</b>	No information available
<b>Bulk Density</b>	No information available
<b>Particle Size</b>	No information available
<b>Particle Size Distribution</b>	No information available

**10. STABILITY AND REACTIVITY**

<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of Hazardous Reactions</b>	None under normal processing.
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Exposure to air or moisture over prolonged periods.
<b>Incompatible materials</b>	Acids. Bases. Oxidizing agent.
<b>Hazardous Decomposition Products</b>	Carbon oxides.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

<b>Product Information</b>	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:
<b>Inhalation</b>	Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May be harmful in contact with skin.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Redness. Burning. May cause blindness. Coughing and/ or wheezing. Itching. Rashes. Hives.

### Numerical measures of toxicity

#### Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)** 4,319.10 mg/kg  
**ATEmix (dermal)** 2,760.00 mg/kg

**Unknown acute toxicity** 54 % of the mixture consists of ingredient(s) of unknown toxicity  
 51 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
 54 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
 54 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
 54 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
 54 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

### Product Information

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Lithium Cobalt Oxide (CoLiO <sub>2</sub> )	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	> 5.05 mg/L ( Rat ) 4 h
Graphite	-	-	> 2000 mg/m <sup>3</sup> ( Rat ) 4 h
Propylene carbonate	= 29000 mg/kg ( Rat )	> 3000 mg/kg ( Rabbit )	-
Ethylene carbonate	= 10 g/kg ( Rat )	> 26420 mg/kg ( Rabbit )	> 730 mg/m <sup>3</sup> ( Rat ) 8 h
Copper	-	-	> 5.11 mg/L ( Rat ) 4 h
Aluminum	-	-	> 0.888 mg/L ( Rat ) 4 h
Nickel	> 9000 mg/kg ( Rat )	-	> 10.2 mg/L ( Rat ) 1 h
Carbon black	> 10000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 4.6 mg/m <sup>3</sup> ( Rat ) 4 h
Sodium carboxymethyl cellulose	= 27000 mg/kg ( Rat )	-	> 5800 mg/m <sup>3</sup> ( Rat ) 4 h
1,3-Propane sultone	= 157 mg/kg ( Rat )	-	-
Acrylic acid	= 193 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3.6 mg/L ( Rat ) 4 h = 11.1 mg/L ( Rat ) 1 h
Titanium dioxide	> 2000 mg/kg ( Rat )	-	> 5.09 mg/L ( Rat ) 4 h

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes burns.

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Risk of serious damage to eyes. Causes burns.

**Respiratory or skin sensitization** May cause sensitization by skin contact.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer. This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	A3	Group 2B	Reasonably Anticipated	X
Glass fiber 65997-17-3	-	Group 3	-	-
Nickel 7440-02-0	-	Group 2B	Reasonably Anticipated	X
Carbon black 1333-86-4	A3	Group 2B	-	X
1,3-Propane sultone 1120-71-4	A3	Group 2A	Reasonably Anticipated	X
Acrylic acid 79-10-7	-	Group 3	-	-
Titanium dioxide 13463-67-7	A3	Group 2B	-	X

**Legend**

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

**NTP (National Toxicology Program)**

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

<b>Reproductive toxicity</b>	No information available.
<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	No information available.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Graphite	No data available	96h LC50: > 100 mg/L (Danio rerio)	No data available	No data available
Propylene carbonate	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: > 1000 mg/L (Cyprinus carpio)	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L (Daphnia magna)
Ethylene carbonate	No data available	96h LC50: > 100 mg/L (Oncorhynchus mykiss)	No data available	No data available
Copper	72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L	No data available	48h EC50: = 0.03 mg/L (Daphnia magna)



	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata)	(Pimephales promelas) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 0.112 mg/L (Poecilia reticulata)		
Nickel	72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 100 mg/L (Brachydanio rerio) 96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio)	No data available	48h EC50: > 100 mg/L (Daphnia magna) 48h EC50: = 1 mg/L (Daphnia magna)
Acrylic acid	96h EC50: = 0.17 mg/L (Pseudokirchneriella subcapitata) 72h EC50: = 0.04 mg/L (Desmodesmus subspicatus)	96h LC50: = 222 mg/L (Brachydanio rerio)	No data available	48h EC50: = 95 mg/L (Daphnia magna)

**Persistence and Degradability** No information available.

**Bioaccumulation**

**Component Information**

Chemical name	Partition coefficient
Propylene carbonate	0.48
Ethylene carbonate	0.11
Acrylic acid	0.46

**Mobility** No information available.

**Other adverse effects** No information available.

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Waste from residues/unused products** Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Do not reuse empty containers.

**California Waste Codes** 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.



Chemical name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	Toxic
Aluminum 7429-90-5	Ignitable powder
Nickel 7440-02-0	Toxic powder Ignitable powder

**14. TRANSPORT INFORMATION**

**Note:** The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)  
Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

**DOT** NOT REGULATED  
**Proper Shipping Name** NON-REGULATED  
**Hazard Class** N/A  
**Emergency Response Guide Number** 147

**TDG** Not applicable

**MEX** Not applicable

**ICAO** Not applicable

**IATA**  
**UN-No.** UN3480  
**Proper Shipping Name** LITHIUM ION BATTERIES  
**Hazard Class** 9  
**ERG Code** 12FZ  
**Description** UN3480, LITHIUM ION BATTERIES, 9

**IMDG/IMO** Not applicable  
**Proper Shipping Name** NON-REGULATED PER SP 188  
**Hazard Class** N/A  
**EmS-No.** F-A, S-I  
**Marine Pollutant** This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO

**RID** Not applicable

**ADR** Not applicable

**ADN** Not applicable



## 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Regulations

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

#### International Inventories

<b>TSCA</b>	Contact supplier for inventory compliance status.
<b>DSL/NDSL</b>	Contact supplier for inventory compliance status.
<b>EINECS/ELINCS</b>	Contact supplier for inventory compliance status.
<b>ENCS</b>	Contact supplier for inventory compliance status.
<b>KECL</b>	Contact supplier for inventory compliance status.
<b>PICCS</b>	Contact supplier for inventory compliance status.
<b>AICS</b>	Contact supplier for inventory compliance status.

#### Legend

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

#### US Federal Regulations

##### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) - 12190-79-3	12190-79-3	50	0.1
Copper - 7440-50-8	7440-50-8	10	1.0
Aluminum - 7429-90-5	7429-90-5	10	1.0
Nickel - 7440-02-0	7440-02-0	2	0.1
1,3-Propane sultone - 1120-71-4	1120-71-4	0.5	0.1
Acrylic acid - 79-10-7	79-10-7	0.2	1.0

##### **SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

##### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper		X	X	



7440-50-8			
Nickel 7440-02-0		X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
1,3-Propane sultone 1120-71-4	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ
Acrylic acid 79-10-7	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Carbon black - 1333-86-4	Carcinogen
Nickel - 7440-02-0	carcinogen, 10/1/1989 (metallic)
1,3-Propane sultone - 1120-71-4	carcinogen, 1/1/1988
Titanium dioxide - 13463-67-7	Carcinogen

**U.S. State Right-to-Know Regulations**

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	X		X	X	X
Graphite 7782-42-5	X	X	X		
Ethylene carbonate 96-49-1		X	X		
Copper 7440-50-8	X	X	X	X	X
Aluminum 7429-90-5	X	X	X	X	
Phosphate(1-), hexafluoro-, lithium 21324-40-3	X				
Nickel 7440-02-0	X	X	X	X	X
Carbon black 1333-86-4	X	X	X		X
1,3-Propane sultone 1120-71-4	X	X	X	X	X
Acrylic acid 79-10-7	X	X	X	X	X
Titanium dioxide	X	X	X		



---

13463-67-7					
------------	--	--	--	--	--

**16. OTHER INFORMATION**

<b>NFPA</b>	Health hazards 1	Flammability 0	Instability 0	Physical and Chemical Properties -
<b>HMIS</b>	Health hazards 0	Flammability 0	Physical hazards 0	Personal Protection X

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Issuing Date** 26-Sep-2024

**Revision Date** 24-Sep-2024

**Revision Note** No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**



# SAFETY DATA SHEET

Issuing Date 26-Sep-2024

Revision Date 24-Sep-2024

Revision Number 1

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is ©2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION

### Product identifier

**Product Name** Rechargeable Li-ion Battery L24B3PK3 by BYD

### Other means of identification

**Product Code(s)** 1820023

### Recommended use of the chemical and restrictions on use

**Recommended Use** Lithium Ion Battery

**Restrictions on use** No information available

### Details of the supplier of the safety data sheet

**Supplier Identification** Lenovo LNB laptops

**Address** Songtao Road 696  
shanghai  
shanghai  
201203  
CN

**Telephone** Phone:18116118603

**E-mail** yuanbb1@lenovo.com

### Emergency telephone number

**Company Emergency Phone Number** 18116118603

## 2. HAZARDS IDENTIFICATION

### Classification

Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1B



Specific target organ toxicity (repeated exposure)	Category 1
--	------------

This is a battery. In case of rupture: the above hazards exist.

**Appearance** Black

**Physical state** Solid

**Odor** Odorless

**GHS Label elements, including precautionary statements**

**Danger**

**Hazard statements**

- Causes severe skin burns and eye damage
- May cause an allergic skin reaction
- May cause cancer
- Causes damage to organs through prolonged or repeated exposure



**Precautionary Statements - Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Wear protective gloves/protective clothing/eye protection/face protection
- Wash face, hands and any exposed skin thoroughly after handling
- Contaminated work clothing must not be allowed out of the workplace
- Do not breathe dust/fume/gas/mist/vapors/spray
- Do not eat, drink or smoke when using this product

**Precautionary Statements - Response**

- Immediately call a POISON CENTER or doctor
- Specific treatment (see supplemental first aid instructions on this label)

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Immediately call a POISON CENTER or doctor

**Skin**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower  
Wash contaminated clothing before reuse  
If skin irritation or rash occurs: Get medical advice/attention

**Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing  
Immediately call a POISON CENTER or doctor

**Ingestion**

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

**Precautionary Statements - Storage**

Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other information**



May be harmful in contact with skin. Very toxic to aquatic life with long lasting effects.

**Unknown acute toxicity** 34 % of the mixture consists of ingredient(s) of unknown toxicity  
 27 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
 34 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
 34 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
 34 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
 34 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Substance**

Not applicable.

**Mixture**

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lithium Cobalt Oxide (CoLiO2)	12190-79-3	45	-	-
Graphite	7782-42-5	25	-	-
Propylene carbonate	108-32-7	10	-	-
Propyl propionate	106-36-5	10	-	-
Ethylene carbonate	96-49-1	10	-	-
Copper	7440-50-8	10	-	-
Phosphate(1-), hexafluoro-, lithium	21324-40-3	5	-	-
Nickel	7440-02-0	5	-	-
Aluminum	7429-90-5	5	-	-
Ci 77266	1333-86-4	2	-	-

### 4. FIRST AID MEASURES

**Description of first aid measures**

**General advice**

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. First aid is upon rupture of sealed battery. In case of rupture:

**Inhalation**

Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get immediate medical advice/attention.

**Eye contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

**Skin contact**

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get immediate medical advice/attention. May cause an allergic skin reaction.



---

<b>Ingestion</b>	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Wear personal protective clothing (see section 8).

**Most important symptoms and effects, both acute and delayed**

**Symptoms** Burning sensation. Itching. Rashes. Hives.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause sensitization in susceptible persons. Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Large Fire</b>	CAUTION: Use of water spray when fighting fire may be inefficient.
<b>Unsuitable extinguishing media</b>	Do not scatter spilled material with high pressure water streams.
<b>Specific hazards arising from the chemical</b>	The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.
<b>Hazardous Combustion Products</b>	Carbon oxides.
<b>Explosion Data</b>	
<b>Sensitivity to Mechanical Impact</b>	None.
<b>Sensitivity to Static Discharge</b>	None.
<b>Special protective equipment for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Other Information** Refer to protective measures listed in Sections 7 and 8.

**Methods and material for containment and cleaning up**



**Methods for containment** Prevent further leakage or spillage if safe to do so.  
**Methods for cleaning up** Pick up and transfer to properly labeled containers.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	TWA: 0.02 mg/m <sup>3</sup>	-	
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup> respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m <sup>3</sup> total dust synthetic TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf respirable dust natural (vacated) TWA: 2.5 mg/m <sup>3</sup> respirable dust natural (vacated) TWA: 10 mg/m <sup>3</sup> total dust synthetic (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup> respirable dust
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> fume	TWA: 0.1 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> dust and mist (vacated) TWA: 0.1 mg/m <sup>3</sup> Cu dust, fume, mist	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup> F (vacated) TWA: 2.5 mg/m <sup>3</sup>	IDLH: 250 mg/m <sup>3</sup> F
Nickel 7440-02-0	TWA: 1.5 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> (vacated) TWA: 1 mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> TWA: 0.015 mg/m <sup>3</sup>
Aluminum	TWA: 1 mg/m <sup>3</sup> respirable	TWA: 15 mg/m <sup>3</sup> total dust	TWA: 10 mg/m <sup>3</sup> total dust



7429-90-5	particulate matter	TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 5 mg/m <sup>3</sup> respirable dust	
Ci 77266 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH	
Chemical name	Alberta	British Columbia	Ontario TWAEV	Quebec
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>
Nickel 7440-02-0	TWA: 1.5 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 1.5 mg/m <sup>3</sup>
Aluminum 7429-90-5	TWA: 10 mg/m <sup>3</sup>	TWA: 1.0 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
Ci 77266 1333-86-4	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

**Appropriate engineering controls**

**Engineering controls**

Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Face protection shield.

**Hand protection**

Wear suitable gloves. Impervious gloves.

**Skin and body protection**

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

**Respiratory protection**

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

**9. PHYSICAL AND CHEMICAL PROPERTIES**



**Information on basic physical and chemical properties**

Physical state	Solid
Appearance	Black
Odor	Odorless
Color	No information available
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	No data available	None known
Water Solubility	Insoluble in water	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water <sup>1</sup>		
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

**Other Information**

Explosive properties	No information available
Oxidizing properties	No information available
Softening Point	No information available
Molecular Weight	No information available
VOC Content (%)	No information available
Liquid Density	No information available
Bulk Density	No information available
Particle Size	No information available
Particle Size Distribution	No information available

**10. STABILITY AND REACTIVITY**

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Exposure to air or moisture over prolonged periods.
Incompatible materials	Acids. Bases. Oxidizing agent.
Hazardous Decomposition Products	Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:
<b>Inhalation</b>	Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May be harmful in contact with skin.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Symptoms</b>	Redness. Burning. May cause blindness. Coughing and/ or wheezing. Itching. Rashes. Hives.
-----------------	---

### Numerical measures of toxicity

#### Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

<b>ATEmix (oral)</b>	5,424.30 mg/kg
<b>ATEmix (dermal)</b>	3,816.50 mg/kg
<b>ATEmix (inhalation-gas)</b>	29,700.00 ppm
<b>ATEmix (inhalation-dust/mist)</b>	9.90 mg/L
<b>ATEmix (inhalation-vapor)</b>	72.60 mg/L

<b>Unknown acute toxicity</b>	34 % of the mixture consists of ingredient(s) of unknown toxicity
	27 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
	34 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
	34 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
	34 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
	34 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

#### Product Information

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Lithium Cobalt Oxide (CoLiO2)	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	> 5.05 mg/L ( Rat ) 4 h
Graphite	-	-	> 2000 mg/m <sup>3</sup> ( Rat ) 4 h



Propylene carbonate	= 29000 mg/kg ( Rat )	> 3000 mg/kg ( Rabbit )	-
Propyl propionate	= 10331 mg/kg ( Rat )	= 16 mL/kg ( Rabbit )	-
Ethylene carbonate	= 10 g/kg ( Rat )	> 26420 mg/kg ( Rabbit )	> 730 mg/m <sup>3</sup> ( Rat ) 8 h
Copper	-	-	> 5.11 mg/L ( Rat ) 4 h
Nickel	> 9000 mg/kg ( Rat )	-	> 10.2 mg/L ( Rat ) 1 h
Aluminum	-	-	> 0.888 mg/L ( Rat ) 4 h
Ci 77266	> 10000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 4.6 mg/m <sup>3</sup> ( Rat ) 4 h

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Skin corrosion/irritation</b>	Classification based on data available for ingredients. Causes burns.
<b>Serious eye damage/eye irritation</b>	Classification based on data available for ingredients. Risk of serious damage to eyes. Causes burns.
<b>Respiratory or skin sensitization</b>	May cause sensitization by skin contact.
<b>Germ cell mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	A3	Group 2B	Reasonably Anticipated	X
Nickel 7440-02-0	-	Group 2B	Reasonably Anticipated	X
Ci 77266 1333-86-4	A3	Group 2B	-	X

**Legend**

- ACGIH (American Conference of Governmental Industrial Hygienists)**  
A3 - Animal Carcinogen
- IARC (International Agency for Research on Cancer)**  
Group 2B - Possibly Carcinogenic to Humans
- NTP (National Toxicology Program)**  
Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
- OSHA (Occupational Safety and Health Administration of the US Department of Labor)**  
X - Present

<b>Reproductive toxicity</b>	No information available.
<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	No information available.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
---------------	----------------------	------	-------------	-----------



			microorganisms	
Graphite	No data available	96h LC50: > 100 mg/L (Danio rerio)	No data available	No data available
Propylene carbonate	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: > 1000 mg/L (Cyprinus carpio)	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L (Daphnia magna)
Ethylene carbonate	No data available	96h LC50: > 100 mg/L (Oncorhynchus mykiss)	No data available	No data available
Copper	72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 0.112 mg/L (Poecilia reticulata)	No data available	48h EC50: = 0.03 mg/L (Daphnia magna)
Nickel	72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 100 mg/L (Brachydanio rerio) 96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio)	No data available	48h EC50: > 100 mg/L (Daphnia magna) 48h EC50: = 1 mg/L (Daphnia magna)

**Persistence and Degradability** No information available.

**Bioaccumulation**

**Component Information**

Chemical name	Partition coefficient
Propylene carbonate	0.48
Ethylene carbonate	0.11

**Mobility** No information available.

**Other adverse effects** No information available.

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Waste from residues/unused products** Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Do not reuse empty containers.



**California Waste Codes** 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	Toxic
Nickel 7440-02-0	Toxic powder Ignitable powder
Aluminum 7429-90-5	Ignitable powder

**14. TRANSPORT INFORMATION**

**Note:** The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)  
Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

**DOT** NOT REGULATED  
**Proper Shipping Name** NON-REGULATED  
**Hazard Class** N/A  
**Emergency Response Guide Number** 147

**TDG** Not applicable

**MEX** Not applicable

**ICAO** Not applicable

**IATA**  
**UN-No.** UN3480  
**Proper Shipping Name** LITHIUM ION BATTERIES  
**Hazard Class** 9  
**ERG Code** 12FZ  
**Description** UN3480, LITHIUM ION BATTERIES, 9

**IMDG/IMO** Not applicable  
**Proper Shipping Name** NON-REGULATED PER SP 188  
**Hazard Class** N/A  
**EmS-No.** F-A, S-I  
**Marine Pollutant** This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO

**RID** Not applicable



**ADR** Not applicable

**ADN** Not applicable

**15. REGULATORY INFORMATION**

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

**International Regulations**

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

**International Inventories**

**TSCA** Contact supplier for inventory compliance status.  
**DSL/NDSL** Contact supplier for inventory compliance status.  
**EINECS/ELINCS** Contact supplier for inventory compliance status.  
**ENCS** Contact supplier for inventory compliance status.  
**KECL** Contact supplier for inventory compliance status.  
**PICCS** Contact supplier for inventory compliance status.  
**AICS** Contact supplier for inventory compliance status.

**Legend**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Lithium Cobalt Oxide (CoLiO2) - 12190-79-3	12190-79-3	45	0.1
Copper - 7440-50-8	7440-50-8	10	1.0
Nickel - 7440-02-0	7440-02-0	5	0.1
Aluminum - 7429-90-5	7429-90-5	5	1.0

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable	CWA - Toxic Pollutants	CWA - Priority	CWA - Hazardous
---------------	------------------	------------------------	----------------	-----------------



	Quantities		Pollutants	Substances
Copper 7440-50-8		X	X	
Nickel 7440-02-0		X	X	

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Nickel - 7440-02-0	carcinogen, 10/1/1989 (metallic)
Ci 77266 - 1333-86-4	carcinogen, 2/21/2003 (airborne, unbound particles of respirable size)

**U.S. State Right-to-Know Regulations**

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	X		X	X	X
Graphite 7782-42-5	X	X	X		
Propyl propionate 106-36-5		X	X		
Ethylene carbonate 96-49-1		X	X		
Copper 7440-50-8	X	X	X	X	X
Phosphate(1-), hexafluoro-, lithium 21324-40-3	X				
Nickel 7440-02-0	X	X	X	X	X
Aluminum 7429-90-5	X	X	X	X	
Ci 77266 1333-86-4	X	X	X		X

**16. OTHER INFORMATION**

**NFPA** Health hazards 1 Flammability 0 Instability 0 Physical and Chemical Properties -



---

**HMIS**                      **Health hazards** 0                      **Flammability** 0                      **Physical hazards** 0                      **Personal Protection** X

**Prepared By**                      Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Issuing Date**                      26-Sep-2024

**Revision Date**                      24-Sep-2024

**Revision Note**                      No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**