

SAFETY DATA SHEET

Sample name : Lithium-Polymer Battery

Model No. : TW 252540

Consignor : SHENZHEN TAIWOO BATTERY CO.,LTD

Address : A BUILDING JUNXINGLONG
INDUSTRIALAREA SHIYAN TOWN SHENZHEN
P. R. CHINA

1. IDENTIFICATION

Product identifier

Product Name Lithium-Polymer Battery
 Model: TW 252540
 Nominal Voltage: 3.7V
 Typical Capacity: 250mAh
 Watt-hour: 0.925Wh

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use LITHIUM ION BATTERIES
Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name SHENZHEN TAIWOO BATTERY CO.,LTD
Supplier Address A BUILDING JUNXINGLONG INDUSTRIALAREA SHIYAN TOWN
 SHENZHEN P. R. CHINA
Supplier Phone Number Phone: +86-755-27648152
Emergency telephone number Phone: +86-755-27648152

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the OSHA Hazard Communication Standard. This product is an article which is a sealed battery and as such does not require an SDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

GHS Label elements, including precautionary statements

Emergency Overview

Signal word	Danger
Hazard Statements	
Harmful if swallowed	
Causes severe skin burns and eye damage	
Suspected of causing cancer	
Causes damage to organs through prolonged or repeated exposure	
	

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Wear protective gloves/protective clothing/eye protection/face protection
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor
 Specific treatment (see supplemental first aid instructions on this label)

Eyes

Immediately call a POISON CENTER or doctor
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]
 Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing
 Immediately call a POISON CENTER or doctor

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell
 Rinse mouth
 IF SWALLOWED: Rinse mouth. DO NOT induce vomiting
 Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Unknown Toxicity

112.3 % of the mixture consists of ingredient(s) of unknown toxicity

88.4 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

101.1 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

112.3 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

112.3 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

112.3 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Other information

May be harmful in contact with skin Very toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
Lithium Cobalt Oxide	12190-79-3	25~50
1,1-Difluoroethylene polymer	24937-79-9	0~5
Aluminum	7429-90-5	2~10
Graphite	7782-42-5	20~30
Copper	7440-50-8	5~10
Polyethylene	9002-88-4	5~10
Phosphate(1-), hexafluoro-, lithium	21324-40-3	10~20
Nickel	7440-02-0	0.5~5
Polypropylene	9003-07-0	5~10

4. FIRST AID MEASURES

First aid measures

General Advice

First aid is upon rupture of sealed battery.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.

Skin Contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.

Inhalation

Remove to fresh air. Get medical attention immediately if symptoms occur.

Ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Call a physician.

Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8).
Most important symptoms and effects, both acute and delayed	
Most Important Symptoms and Effects	Coughing and/or wheezing. Itching.
Indication of any immediate medical attention and special treatment needed	
Notes to Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

No information available.

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental Precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

In case of rupture. Use personal protection equipment. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Do not breathe dust / fume / gas / mist / vapors / spray.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Incompatible Products

Strong acids. Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide 12190-79-3	TWA: 0.02 mg/m ³	--	--
Carbon 7440-44-0	TWA: 2 mg/m ³ respirable fraction all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust
Copper 7440-50-8	TWA: 0.2 mg/m ³ fume TWA: 1 mg/m ³ Cu dust and mist	TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ dust and mist (vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust

		total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Al Aluminum	
--	--	--	--

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value
 OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIOv. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers
 Eyewash stations
 Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection If splashes are likely to occur: Wear safety glasses with side shields (or goggles). None required for consumer use.

Skin and Body Protection Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical	Solid containing liquid, Solid	Odor	None
Appearance	Silvery	Odor Threshold	No information available
Color	No information available		

Property	Values	Remarks Method
pH	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air	No data available	None known

Upper flammability limit	No data available	None known
Lower flammability limit	No data available	None known
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	Insoluble in water	None known
Solubility in other solvents	No data available	None known
Partition coefficient:	No data available	None known
n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing Properties	No data available	
Other Information		
Softening Point	No data available	
VOC Content (%)	No data available	
Particle Size	No data available	
Particle Size Distribution		

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Product does not present an acute toxicity hazard based on known or supplied

information. In case of rupture.

Inhalation

Specific test data for the substance or mixture is not available.

May cause irritation of respiratory tract.

Eye Contact

Specific test data for the substance or mixture is not available.

Expected to be an irritant based on components. Irritating to eyes.

May cause redness, itching, and pain. May cause temporary eye irritation.

Skin Contact

Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation.

Ingestion

Specific test data for the substance or mixture is not available.

Ingestion may cause irritation to mucous membranes.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Graphite 7782-42-5	> 10000 mg/kg (Rat)	-	-

Information on toxicological effects**Symptoms**

Erythema (skin redness). May cause redness and tearing of the eyes.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Sensitization**

No information available.

Mutagenic Effects

No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide 12190-79-3	A3	Group 2B	Reasonably Anticipated	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity

Contains a known or suspected reproductive toxin.

STOT - single exposure

No information available.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the OSHA Hazard Communication Standard, this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

Chronic Toxicity

Contains a known or suspected carcinogen. Contains a known or

suspected reproductive toxin. Possible risk of irreversible effects. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse liver effects.

Target Organ Effects

Respiratory system. Eyes. Skin. Reproductive System. Central Vascular System (CVS). Kidney. Liver. Bone marrow. Endocrine system. Lungs. Spleen.

Aspiration Hazard

No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

497.20 mg/kg

ATEmix**(dermal)**

2,678.60 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Copper 7440-50-8	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50:= 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas)		48h EC50: = 0.03 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Other adverse effects

No information available.

13.DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

Should not be released into the environment.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste

Chemical Name	California Hazardous Waste
Lithium Cobalt Oxide	Toxic
Copper	Toxic
Aluminum	Ignitable powder

14. TRANSPORT INFORMATION

Note:

According to PACKING INSTRUCTION 967 of IATA DGR 60th Edition for transportation, the special provision 188 of IMDG (inc Amdt 38-16). The batteries should be securely packed and protected against short-circuits. Examine whether the package of the containers are integrate and tighten closed before transport. Take in a cargo of them without falling, dropping, and breakage. Prevent collapse of cargo piles. Don't put the goods together with oxidizer and chief food chemicals. The transport vehicle and ship must be cleaned and sterilized otherwise it is not allowed to assemble articles. During transport, the vehicle should prevent exposure, rain and high temperature. For stopovers, the vehicle should be away from fire and heat sources. When transported by sea, the assemble place should keep away from bedroom and kitchen, and isolated from the engine room, power and fire source. Under the condition of Road Transportation, the driver should drive in accordance with regulated route, don't stop over in the residential area and congested area. Forbid to use wooden, cement for bulk transport.

UN number

3481

UN Proper shipping name

LITHIUM ION BATTERIES PACKED WITH EQUIPMENT (including lithium ion polymer batteries)

Transport hazard class(es)	9
Packing group (if applicable)	II
Marine pollutant (Yes/No)	Not regulated
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)	No information available.
Special precautions	No information available.
Transport fashion	By air, by sea, by railway, by road.

15. REGULATORY INFORMATION

OSHA hazard communication standard

_____Hazardous

_____V_____Non-hazardous

16. OTHER INFORMATION

Preparation and revision information

Prepared By	SHENZHEN TAIWOO BATTERY CO.,LTD A BUILDING JUNXINGLONG INDUSTRIALAREA SHIYAN TOWN SHENZHEN P. R. CHINA
Date of this revision	2019-07-29

Abbreviations and acronyms

TSCA:	Toxic Substances Control Act, The American chemical inventory.
DSL	Domestic Substances List
EINECS:	European Inventory of Existing Commercial chemical Substances
ECL	Existing Chemicals List, the Korean chemical inventory.
IECSC	Inventory of existing chemical substances in China.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet