



AMERICAN INTERNATIONAL INDUSTRIES

Safety Data Sheet

NailTek Hydrate 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name NailTek Hydrate 1
Product number 87-0806.2 found in 37806 (30-12332 Blend)

Relevant identified uses of the substance or mixture and uses advised against

Uses: Personal Care Products

Details of the supplier of the safety data sheet

Name American International Industries
Address 2220 Gaspar Ave
Los Angeles, CA 90040
USA

Telephone 323-728-2999

Emergency telephone number

Chem-Tel: 1(800) 255-3924

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP) and OSHA Hazardous Communication Standard 29 CFR §1910.1200.

- Eye damage/irritation (chapter 3.3), Cat. 2, H319
- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3, H336
- Flammable liquids (chapter 2.6), Cat. 2, H225

For the full text corresponding to the "H"-codes displayed in this section, refer to Section 16.

Label elements

Labeling according to Regulation (EC) No 1272/2008 [CLP] and OSHA Hazardous Communication Standard 29 CFR §1910.1200.

Safety Data Sheet

NailTek Hydrate 1

Hazard pictograms



Signal word

Danger

Hazard statement(s)

H319

Causes serious eye irritation

H336

May cause drowsiness or dizziness

H225

Highly flammable liquid and vapor

Precautionary statement(s)

P210

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

P261

Avoid breathing dust/fume/gas/mist/vapours/spray.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

P312

Call a POISON CENTER/doctor/... if you feel unwell.

P337+P313

If eye irritation persists: Get medical advice/attention.

SECTION 3: Composition/information on ingredients

Mixtures

Components

Component	Concentration
n-Butyl Acetate (CAS no.: 123-86-4; EC no.: 204-658-1; Index no.: 607-025-00-1)	10 - 40 %
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 3; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H226 - Flammable liquid and vapor; H336 - May cause drowsiness or dizziness.	
Ethyl Acetate (CAS no.: 141-78-6; EC no.: 205-500-4; Index no.: 607-022-00-5)	25 - 50 %
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2; Eye damage/irritation (chapter 3.3), Cat. 2; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H225 - Highly flammable liquid and vapor; H319 - Causes serious eye irritation; H336 - May cause drowsiness or dizziness.	
Isopropyl Alcohol (CAS no.: 67-63-0; EC no.: 200-661-7; Index no.: 603-117-00-0)	2 - 8 %
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2; Eye damage/irritation (chapter 3.3), Cat. 2; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H225 - Highly flammable liquid and vapor; H319 - Causes serious eye irritation; H336-May cause drowsiness or dizziness.	
Acetyl Tributyl Citrate (CAS no.: 77-90-7)	5 - 10 %
CLASSIFICATION: Hazardous to the aquatic environment, long-term hazard (chapter 4.1), Cat. 3. HAZARDS: H412 - Harmful to aquatic life with long lasting effects.	

SECTION 4: First aid measures

Description of first aid measures

General notes

Though this product is non hazardous for its indented use, in all cases, if symptoms persists contact a physician.

Following inhalation

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

Following skin contact

Rinse with plenty of water. Get medical attention if irritation develops and persists.

Following eye contact

Rinse thoroughly with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.

Following ingestion

Get medical attention immediately. If swallowed, do NOT induce vomiting.

Safety Data Sheet

NailTek Hydrate 1

Contact a physician or a poison control center immediately. Never give anything by mouth to an unconscious person.

Self-protection of the first aider

Use personal protective equipment.

Most important symptoms and effects, both acute and delayed

If inhaled for long periods of time, can cause dizziness/drowsiness, headache and nausea.

SECTION 5: Firefighting measures

Extinguishing media

Dry chemical, carbon dioxide, Halon foam. Water may be ineffective. Water spray may be used to keep fire exposed containers cool and to disperse vapors.

Special hazards arising from the substance or mixture

Vapors can travel to a source of ignition and flashback. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

Advice for firefighters

First responders should wear eye protection. Structural fire-fighters must wear MSHA/NIOSH approved SCBA and full protective equipment. Use a water spray or fog to reduce vapors. Water may not be effective in extinguishing a fire involving this product.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Household: Absorb with inert material and place in a appropriate waste disposal

Industrial: Avoid contact with skin, eyes, and clothing. Remove all sources of ignition. Absorb with an inert material and put the spilled material in an appropriate waste disposal. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system

Environmental precautions

Household: Do not place spilled product in any drain or water system that can go into the environment.

Industrial: Should not be released into the environment.

Methods and material for containment and cleaning up

Highway or railway spills call chemtrec (800) 424-9600 cont. U.S. Collect (202) 483-7616 from Alaska and Hawaii. Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (phone number: 800-424-8802) in case if the spill is in excess of EPA reportable quantity.

SECTION 7: Handling and storage

Precautions for safe handling

Avoid prolonged contact with the product. After use, wash hands and exposed skin with soap and water. Do not eat, drink, or smoke while handling this product.

Conditions for safe storage, including any incompatibilities

Keep this material away from heat, sparks, and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty containers may contain residual amounts of the product; therefore handle empty container with care.

Store containers in a cool dry place, away from direct sunlight, other light sources, or any intense heat. Store away from incompatible materials as appropriate.

Safety Data Sheet

NailTek Hydrate 1

SECTION 8: Exposure controls/personal protection

Control parameters

CAS: 123-86-4

n-Butyl-acetate

Cal/OSHA: 150 ppm, (ST) 200 ppm PEL inhalation; NIOSH: 150 ppm, (ST) 200 ppm REL inhalation; OSHA: 150 ppm PEL inhalation; 710 mg/m³ PEL inhalation

CAS: 141-78-6

Ethyl acetate

Cal/OSHA: 400 ppm PEL inhalation; NIOSH: 400 ppm REL inhalation; OSHA: 400 ppm PEL inhalation; 1400 mg/m³ PEL inhalation

CAS: 67-63-0

Isopropyl alcohol

Cal/OSHA: 400 ppm, (ST) 500 ppm PEL inhalation; NIOSH: 400 ppm, (ST) 500 ppm REL inhalation; OSHA: 400 ppm PEL inhalation; 980 mg/m³ PEL inhalation

Exposure controls

Appropriate engineering controls

Distribution, Workplace and Household Settings: Ensure adequate ventilation. Product Manufacturing Plant (needed at Product-Producing Plant ONLY): Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal protection equipment

Eye and face protection

Depending on the use of this product splash or safety glasses may be worn in an industrial setting. When necessary refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European standard EN166.

Skin protection

Skin Protection: None required with normal household use. Industrial Setting: Protective gloves (for hands) and protective clothing are required where repeated or prolonged skin contact may occur.

Body protection

No special body protection is required for this product under typical use and handling.

Respiratory protection

No respiratory protection is required under typical circumstances of use and handling. If necessary, use only respiratory protection authorized by U.S. OSHA 29 CFR §1920.134, or applicable U.S. local state regulations,

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Viscous Liquid/ Light Cream
Odour	Strong solvent
Odour threshold	50 ppm ethyl acetate 7 – 20 mg/m ³ n-butyl acetate
pH	No data available.
VOC	No data available.
Melting point / freezing point	No data available.
Initial boiling point and boiling range	77 C (171 F) ethyl acetate
Flash point	- 4 C (24.8 F) ethyl acetate
Evaporation rate	No data available.
Flammability (solid, gas)	Flammable

Safety Data Sheet

NailTek Hydrate 1

Upper/lower flammability limits	No data available.
Vapour pressure	100 hPa ethyl acetate
Vapour density	No data available.
Relative density	0.9 – 1.1
Solubilit(ies)	Insoluble
Partition coefficient: n-octanol/water (log Know)	0.6 ethyl acetate
Auto-ignition temperature	460 C (860 F) ethyl acetate
Decomposition temperature	No data available.
Viscosity	No data available.
Explosive properties	No data available.
Oxidising properties	No data available.
Specific gravity	0.9 – 1.1

SECTION 10: Stability and reactivity

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Incompatible materials

Acids, Alkalies, and Peroxides

Hazardous decomposition products

If exposed to extremely high temperatures, the products of decomposition may include irritating vapors and carbon oxide gases (e.g. CO₂, CO).

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Not classified

Skin corrosion/irritation

Not classified

Serious eye damage/irritation

Cause serious eye irritation.

Germ cell mutagenicity

Not classified

Carcinogenicity

Not classified

Reproductive toxicity

Not classified

STOT-single exposure

May cause drowsiness or dizziness

STOT-repeated exposure

Not classified

Safety Data Sheet

NailTek Hydrate 1

Aspiration hazard
Not classified

SECTION 12: Ecological information

Toxicity

The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Persistence and degradability

No data available.

Bioaccumulative potential

No data available.

Mobility in soil

No data available.

SECTION 13: Disposal considerations

Waste treatment methods

Disposal of the product

Dispose of in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

DOT (US)

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint

IMDG

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint

IATA

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Massachusetts Right To Know Components

Chemical name: Butyl acetate

CAS number: 123-86-4

New Jersey Right To Know Components

Common name: n-BUTYL ACETATE

CAS number: 123-86-4

Pennsylvania Right To Know Components

Safety Data Sheet

NailTek Hydrate 1

Chemical name: Acetic acid, butyl ester
CAS number: 123-86-4

Massachusetts Right To Know Components

Chemical name: Ethyl acetate
CAS number: 141-78-6

New Jersey Right To Know Components

Common name: ETHYL ACETATE
CAS number: 141-78-6

Pennsylvania Right To Know Components

Chemical name: Acetic acid ethyl ester
CAS number: 141-78-6

New Jersey Right To Know Components

Common name: NITROCELLULOSE
CAS number: 9004-70-0

Pennsylvania Right To Know Components

Chemical name: Cellulose, nitrate
CAS number: 9004-70-0

Massachusetts Right To Know Components

Chemical name: Isopropyl alcohol (mfg-strong acid process)
CAS number: 67-63-0

New Jersey Right To Know Components

Common name: ISOPROPYL ALCOHOL
CAS number: 67-63-0

Pennsylvania Right To Know Components

Chemical name: 2-Propanol
CAS number: 67-63-0

SECTION 16: Other information

Full text of hazard statements referenced in Section 2

H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H361	Suspected of damaging fertility or the unborn child
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Further information/disclaimer

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR § 1910.1200 and GHS. To the best of A.I.I.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.



AMERICAN INTERNATIONAL INDUSTRIES

Safety Data Sheet

NailTek Strengthen 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name NailTek Strengthen 1
Product number 87-20372.2 found in 37806 (30-12328 Blend)

Relevant identified uses of the substance or mixture and uses advised against

Uses: Personal Care Products

Details of the supplier of the safety data sheet

Name American International Industries
Address 2220 Gaspar Ave
Los Angeles, CA 90040
USA

Telephone 323-728-2999

Emergency telephone number

Chem-Tel: 1(800) 255-3924

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP) and OSHA Hazardous Communication Standard 29 CFR §1910.1200.

- Eye damage/irritation (chapter 3.3), Cat. 2, H319
- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3, H336
- Flammable liquids (chapter 2.6), Cat. 2, H225

For the full text corresponding to the "H"-codes displayed in this section, refer to Section 16.

Label elements

Labeling according to Regulation (EC) No 1272/2008 [CLP] and OSHA Hazardous Communication Standard 29 CFR §1910.1200.

Safety Data Sheet

NailTek Strengthen 1

Hazard pictograms



Signal word

Danger

Hazard statement(s)

H319

Causes serious eye irritation

H336

May cause drowsiness or dizziness

H225

Highly flammable liquid and vapor

Precautionary statement(s)

P210

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

P261

Avoid breathing dust/fume/gas/mist/vapours/spray.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

P312

Call a POISON CENTER/doctor/... if you feel unwell.

P337+P313

If eye irritation persists: Get medical advice/attention.

SECTION 3: Composition/information on ingredients

Mixtures

Components

Component	Concentration
n-Butyl Acetate (CAS no.: 123-86-4; EC no.: 204-658-1; Index no.: 607-025-00-1)	10 - 40 %
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 3; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H226 - Flammable liquid and vapor; H336 - May cause drowsiness or dizziness.	
Ethyl Acetate (CAS no.: 141-78-6; EC no.: 205-500-4; Index no.: 607-022-00-5)	25 - 50 %
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2; Eye damage/irritation (chapter 3.3), Cat. 2; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H225 - Highly flammable liquid and vapor; H319 - Causes serious eye irritation; H336 - May cause drowsiness or dizziness.	
Isopropyl Alcohol (CAS no.: 67-63-0; EC no.: 200-661-7; Index no.: 603-117-00-0)	2 - 8 %
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2; Eye damage/irritation (chapter 3.3), Cat. 2; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H225 - Highly flammable liquid and vapor; H319 - Causes serious eye irritation; H336-May cause drowsiness or dizziness.	
Acetyl Tributyl Citrate (CAS no.: 77-90-7)	5 - 10 %
CLASSIFICATION: Hazardous to the aquatic environment, long-term hazard (chapter 4.1), Cat. 3. HAZARDS: H412 - Harmful to aquatic life with long lasting effects.	

SECTION 4: First aid measures

Description of first aid measures

General notes

Though this product is non hazardous for its indented use, in all cases, if symptoms persists contact a physician.

Following inhalation

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

Following skin contact

Rinse with plenty of water. Get medical attention if irritation develops and persists.

Following eye contact

Rinse thoroughly with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.

Following ingestion

Get medical attention immediately. If swallowed, do NOT induce vomiting.

Safety Data Sheet

NailTek Strengthen 1

Contact a physician or a poison control center immediately. Never give anything by mouth to an unconscious person.

Self-protection of the first aider

Use personal protective equipment.

Most important symptoms and effects, both acute and delayed

If inhaled for long periods of time, can cause dizziness/drowsiness, headache and nausea.

SECTION 5: Firefighting measures

Extinguishing media

Dry chemical, carbon dioxide, Halon foam. Water may be ineffective. Water spray may be used to keep fire exposed containers cool and to disperse vapors.

Special hazards arising from the substance or mixture

Vapors can travel to a source of ignition and flashback. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

Advice for firefighters

First responders should wear eye protection. Structural fire-fighters must wear MSHA/NIOSH approved SCBA and full protective equipment. Use a water spray or fog to reduce vapors. Water may not be effective in extinguishing a fire involving this product.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Household: Absorb with inert material and place in a appropriate waste disposal

Industrial: Avoid contact with skin, eyes, and clothing. Remove all sources of ignition. Absorb with an inert material and put the spilled material in an appropriate waste disposal. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system

Environmental precautions

Household: Do not place spilled product in any drain or water system that can go into the environment.

Industrial: Should not be released into the environment.

Methods and material for containment and cleaning up

Highway or railway spills call chemtrec (800) 424-9600 cont. U.S. Collect (202) 483-7616 from Alaska and Hawaii. Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (phone number: 800-424-8802) in case if the spill is in excess of EPA reportable quantity.

SECTION 7: Handling and storage

Precautions for safe handling

Avoid prolonged contact with the product. After use, wash hands and exposed skin with soap and water. Do not eat, drink, or smoke while handling this product.

Conditions for safe storage, including any incompatibilities

Keep this material away from heat, sparks, and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty containers may contain residual amounts of the product; therefore handle empty container with care.

Store containers in a cool dry place, away from direct sunlight, other light sources, or any intense heat. Store away from incompatible materials as appropriate.

Safety Data Sheet

NailTek Strengthen 1

SECTION 8: Exposure controls/personal protection

Control parameters

CAS: 123-86-4

n-Butyl-acetate

Cal/OSHA: 150 ppm, (ST) 200 ppm PEL inhalation; NIOSH: 150 ppm, (ST) 200 ppm REL inhalation; OSHA: 150 ppm PEL inhalation; 710 mg/m³ PEL inhalation

CAS: 141-78-6

Ethyl acetate

Cal/OSHA: 400 ppm PEL inhalation; NIOSH: 400 ppm REL inhalation; OSHA: 400 ppm PEL inhalation; 1400 mg/m³ PEL inhalation

CAS: 67-63-0

Isopropyl alcohol

Cal/OSHA: 400 ppm, (ST) 500 ppm PEL inhalation; NIOSH: 400 ppm, (ST) 500 ppm REL inhalation; OSHA: 400 ppm PEL inhalation; 980 mg/m³ PEL inhalation

Exposure controls

Appropriate engineering controls

Distribution, Workplace and Household Settings: Ensure adequate ventilation. Product Manufacturing Plant (needed at Product-Producing Plant ONLY): Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal protection equipment

Eye and face protection

Depending on the use of this product splash or safety glasses may be worn in an industrial setting. When necessary refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European standard EN166.

Skin protection

Skin Protection: None required with normal household use. Industrial Setting: Protective gloves (for hands) and protective clothing are required where repeated or prolonged skin contact may occur.

Body protection

No special body protection is required for this product under typical use and handling.

Respiratory protection

No respiratory protection is required under typical circumstances of use and handling. If necessary, use only respiratory protection authorized by U.S. OSHA 29 CFR §1920.134, or applicable U.S. local state regulations,

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Clear Viscous Liquid/ Light Cream
Odour	Strong solvent
Odour threshold	50 ppm ethyl acetate. 7 – 20 mg/m ³ n-butyl acetate
pH	No data available.
VOC	No data available.
Melting point / freezing point	No data available.
Initial boiling point and boiling range	77 C (171 F) ethyl acetate
Flash point	- 4 C (24.8 F) ethyl acetate
Evaporation rate	No data available.
Flammability (solid, gas)	Flammable

Safety Data Sheet

NailTek Strengthen 1

Upper/lower flammability limits	No data available.
Vapour pressure	100 hPa ethyl acetate
Vapour density	No data available.
Relative density	0.9 – 1.1
Solubilit(ies)	Insoluble
Partition coefficient: n-octanol/water (log Know)	0.6 ethyl acetate
Auto-ignition temperature	460 C (860 F) ethyl acetate
Decomposition temperature	No data available.
Viscosity	No data available.
Explosive properties	No data available.
Oxidising properties	No data available.
Specific gravity	0.9 – 1.1

SECTION 10: Stability and reactivity

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Incompatible materials

Acids, Alkalies, and Peroxides

Hazardous decomposition products

If exposed to extremely high temperatures, the products of decomposition may include irritating vapors and carbon oxide gases (e.g. CO₂, CO).

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Not classified

Skin corrosion/irritation

Not classified

Serious eye damage/irritation

Cause serious eye irritation.

Germ cell mutagenicity

Not classified

Carcinogenicity

Not classified

Reproductive toxicity

Not classified

STOT-single exposure

May cause drowsiness or dizziness

STOT-repeated exposure

Not classified

Safety Data Sheet

NailTek Strengthen 1

Aspiration hazard
Not classified

SECTION 12: Ecological information

Toxicity

The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Persistence and degradability

No data available.

Bioaccumulative potential

No data available.

Mobility in soil

No data available.

SECTION 13: Disposal considerations

Waste treatment methods

Disposal of the product

Dispose of in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

DOT (US)

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint

IMDG

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint

IATA

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Massachusetts Right To Know Components

Chemical name: Butyl acetate

CAS number: 123-86-4

New Jersey Right To Know Components

Common name: n-BUTYL ACETATE

CAS number: 123-86-4

Pennsylvania Right To Know Components

Safety Data Sheet

NailTek Strengthen 1

Chemical name: Acetic acid, butyl ester
CAS number: 123-86-4

Massachusetts Right To Know Components

Chemical name: Ethyl acetate
CAS number: 141-78-6

New Jersey Right To Know Components

Common name: ETHYL ACETATE
CAS number: 141-78-6

Pennsylvania Right To Know Components

Chemical name: Acetic acid ethyl ester
CAS number: 141-78-6

New Jersey Right To Know Components

Common name: NITROCELLULOSE
CAS number: 9004-70-0

Pennsylvania Right To Know Components

Chemical name: Cellulose, nitrate
CAS number: 9004-70-0

Massachusetts Right To Know Components

Chemical name: Isopropyl alcohol (mfg-strong acid process)
CAS number: 67-63-0

New Jersey Right To Know Components

Common name: ISOPROPYL ALCOHOL
CAS number: 67-63-0

Pennsylvania Right To Know Components

Chemical name: 2-Propanol
CAS number: 67-63-0

SECTION 16: Other information

Full text of hazard statements referenced in Section 2

H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapour
H361	Suspected of damaging fertility or the unborn child
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Further information/disclaimer

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR § 1910.1200 and GHS. To the best of A.I.I.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.