



AMERICAN INTERNATIONAL INDUSTRIES

Safety Data Sheet

NailTek Hydrate 3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name NailTek Hydrate 3
Product number 37825 (30-12359 Blend) Found in Kit: 37808

Relevant identified uses of the substance or mixture and uses advised against

Uses: Personal Care Products

Details of the supplier of the safety data sheet

Name American International Industries
Address 2220 Gaspar Ave
Los Angeles, CA 90040
USA

Telephone 323-728-2999

Emergency telephone number

Chem-Tel: 1(800) 255-3924

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP) and OSHA Hazardous Communication Standard 29 CFR §1910.1200.

- Eye damage/irritation (chapter 3.3), Cat. 2, H319
- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3, H336
- Hazardous to the aquatic environment, long-term hazard (chapter 4.1), Cat. 3, H412
- Flammable liquids (chapter 2.6), Cat. 2, H225

For the full text corresponding to the "H"-codes displayed in this section, refer to Section 16.

Label elements

Labeling according to Regulation (EC) No 1272/2008 [CLP] and OSHA Hazardous Communication Standard 29 CFR §1910.1200.

Safety Data Sheet

NailTek Hydrate 3

Hazard pictograms



Signal word

Danger

Hazard statement(s)

H319 Causes serious eye irritation
H336 May cause drowsiness or dizziness
H412 Harmful to aquatic life with long lasting effects
H225 Highly flammable liquid and vapor

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P312 Call a POISON CENTER/doctor/... if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice/attention.

SECTION 3: Composition/information on ingredients

Mixtures

Components

Component	Concentration
n-Butyl Acetate (CAS no.: 123-86-4; EC no.: 204-658-1; Index no.: 607-025-00-1)	25 - 50 %
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 3; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H226 - Flammable liquid and vapor; H336 - May cause drowsiness or dizziness.	
Ethyl Acetate (CAS no.: 141-78-6; EC no.: 205-500-4; Index no.: 607-022-00-5)	25 - 50 %
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2; Eye damage/irritation (chapter 3.3), Cat. 2; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H225 - Highly flammable liquid and vapor; H319 - Causes serious eye irritation; H336 - May cause drowsiness or dizziness.	
Isopropyl Alcohol (CAS no.: 67-63-0; EC no.: 200-661-7; Index no.: 603-117-00-0)	4.25 - 8.5 %
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2; Eye damage/irritation (chapter 3.3), Cat. 2; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H225 - Highly flammable liquid and vapor; H319 - Causes serious eye irritation; H336 - May cause drowsiness or dizziness.	
Acetyl Tributyl Citrate (CAS no.: 77-90-7)	5 - 10 %
CLASSIFICATION: Hazardous to the aquatic environment, long-term hazard (chapter 4.1), Cat. 3. HAZARDS: H412 - Harmful to aquatic life with long lasting effects.	
Benzophenone-3 (CAS no.: 131-57-7; EC no.: 205-031-5)	0.1 - < 1%
CLASSIFICATIONS: Specific target organ toxicity, repeated exposure (chapter 3.9), Cat. 2; Hazardous to the aquatic environment, acute hazard (chapter 4.1), Cat. 1; Hazardous to the aquatic environment, long-term hazard (chapter 4.1), Cat. 1. HAZARDS: H373 - May cause damage to organs; H400 - Very toxic to aquatic life; H410 - Very toxic to aquatic life with long lasting effects.	

SECTION 4: First aid measures

Description of first aid measures

General notes Though this product is non hazardous for its intended use, in all cases, if symptoms persists contact a physician.

Following inhalation If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

Following skin contact Rinse with plenty of water. Get medical attention if irritation develops and persists.

Safety Data Sheet

NailTek Hydrate 3

Following eye contact	Rinse thoroughly with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.
Following ingestion	Get medical attention immediately. If swallowed, do NOT induce vomiting. Contact a physician or a poison control center immediately. Never give anything by mouth to an unconscious person.
Self-protection of the first aider	Use personal protective equipment.

Most important symptoms and effects, both acute and delayed

If inhaled for long periods of time, can cause dizziness/drowsiness, headache and nausea.

SECTION 5: Firefighting measures

Extinguishing media

Dry chemical, carbon dioxide, Halon foam. Water may be ineffective. Water spray may be used to keep fire exposed containers cool and to disperse vapors.

Special hazards arising from the substance or mixture

Vapors can travel to a source of ignition and flashback. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

Advice for firefighters

First responders should wear eye protection. Structural fire-fighters must wear MSHA/NIOSH approved SCBA and full protective equipment. Use a water spray or fog to reduce vapors. Water may not be effective in extinguishing a fire involving this product.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Household: Absorb with inert material and place in a appropriate waste disposal

Industrial: Avoid contact with skin, eyes, and clothing. Remove all sources of ignition. Absorb with an inert material and put the spilled material in an appropriate waste disposal. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system

Environmental precautions

Household: Do not place spilled product in any drain or water system that can go into the environment.

Industrial: Should not be released into the environment.

Methods and material for containment and cleaning up

Highway or railway spills call chemtrec (800) 424-9600 cont. U.S. Collect (202) 483-7616 from Alaska and Hawaii. Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (phone number: 800-424-8802) in case if the spill is in excess of EPA reportable quantity.

SECTION 7: Handling and storage

Precautions for safe handling

Avoid prolonged contact with the product. After use, wash hands and exposed skin with soap and water. Do not eat, drink, or smoke while handling this product.

Conditions for safe storage, including any incompatibilities

Keep this material away from heat, sparks, and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty containers may contain residual amounts of the product; therefore

Safety Data Sheet

NailTek Hydrate 3

handle empty container with care.

Store containers in a cool dry place, away from direct sunlight, other light sources, or any intense heat. Store away from incompatible materials as appropriate.

SECTION 8: Exposure controls/personal protection

Control parameters

CAS: 123-86-4

n-Butyl-acetate

Cal/OSHA: 150 ppm, (ST) 200 ppm PEL inhalation; NIOSH: 150 ppm, (ST) 200 ppm REL inhalation; OSHA: 150 ppm PEL inhalation; 710 mg/m³ PEL inhalation

CAS: 141-78-6

Ethyl acetate

Cal/OSHA: 400 ppm PEL inhalation; NIOSH: 400 ppm REL inhalation; OSHA: 400 ppm PEL inhalation; 1400 mg/m³ PEL inhalation

CAS: 67-63-0

Isopropyl alcohol

Cal/OSHA: 400 ppm, (ST) 500 ppm PEL inhalation; NIOSH: 400 ppm, (ST) 500 ppm REL inhalation; OSHA: 400 ppm PEL inhalation; 980 mg/m³ PEL inhalation

Exposure controls

Appropriate engineering controls

Distribution, Workplace and Household Settings: Ensure adequate ventilation. Product Manufacturing Plant (needed at Product-Producing Plant ONLY): Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal protection equipment

Eye and face protection

Depending on the use of this product splash or safety glasses may be worn in an industrial setting. When necessary refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European standard EN166.

Skin protection

Skin Protection: None required with normal household use. Industrial Setting: Protective gloves (for hands) and protective clothing are required where repeated or prolonged skin contact may occur.

Body protection

No special body protection is required for this product under typical use and handling.

Respiratory protection

No respiratory protection is required under typical circumstances of use and handling. If necessary, use only respiratory protection authorized by U.S. OSHA 29 CFR §1920.134, or applicable U.S. local state regulations,

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Viscous Liquid/ Transparent.
Odour	Strong solvent
Odour threshold	50 ppm ethyl acetate 7 – 20 mg/m ³ n-butyl acetate
pH	No data available.
VOC	No data available.
Melting point / freezing point	No data available.

Safety Data Sheet

NailTek Hydrate 3

Initial boiling point and boiling range	77 C (171 F) ethyl acetate
Flash point	- 4 C (24.8 F) ethyl acetate
Evaporation rate	No data available.
Flammability (solid, gas)	Flammable
Upper/lower flammability limits	No data available.
Vapour pressure	100 hPa ethyl acetate
Vapour density	No data available.
Relative density	0.9 – 1.1
Solubilit(ies)	No data available.
Partition coefficient: n-octanol/water (log Know)	0.6 ethyl acetate
Auto-ignition temperature	460 C (860 F) ethyl acetate
Decomposition temperature	No data available.
Viscosity	No data available.
Explosive properties	No data available.
Oxidising properties	No data available.
Specific gravity	0.9 – 1.1

SECTION 10: Stability and reactivity

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Incompatible materials

Acids, Alkalies, and Peroxides

Hazardous decomposition products

If exposed to extremely high temperatures, the products of decomposition may include irritating vapors and carbon oxide gases (e.g. CO₂, CO).

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Not classified

Skin corrosion/irritation

Not classified

Serious eye damage/irritation

Cause serious eye irritation.

Germ cell mutagenicity

Not classified

Carcinogenicity

Not classified

Reproductive toxicity

Not classified

STOT-single exposure

May cause drowsiness or dizziness

Safety Data Sheet

NailTek Hydrate 3

STOT-repeated exposure

Not classified

Aspiration hazard

Not classified

SECTION 12: Ecological information

Toxicity

Harmful to aquatic life with long lasting effects.

Persistence and degradability

No data available.

Bioaccumulative potential

No data available.

Mobility in soil

No data available.

SECTION 13: Disposal considerations

Waste treatment methods

Disposal of the product

Dispose of in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

DOT (US)

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint

IMDG

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint

IATA

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Massachusetts Right To Know Components

Chemical name: Butyl acetate

CAS number: 123-86-4

New Jersey Right To Know Components

Common name: n-BUTYL ACETATE

Safety Data Sheet

NailTek Hydrate 3

CAS number: 123-86-4

Pennsylvania Right To Know Components

Chemical name: Acetic acid, butyl ester

CAS number: 123-86-4

Massachusetts Right To Know Components

Chemical name: Ethyl acetate

CAS number: 141-78-6

New Jersey Right To Know Components

Common name: ETHYL ACETATE

CAS number: 141-78-6

Pennsylvania Right To Know Components

Chemical name: Acetic acid ethyl ester

CAS number: 141-78-6

New Jersey Right To Know Components

Common name: NITROCELLULOSE

CAS number: 9004-70-0

Pennsylvania Right To Know Components

Chemical name: Cellulose, nitrate

CAS number: 9004-70-0

Massachusetts Right To Know Components

Chemical name: Isopropyl alcohol (mfg-strong acid process)

CAS number: 67-63-0

New Jersey Right To Know Components

Common name: ISOPROPYL ALCOHOL

CAS number: 67-63-0

Pennsylvania Right To Know Components

Chemical name: 2-Propanol

CAS number: 67-63-0

SECTION 16: Other information

Full text of hazard statements referenced in Section 2

H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapour

Further information/disclaimer

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR § 1910.1200 and GHS. To the best of A.I.I.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.



AMERICAN INTERNATIONAL INDUSTRIES

Safety Data Sheet

NailTek Strengthen 3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name NailTek Strengthen 3
Product number 37819 (30-12360 Blend) Found in Kit: 37808

Relevant identified uses of the substance or mixture and uses advised against

Uses: Personal Care Products

Details of the supplier of the safety data sheet

Name American International Industries
Address 2220 Gaspar Ave
Los Angeles, CA 90040
USA

Telephone 323-728-2999

Emergency telephone number

Chem-Tel: 1(800) 255-3924

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP) and OSHA Hazardous Communication Standard 29 CFR §1910.1200.

- Eye damage/irritation (chapter 3.3), Cat. 2, H319
- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3, H336
- Hazardous to the aquatic environment, long-term hazard (chapter 4.1), Cat. 3, H412
- Flammable liquids (chapter 2.6), Cat. 2, H225

For the full text corresponding to the "H"-codes displayed in this section, refer to Section 16.

Label elements

Labeling according to Regulation (EC) No 1272/2008 [CLP] and OSHA Hazardous Communication Standard 29 CFR §1910.1200.

Safety Data Sheet

NailTek Strengthen 3

Hazard pictograms



Signal word

Danger

Hazard statement(s)

H319

Causes serious eye irritation

H336

May cause drowsiness or dizziness

H412

Harmful to aquatic life with long lasting effects

H225

Highly flammable liquid and vapor

Precautionary statement(s)

P210

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

P261

Avoid breathing dust/fume/gas/mist/vapours/spray.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

P312

Call a POISON CENTER/doctor/... if you feel unwell.

P337+P313

If eye irritation persists: Get medical advice/attention.

SECTION 3: Composition/information on ingredients

Mixtures

Components

Component	Concentration
n-Butyl Acetate (CAS no.: 123-86-4; EC no.: 204-658-1; Index no.: 607-025-00-1)	25 - 50 %
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 3; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H226 - Flammable liquid and vapor; H336 - May cause drowsiness or dizziness.	
Ethyl Acetate (CAS no.: 141-78-6; EC no.: 205-500-4; Index no.: 607-022-00-5)	25 - 50 %
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2; Eye damage/irritation (chapter 3.3), Cat. 2; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H225 - Highly flammable liquid and vapor; H319 - Causes serious eye irritation; H336 - May cause drowsiness or dizziness.	
Isopropyl Alcohol (CAS no.: 67-63-0; EC no.: 200-661-7; Index no.: 603-117-00-0)	4.25 - 8.5 %
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2; Eye damage/irritation (chapter 3.3), Cat. 2; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H225 - Highly flammable liquid and vapor; H319 - Causes serious eye irritation; H336 - May cause drowsiness or dizziness.	
Acetyl Tributyl Citrate (CAS no.: 77-90-7)	5 - 10 %
CLASSIFICATION: Hazardous to the aquatic environment, long-term hazard (chapter 4.1), Cat. 3. HAZARDS: H412 - Harmful to aquatic life with long lasting effects.	
Benzophenone-3 (CAS no.: 131-57-7; EC no.: 205-031-5)	0.1 - < 1%
CLASSIFICATIONS: Specific target organ toxicity, repeated exposure (chapter 3.9), Cat. 2; Hazardous to the aquatic environment, acute hazard (chapter 4.1), Cat. 1; Hazardous to the aquatic environment, long-term hazard (chapter 4.1), Cat. 1. HAZARDS: H373 - May cause damage to organs; H400 - Very toxic to aquatic life; H410 - Very toxic to aquatic life with long lasting effects.	

SECTION 4: First aid measures

Description of first aid measures

General notes

Though this product is non hazardous for its intended use, in all cases, if symptoms persists contact a physician.

Following inhalation

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

Following skin contact

Rinse with plenty of water. Get medical attention if irritation develops and persists.

Safety Data Sheet

NailTek Strengthen 3

Following eye contact	Rinse thoroughly with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.
Following ingestion	Get medical attention immediately. If swallowed, do NOT induce vomiting. Contact a physician or a poison control center immediately. Never give anything by mouth to an unconscious person.
Self-protection of the first aider	Use personal protective equipment.

Most important symptoms and effects, both acute and delayed

If inhaled for long periods of time, can cause dizziness/drowsiness, headache and nausea.

SECTION 5: Firefighting measures

Extinguishing media

Dry chemical, carbon dioxide, Halon foam. Water may be ineffective. Water spray may be used to keep fire exposed containers cool and to disperse vapors.

Special hazards arising from the substance or mixture

Vapors can travel to a source of ignition and flashback. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

Advice for firefighters

First responders should wear eye protection. Structural fire-fighters must wear MSHA/NIOSH approved SCBA and full protective equipment. Use a water spray or fog to reduce vapors. Water may not be effective in extinguishing a fire involving this product.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Household: Absorb with inert material and place in a appropriate waste disposal

Industrial: Avoid contact with skin, eyes, and clothing. Remove all sources of ignition. Absorb with an inert material and put the spilled material in an appropriate waste disposal. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system

Environmental precautions

Household: Do not place spilled product in any drain or water system that can go into the environment.

Industrial: Should not be released into the environment.

Methods and material for containment and cleaning up

Highway or railway spills call chemtrec (800) 424-9600 cont. U.S. Collect (202) 483-7616 from Alaska and Hawaii. Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (phone number: 800-424-8802) in case if the spill is in excess of EPA reportable quantity.

SECTION 7: Handling and storage

Precautions for safe handling

Avoid prolonged contact with the product. After use, wash hands and exposed skin with soap and water. Do not eat, drink, or smoke while handling this product.

Conditions for safe storage, including any incompatibilities

Keep this material away from heat, sparks, and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty containers may contain residual amounts of the product; therefore

Safety Data Sheet

NailTek Strengthen 3

handle empty container with care.

Store containers in a cool dry place, away from direct sunlight, other light sources, or any intense heat. Store away from incompatible materials as appropriate.

SECTION 8: Exposure controls/personal protection

Control parameters

CAS: 123-86-4

n-Butyl-acetate

Cal/OSHA: 150 ppm, (ST) 200 ppm PEL inhalation; NIOSH: 150 ppm, (ST) 200 ppm REL inhalation; OSHA: 150 ppm PEL inhalation; 710 mg/m³ PEL inhalation

CAS: 141-78-6

Ethyl acetate

Cal/OSHA: 400 ppm PEL inhalation; NIOSH: 400 ppm REL inhalation; OSHA: 400 ppm PEL inhalation; 1400 mg/m³ PEL inhalation

CAS: 67-63-0

Isopropyl alcohol

Cal/OSHA: 400 ppm, (ST) 500 ppm PEL inhalation; NIOSH: 400 ppm, (ST) 500 ppm REL inhalation; OSHA: 400 ppm PEL inhalation; 980 mg/m³ PEL inhalation

Exposure controls

Appropriate engineering controls

Distribution, Workplace and Household Settings: Ensure adequate ventilation. Product Manufacturing Plant (needed at Product-Producing Plant ONLY): Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal protection equipment

Eye and face protection

Depending on the use of this product splash or safety glasses may be worn in an industrial setting. When necessary refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European standard EN166.

Skin protection

Skin Protection: None required with normal household use. Industrial Setting: Protective gloves (for hands) and protective clothing are required where repeated or prolonged skin contact may occur.

Body protection

No special body protection is required for this product under typical use and handling.

Respiratory protection

No respiratory protection is required under typical circumstances of use and handling. If necessary, use only respiratory protection authorized by U.S. OSHA 29 CFR §1920.134, or applicable U.S. local state regulations,

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Transparent Viscous Liquid
Odour	Strong solvent
Odour threshold	50 ppm ethyl acetate 7 – 20 mg/m ³ n-butyl acetate
pH	No data available.
VOC	No data available.
Melting point / freezing point	No data available.

Safety Data Sheet

NailTek Strengthen 3

Initial boiling point and boiling range	77 C (171 F) ethyl acetate
Flash point	- 4 C (24.8 F) ethyl acetate
Evaporation rate	No data available.
Flammability (solid, gas)	Flammable
Upper/lower flammability limits	No data available.
Vapour pressure	100 hPa ethyl acetate
Vapour density	No data available.
Relative density	0.9 – 1.1
Solubilit(ies)	No data available.
Partition coefficient: n-octanol/water (log Know)	0.6 ethyl acetate
Auto-ignition temperature	460 C (860 F) ethyl acetate
Decomposition temperature	No data available.
Viscosity	No data available.
Explosive properties	No data available.
Oxidising properties	No data available.
Specific gravity	0.9 – 1.1

SECTION 10: Stability and reactivity

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Incompatible materials

Acids, Alkalies, and Peroxides

Hazardous decomposition products

If exposed to extremely high temperatures, the products of decomposition may include irritating vapors and carbon oxide gases (e.g. CO₂, CO).

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Not classified

Skin corrosion/irritation

Not classified

Serious eye damage/irritation

Cause serious eye irritation.

Germ cell mutagenicity

Not classified

Carcinogenicity

Not classified

Reproductive toxicity

Not classified

STOT-single exposure

May cause drowsiness or dizziness

Safety Data Sheet

NailTek Strengthen 3

STOT-repeated exposure

Not classified

Aspiration hazard

Not classified

SECTION 12: Ecological information

Toxicity

Harmful to aquatic life with long lasting effects.

Persistence and degradability

No data available.

Bioaccumulative potential

No data available.

Mobility in soil

No data available.

SECTION 13: Disposal considerations

Waste treatment methods

Disposal of the product

Dispose of in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

DOT (US)

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint

IMDG

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint

IATA

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Massachusetts Right To Know Components

Chemical name: Butyl acetate

CAS number: 123-86-4

New Jersey Right To Know Components

Safety Data Sheet

NailTek Strengthen 3

Common name: n-BUTYL ACETATE
CAS number: 123-86-4

Pennsylvania Right To Know Components

Chemical name: Acetic acid, butyl ester
CAS number: 123-86-4

Massachusetts Right To Know Components

Chemical name: Ethyl acetate
CAS number: 141-78-6

New Jersey Right To Know Components

Common name: ETHYL ACETATE
CAS number: 141-78-6

Pennsylvania Right To Know Components

Chemical name: Acetic acid ethyl ester
CAS number: 141-78-6

New Jersey Right To Know Components

Common name: NITROCELLULOSE
CAS number: 9004-70-0

Pennsylvania Right To Know Components

Chemical name: Cellulose, nitrate
CAS number: 9004-70-0

Massachusetts Right To Know Components

Chemical name: Isopropyl alcohol (mfg-strong acid process)
CAS number: 67-63-0

New Jersey Right To Know Components

Common name: ISOPROPYL ALCOHOL
CAS number: 67-63-0

Pennsylvania Right To Know Components

Chemical name: 2-Propanol
CAS number: 67-63-0

SECTION 16: Other information

Full text of hazard statements referenced in Section 2

H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Further information/disclaimer

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR § 1910.1200 and GHS. To the best of A.I.I.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.



AMERICAN INTERNATIONAL INDUSTRIES

Safety Data Sheet Nail Tek Renew Cuticle Oil

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name Nail Tek Renew Cuticle Oil
Product number 55820, 55518, 87-1622, 87-1627

Other means of identification

Uses: Personal Care Product

Details of the supplier of the safety data sheet

Name American International Industries
Address 2220 Gaspar Ave
Los Angeles, CA 90040
USA

Telephone 323-728-2999

Emergency telephone number

Chem-Tel: 1(800) 255-3924

SECTION 2: Hazards identification

General hazard statement

Non Hazardous

Classification of the substance or mixture

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910 1200)

No Pictogram Required
No Hazard Statement Required
No Signal Word Required

Classification according to Regulation (EC) No 1272/2008 (CLP) and OSHA Hazardous Communication Standard 29 CFR §1910.1200.

This product does not meet the criteria for classification in any hazard class according to Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.

Label elements

Safety Data Sheet

Nail Tek Renew Cuticle Oil

Labeling according to Regulation (EC) No 1272/2008 [CLP] and OSHA Hazardous Communication Standard 29 CFR §1910.1200.

This product does not meet the criteria for classification in any hazard class according to Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.

Other hazards

None.

SECTION 3: Composition/information on ingredients

Mixtures

Components

Component	Concentration
Non Hazardous	100 %
CLASSIFICATIONS: Not Classified. HAZARDS: Non Hazardous	

SECTION 4: First aid measures

Description of first aid measures

General notes	Consult a physician. Show this safety data sheet to the doctor in attendance.
Following inhalation	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.
Following skin contact	Wash off with soap and plenty of water.
Following eye contact	Flush eyes with water as a precaution.

SECTION 5: Firefighting measures

Extinguishing media

Use extinguishing media appropriate for surrounding fire. Dry chemical powder, Alcohol-resistant foam, Carbon dioxide (CO₂).

Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. For personal protection see section 8.

Environmental precautions

Small or household quantities may be disposed in sewer or other liquid waste system. For larger quantities check with your local water treatment plant.

SECTION 7: Handling and storage

Safety Data Sheet

Nail Tek Renew Cuticle Oil

Precautions for safe handling

Avoid exposure to skin and eye. Good standards of safe working practice and industrial hygiene should be observed.

Conditions for safe storage, including any incompatibilities

Original packaging units tightly closed at room temperature (below 25C)

SECTION 8: Exposure controls/personal protection

Control parameters

None Known

Exposure controls

Appropriate engineering controls

General industrial hygiene practice.

Personal protection equipment

Eye and face protection

Eye/Face Protection: None required with normal household use. Industrial Setting: For splash protection, use chemical goggles. Eye wash fountain is recommended.

Skin protection

Distribution, Workplace and Household Settings: No special protective equipment required. Product Manufacturing Plant (needed at Product-Producing Plant ONLY): Wear suitable protective clothing.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Hazy oily liquid
Odour	Sweet
Odour threshold	No data
pH	6 - 7
Melting point / freezing point	No data
Initial boiling point and boiling range	No data
Flash point	>160 C (>320 F)
Evaporation rate	No data
VOC	<1%
Flammability (solid, gas)	No data
Upper/lower flammability limits	No data
Vapour pressure	No data
Vapour density	No data
Relative density	No data
Solubility	Negligible in water
Partition coefficient: n-octanol/water	No data
Auto-ignition temperature	No data
Decomposition temperature	No data
Viscosity	No data
Explosive properties	No data
Oxidizing properties	No data
Specific gravity	0.970 – 0.985

Safety Data Sheet

Nail Tek Renew Cuticle Oil

SECTION 10: Stability and reactivity

Reactivity

None under normal use conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal use conditions.

SECTION 11: Toxicological information

Information on toxicological effects**Acute toxicity**

No data available

Skin corrosion/irritation

No data available

Serious eye damage/irritation

May be mildly irritating to eyes

Respiratory or skin sensitization

No data available

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12: Ecological information

Toxicity

No known hazards

SECTION 13: Disposal considerations

Waste treatment methods**Disposal of the product**

Collect all waste in suitable and labeled containers and dispose according to local legislation. Can be recycled.

Safety Data Sheet

Nail Tek Renew Cuticle Oil

SECTION 14: Transport information

DOT (US)

Not regulated

IMDG

Not regulated

IATA

Not regulated

SECTION 15: Regulatory information

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

New Jersey Right To Know Components

No components are subject to the New Jersey Right to Know Act.

Pennsylvania Right To Know Components

No components are subject to the Pennsylvania Right To Know Act.

Safety, health and environmental regulations/legislation specific for the substance or mixture**Toxic Substances Control Act (TSCA) Inventory**

The components of this product are listed on the TSCA Inventory as appropriate.

SARA 311/312 Hazards

No SARA hazards.

CERCLA

None

WHMIS (Canada)

Not subject to WHMIS classification.

SECTION 16: Other information

Further information/disclaimer

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR § 1910.1200 and GHS. To the best of A.I.I.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.